



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 6 Issue: I Month of publication: January 2018 DOI: http://doi.org/10.22214/ijraset.2018.1306

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



# A Survey on Different Techniques for Epilepsy Seizures Detection in EEG

C.V. Banupriya<sup>1</sup>, Dr. D. Deviaruna<sup>2</sup>

<sup>1</sup> PhD Scholar, Dr.NGP Arts and Science College, Department of Computer science, Coimbatore, India <sup>2</sup> Assistant Professor, Dr.NGP Arts and Science College, Department of Computer Applications, Coimbatore, India

Abstract: Epilepsy is a constant neurological disorder of the brain, described by regular seizures, i.e., abnormal activities. Seizures are the most important indication of epilepsy, which is one of the most regular neurological disorders. An electroencephalogram (EEG) is a test out used to evaluate the electrical activity in the brain, and is widely used in the detection and study of epileptic seizures. Hence, it is critical to develop a quantitative method to automatically classify the normal and epileptic brain activities. Several techniques have been developed for straightening out the important features of seizures present in EEGs. In the paper reviews epilepsy recognition algorithms developed in the last decade. In general terms, various techniques based on the wavelet transforms, entropy's, decomposition, wavelet theory, and active analysis are surveyed in the field of epilepsy recognition. A presentation comparison of the reviewed algorithms is also performed. Epilepsy recognition research is oriented to build up non-persistent and accurate methods to allow precise and quick diagnoses. For this point, the occurrence components of the EEG are extracted by using the discrete wavelet transform (DWT) and parametric methods based on autoregressive (AR) model. Both these two feature extraction methods are apply to the input of machine learning classification algorithms such as some Neural Network algorithms, Support Vector Machines (SVM) and k-Means clustering. The need of regularity of the methods in the seizure detection field is an emerging problem that has to be solved to allow homogenous comparisons of detector performance.

Keywords: Epilepsy, EEG, Seizures, DWT, Classification, Performance

## I. INTRODUCTION

Epilepsy is a constant neurological disorder of the brain that affects more or less 50 million people worldwide. According to the World Health Organization (WHO), epilepsy is characterized by frequent seizures, which are objective reactions to abrupt, usually concise, too much electrical discharges in a group of brain cells [1]. In the framework of epilepsy monitoring, two types of seizure have to be considered, namely behavioral and electrographic. A behavioral seizure is defined as the clinical manifestations of epilepsy, as alleged by the patient, seen by an observer, or recorded on video. An electrographic (or electroencephalographic (EEG)) seizure is defined as an abnormal paroxysmal EEG pattern. In several cases, there is dissociation between behavior and EEG signals [2]. In cooperation types of epileptic seizures can happen at all ages. Widespread epileptic seizures can be subdivided into nonexistence (petit mal) and tonic-clonic seizures [3]. In epilepsy the ordinary pattern of neuronal activity becomes disturbed, causing strange feelings, emotions, and behavior, or sometimes convulsions, muscle spasms and loss of consciousness [4]. There are various possible causes of epilepsy. Something that scares the normal sample of neuron activity ranging from infection to brain damage to abnormal brain development can lead to seizures .Epileptic seizures are manifestations of epilepsy [5].

Regular EEG seizure finding, quantification, and recognition have been areas of worry and study within the clinical, physics, and engineering communities since the 1970s. In the most recent couple of years, the EEG analysis was mostly focused on epilepsy seizure detection diagnosis. A seizure detection system can be separated into three stages: data acquisition and preprocessing, processing and feature extraction, and classification.

The rest of the paper is organized in a manner that each block of the classification framework is discussed in a separate section. Section II presents the description of the related methods as well as the EEG data used for the experiment. Finally, the last section provides conclusion of the work.

### **II. RELATED WORK**

Aarabi, R et.al [6], in biomedical signal processing, it is critical to determine the sound and artifacts present in the raw signals so that their power in the feature extraction phase can be minimized. Intracranial EEG (iEEG) signals were band-pass-filtered between 0.5 and 100 Hz to only permit the frequencies of attention and a mark filter was used to remove 50-Hz power line sound. Diffusion and pressure group artifacts were recognized. Segments for which the imitative of the iEEG signal was zero were striking as having



saturation artifacts. Pressure group artifacts were discarded using a threshold; Intracranial EEG divisions containing a signal with amplitude of better than 1.5mV were considered as having pressure group artifacts. H. Adeli et.al [7], a wavelet filter that requires the frequency at ease to be limited to the 0-60 Hz band is used, so the EEG is band limited to the preferred band by convolving with a low-pass finite impulse response (FIR) filter.

S. Tong et.al [8], Independent component analysis (ICA) is particularly used for artifact cancellation. ICA identifies sources; in this case an artifact present in the EEG signal, based on screen source separation (BSS) and separates them from the EEG based on their geometric independence. Varsavsky. I et.al [9], the pre-processing slab also normalizes the signal to make the data equivalent with those recorded by another gaining system or from a dissimilar patient. An example of this is locating all the data in given amplitude range, permitting the signals to be measure up to directly.

S Sigurdsson et.al [10], in time-domain techniques to identify EEG seizures, there is a want to study discrete time sequences of EEG epochs. This study can be expert through histograms of the epochs. Runarsson and Sigurdsson offered a simple time-domain seizure finding method that is based on tracing repeated peaks and minima in the signal part at hand and calculate approximately the histograms for two variables: the amplitude variation and time division between peak values as well as minima. The features used for classification of an epoch as an attack (Seizure) or Non attack are the estimated values of the histogram tubs. The authors used a Machine Learning algorithm SVM Classifier for this assignment and reached an standard sensitivity of about 90% on self-recorded data.

J Yoo et.al [11], one more approach to compact with the EEG seizure recognition method in time domain is to compute the signal force during attack (seizure) and non-seizure periods. An improved treatment to the energy evaluation approach is to guess the energies of the signal sub-bands not the signal as a complete in order to assemble a more discriminative feature Vector. They used a collection of seven band-pass filters wrapping the frequency range from 2 to 26 Hz on eight channels of the development EEG signals. Eight highly active analog channels, classification processor, and a 64-KB SRAM have been incorporated in the SoC. A long-period seizure checking and storage tool was built. The authors used a Support Vector Machine as a classifier with a gain and bandwidth (GBW) controller to complete real-time gain and bandwidth edition to analog front end (AFE) in order to maintain a high accuracy. This classifier is well-matched for the hardware performance. The SoC was tested on CHB-MIT scalp EEG database and it was demonstrated in the existence of a rapid eyeball blink giving an accuracy of 84.4% with  $2.03 \mu$ J/classification power.

A Dalton et.al [12], another approach to pact with time-domain seizure finding is to develop some discriminating data between Seizure (attack) and non-seizure epochs. Developed a body senor network (BSN) that can examine and identify epileptic seizures based on data extracted from time-domain signals .These data include the mean, variance, zero-crossing rate, entropy, and autocorrelation with pattern signals. For autocorrelation evaluation, they adopted a dynamic time warping (DTW) move toward for best position between the signal segments to be tested and the template signal. The authors offered a network to be implanted in wearable kinematic sensors and an N810 Internet tablet. Statistics were recorded from the topics using kinematic sensors such as triaccelerometer, gyroscope, and magnetic sensor for physical movement monitoring. This method was, then, commercially spread and a Body Sensor Network (BSN) was residential on a Mercury platform. The sensitivity of the proposed method for a dataset of 21 seizures (attacks) was found to be 91% with a specificity of 84% and battery life span of 10.5 h.

Dr. P.K. Kulkarni et.al [13], the Fourier transform (FT) methods of repeated EEG processing are based on previous observations that the EEG scale contains some feature waveforms that decrease for the most part within four frequency bands. Such methods have verified positive for different EEG characterizations, but fast Fourier transform (FFT), go through from large noise understanding. Parametric methods for power scale evaluation such as autoregressive (AR), decreases the spectral loss problems and provides better frequency decision. Ever since the EEG signals are non-stationary, the parametric methods are not fitting for frequency decomposition of these signals.

Abdulhamit Subasi, M et.al [14], the exercise of autoregressive (AR) model is study by using utmost likelihood estimation (MLE) also explanation together with the presentation of this method to plow out classifiable features from human EEG by means of Artificial Neural Networks (ANNs). It is noticed that; Artificial Neural Networks classification of EEG signals with AR produced notable results. Their approach is on the basis of the previous where the EEG range enclosed a few characteristic waveforms which reduce mainly within four frequency bands-delta (< 4 Hz), theta (4–8 Hz), alpha (8–14 Hz), and beta (14–30 Hz). For the regular classification of seizures a process is offered as well as achieved a classification rate of 92.3% by resources of a neural network with a single hidden unit as a classifier. The classification results of AR with MLE on test data are over 92%. As a result of using FFT as preprocessing in the neural net an average of 91% classification is achieved.



# International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor :6.887 Volume 6 Issue I, January 2018- Available at www.ijraset.com

Samanwoy Ghosh-Dastidar et al [15], a wavelet-chaos-neural network methodology for classification of electroencephalograms (EEGs) into well and interracial EEG. In sort to decompose the EEG into delta, theta, alpha, beta, and gamma sub-bands the wavelet study is utilized. Three factors are used for EEG representation: standard deviation (quantifying the signal variance), correlation dimension, and largest Lyapunov exponent (quantifying the non-linear chaotic dynamics of the signal). The classification precisions of the following techniques are compared: 1) unsupervised - means clustering; 2) linear-quadratic-discriminant analysis (LQDA); 3) radial-basis-function neural net-work (RBF); 4) Levenberg–Marquardt back propagation neural network (LMBPNN). The research was accepted out in two phases with the goal of minimizing the computing time and output scrutiny, band-specific scrutiny and mixed-band scrutiny. In the second part, over 500 different combinations of mixed-band feature spaces com-prising of promising parameters from part one of the research were examined. It is determined that all the three key components the wavelet-chaos-neural network methodologies are significant for enhancing the EEG classification accuracy. Sensible combinations of parameters and classifiers are essential to entirely discriminate between the three types of EEGs. The result of the methodology evidently let know that a exact mixed-band feature space consist of nine parameters and LMBPNN result in the maximum classification accuracy, a high rate of 96.7%.

William J et.al [16], the effectiveness of utilizing an ANN in order to conclude epileptic seizure occurrences for patients with lateralized bursts of theta (LBT) EEGs. By means of the inspection of records of 1,500 consecutive adult seizure patients training and test cases are achieved. Due to the enlargement of the ANN categorization models the small resulting group of 92 patients with LBT EEGs requisite the usage of a jackknife method. Evaluations of the ANNs are for accuracy, specificity, and sensitivity on categorization of each patient into the exact two-group categorization: epileptic seizure or non-epileptic seizure. By means of eight changeable of the innovative ANN model produced a categorization accuracy of 62%. Accordingly, an adapted factor analysis, an ANN model using just four of the original variables attained a categorization accuracy of 68%.

Donald Yu-Chun Lie et.al [17], begin a neural network algorithm that relies primarily on the point field distribution. Multi Layer Perceptron networks with the amount of input and hidden nodes equal to the amount of channels in the record and a single output node are used. Five bipolar 8 channel records from the EMU with durations ranging from 7.1 to 23.3 min are used for training and testing. Two networks are trained on only the angles of the spike's half-waves, and there is no notion of background environment. The first uses the gradient of the half-wave before the spike's apex for all 8 channels as inputs, and the second uses the gradient after the apex. The output of the algorithm is a slanted combination of the two network outputs with a rate near 1.0 representing a spike has been found. The time (not specified) of the spike half waves is permanent so that no waveform decomposition is required. The algorithm falls along the data one sample at a moment and identifies a point when the output is greater than a threshold value (e.g. 0.9). The method requires a separate network for each patient and spike foci, so 7 networks were trained because two of the patients had autonomous foci. The training required 4–6 example spikes and the non spikes were created by statistical variation resulting in 4 times additional nonspikes. Even though this method does not appear to be well matched for general detection, it might be a hopeful method for finding similar events.

Hojjat Adeli et.al [18], have presented a wavelet methodology for analysis of EEGs and delta, theta, alpha, beta, and gamma subbands of EEGs. In the appearance of the correlation dimensions (CD, representing system complexity) and the largest Lyapunov exponent (LLE, representing system chaoticity) the nonlinear dynamics of the original EEGs are computed. The innovative waveletbased methodology isolated the changes in CD and LLE in specific sub-bands of the EEG. The methodology was valuable to three diverse groups of EEG signals: healthy subjects, epileptic subjects during a seizure-free interval (interictal EEG), and epileptic issues during a seizure (iEEG). The success of CD and LLE in distinguishing between the three groups is observed based on statistical consequence of the variations. It has been noted that in the values of the factors acquired from the original EEG there may not be important differences, differences may be recognized when the factors were employed in conjunction with particular EEG sub-bands and proficient that for the higher frequency beta and gamma sub-bands, the CD distinguished between the three groups, in dissimilarity to that the lower frequency alpha sub-band, the LLE distinguished between the three groups.

M. Akin et.al [19], have attempted to discover a new solution for diagnosing the epilepsy. For this aspire, the Wavelet Transform of the EEG signals have taken, and the delta ( $\delta$ ), theta ( $\theta$ ), alpha ( $\alpha$ ), and beta ( $\beta$ ) sub frequencies are extracted. Depending on these subordinate frequencies an artificial neural network has been residential and trained. The accurateness of the neural network outputs is too elevated (97% for epileptic case, 98% for healthy case, and 93% for pathologic case that have been tested). This means that this neural network identifies the fitness conditions of the patients around as 90 of 100. From this point we can say that purpose of this theoretical study will be supportive for the neurologists when they diagnose the epilepsy.

Ganesan. M et.al [20], proposed a technique for the repeated detection of the points in long term 18 channel human electroencephalograms (EEG) with fewer number of data set. The plan for detecting epileptic and non epileptic spikes in EEG is



## International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor :6.887 Volume 6 Issue I, January 2018- Available at www.ijraset.com

based on a multi resolution, multi-level analysis and Artificial Neural Network (ANN) approach. The signal on every EEG channel is decomposed into six subordinate bands using a non-decimated Wavelet Transform. Each subordinate band is analyzed by using a nonlinear power operator, in order to identify spikes. A factor extraction stage extracts the factors of the detected spikes that can be given as the input to Artificial Neural Network (ANN) classifier. The classification is evaluated on testing data from 81 patients, totaling more than 800 hours of recordings. 90.0% of the epileptic measures were correctly detected and the finding rate of non epileptic seizure events was 98.0%.

Sutrisno et.al [21], have attempt to find the seizure prediction algorithm based on take out Shannon entropy from electroencephalography (EEG) signals. The K-nearest neighbor (KNN) technique is used to constantly monitor the EEG signals by comparing the existing sliding window with normal and pre-seizure baselines to predict the future seizure. Both baselines are always updated based on the most recent prediction result using distance-based (DB) method. This algorithm is capable to predict correctly 42 from 55 seizures (76 %), tested using up to 570 hours EEG taken from the MIT dataset. With its ease and fast processing time, the proposed system can be easily implemented in any embedded system such as in FPGA board or mobile devices.

Alejandro Baldominos et.al [22], have illustrated and implement an power-based seizure detection algorithm which runs over electroencephalography (EEG) signals. Because this technique covers different parameters that significantly affect the recognition performance, we will apply genetic algorithms (GAs) to optimize these parameters in order to get better the detection accuracy. They express the GA setup, including the encoding and fitness function. Finally, we calculate the implemented algorithm with the optimized parameters over a subset of the CHB-MIT Scalp EEG Database, a public data set available in PhysioNet's. Results have shown to be very different, attaining almost ideal accuracy for some patients with very low false positive rate, but failing to correctly detect seizures in others. Thus, the restrictions found for power-based seizure detection are discussed and some measures are proposed to address these issues [22].

Different data mining methods covered in this survey are listed in the following Table.I. The table also includes the approaches employed, the tentative results and the dates and authors of the approaches.

Approach	Algorithms	Experiments	Authors/Dates
wavelet-chaos	wavelet filter	Higher frequency beta and gamma	Ghosh-Dastidar
		sub bands, the CD differentiates	(2007)
		between the three groups, whereas	Aarabi, R. Fazel-
		for the lower frequency alpha sub	Rezai (2009)
		band, the LLE differentiates between	
		the three groups.	
Independent component	Blind Source Separation	Locating all the data in given	S. Tong and N. V.
analysis (ICA)	(BSS)	amplitude range, allowing the signals	Thakor (2009)
		to be compared directly.	Varsavsky (2011)
Time-Domain	Discrete Time Sequences	A support vector machine (SVM)	TP Runarsson, S
		Classifier for this task and achieved	Sigurdsson (2005)
		an average sensitivity of about 90%	
		on self-recorded data	
	Energy Estimation	The SoC was tested on CHB-MIT	J Yoo, L Yan
		scalp EEG database and it was	(2013)
		verified in the presence of a rapid	
		eye blink giving an accuracy of	
		84.4% with 2.03 μJ/classification	
		energy.	
	Body Senor Network	The sensitivity of the proposed	A Dalton, S Patel
	(BSN)	algorithm for a dataset of 21 seizures	(2012)
		was found to be 91% with a	
		specificity of 84% and battery	

 Table I

 List Of Data Mining Techniques Currently Used In Epilepsy Seizures Detection



International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor :6.887 Volume 6 Issue I, January 2018- Available at www.ijraset.com

		lifetime of 10.5 h.	
Fourier Transform	Artificial Neural Networks	The classification percentages of AR	Abdulhamit Subasi
	(ANN)	with MLE on test data are over 92%	(2005)
		As a result of employing FFT as	(2000)
		preprocessing in the neural net an	
		average of 91% classification is	
		attained	
Wavelet-Chaos	Neural Network	The result of the methodology	Samanwoy Ghosh-
wavelet-chaos	Neural Network	clearly let know that a specific	Destider (2007)
		mixed band feature space	Dastidai (2007)
		comprising of nine factors and	
		I MRDNN result in the highest	
		classification accuracy a high value	
		of 96 7%	
Spike Field Distribution	Probabilistic Neural	The algorithm slides along the data	Cabor and Saval
Spike Field Distribution	Network	one complete the time and identifies a	(2010)
	INCLWOIK	one sample at a time and identifies a	(2010)
		spike when the output is greater than	
		a unresnoid.	36.41
wavelet I ransform	Artificial Neural Network	The accuracy of the neural network	M.AKIN,
	(ANN)	outputs is too high.	M.A.Arserim
			(2001)
	Artificial Neural Networks	The system is evaluated on testing	Ganesan.M (2010)
	(ANN)	data from 81 patients, totaling more	
		than 800 hours of recordings. 90.0%	
		of the epileptic events were correctly	
		detected and the detection rate of non	
		epileptic events was 98.0%.	G
Shannon Entropy	K-Nearest Neighbor (KNN)	With its simplicity and fast	Sutrisno (2017)
		processing time this method can be	
		easily implemented in any embedded	
		system such as in FPGA board or	
		mobile devices.	
Energy-Based	Genetic Algorithms	Results have shown to be very	Alejandro
		diverse, attaining almost perfect	Baldominos
		accuracy for some patients with very	(2017)
		low false positive rate, but failing to	
		properly detect seizures in others.	

## **III. CONCLUSIONS**

Evolution in epilepsy detection study follows two main lines. One is the improvement of methods that allow noninvasive and accurate detection for diagnostic applications. The major difficulty to overcome is the presence of artifacts that overlap the signal of interest. The other one is in the neuro stimulation and drug delivery field, where the recording and therapy are necessarily invasive, but the aim is to achieve beginning detection and seizure quantification with maximum accuracy. Another important issue in the epileptic seizure detection field is the need for a standardization of methods. First, the unification of metrics used to evaluate detector performance is needed in order to make homogenous comparisons. Second, some procedure are required for the EEG record type (scalp or intracranial) and as well as the duration of these records (it is not the same testing the detector in a record of a



International Journal for Research in Applied Science & Engineering Technology (IJRASET)

ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor :6.887

Volume 6 Issue I, January 2018- Available at www.ijraset.com

few seconds that in a one of an hour long) used the implementation and testing the algorithms. In general terms, a good epilepsy detector should show at least 80% sensitivity and specificity.

#### REFERENCES

- [1] World Health Organization, 2011. Available: http://www.who.int/mediacentre/?factsheets/fs999/en/.
- [2] J. Gotman, "Automatic detection of seizures and spikes," J. Clin. Neurophysiol., 16: 130-140, 1999
- [3] James, C. J. "Detection of epileptic form activity in the electroencephalogram using the electroencephalogram usingUniversity of Canterbury, Christchurch, 1997.
- [4] J.D. Bronzino, "Biomedical Engineering Handbook", New York: CRC Press LLC, Vol. I, 2nd edition 2000.
- [5] Hojjat Adeli, Samanwoy Ghosh and Dastidat, "Automated EEG Based Diagnosis of Neurological Disorders", CRC Press; 1 edition, 2010
- [6] Aarabi, R. Fazel-Rezai and Y. Aghakhani, "A fuzzy rule-based system for epileptic seizure detection in intracranial EEG," Clin. Neurophysiology, 120: 1648-1657, 2009.
- [7] H. Adeli, S. Ghosh-Dastidar and N. Dadmehr, "A Wavelet-Chaos methodology for analysis of EEGs and EEG sub bands to detect seizure and epilepsy," IEEE Trans. Biomed. Eng., 54: 205-211, 2007
- [8] S. Tong and N. V. Thakor (Ed.), "Quantitative EEG Analysis Methods and Clinical Applications", Norwood: Artech
- [9] Varsavsky, I., Mareels and M. Cook, "Epileptic seizures and the EEG", Boca Raton: CRC Press, 201
- [10] TP Runarsson, S Sigurdsson," On-line detection of patient specific neonatal seizures using support vector machines and half-wave attribute histograms, in The International Conference on Computational Intelligence for Modelling, Control and Automation, and International Conference on Intelligent Agents", Web Technologies and Internet Commerce, pp. 673–677. 28–30 Nov 200
- [11] J Yoo, L Yan, D El-Damak, MA Bin Altaf, AH Shoeb, AP Chandrakasan, "An 8 channel scalable EEG acquisition SoC with patient-specific seizure
- [12] A Dalton, S Patel, AR Chowdhury, M Welsh, T Pang, S Schachter, G Olaighin, P Bonato, "Development of a body sensor network to detect motor patterns of epileptic seizures", IEEE Trans. Biomed. Eng. 59(11), 3204–3211,2012
- [13] Sharanreddy.M and Dr.P.K.Kulkarni, "Review of Significant Research on EEG based Automated Detection of Epilepsy Seizures & Brain Tumor", International Journal of Scientific & Engineering Research, Volume 2, Issue 8, August-2011
- [14] Abdulhamit Subasi, M. Kemal Kiymik, Ahmet Alkan, and Etem Koklukaya, "Neural Network Classification Of EEG Signals By Using AR With MLE Preprocessing For Epileptic Seizure Detection", Journal of Mathematical and Computational Applications, Vol. 10, No. 1, pp. 57-70, 2005
- [15] Samanwoy Ghosh-Dastidar, Hojjat Adeli, and Nahid Dadmehr, "Mixed-Band Wavelet-Chaos-Neural Network Methodology for Epilepsy and Epileptic Seizure Detection", IEEE Transactions On Biomedical Engineering, Vol. 54, No. 9, pp. 1545-1551, September 2007
- [16] Steven Walczak and William J. Nowack,"An Artificial Neural Network Approach to Diagnosing Epilepsy Using Lateralized Bursts of Theta EEGs", Journal of Medical Systems, Vol. 25, No. 1, pp. 9-20, February 2001
- [17] Forrest Sheng Bao, Donald Yu-Chun Lie, and Yuanlin Zhang, "A New Approach to Automated Epileptic Diagnosis Using EEG and Probabilistic Neural Network", in Proceedings of the 2008 20th IEEE International Conference on Tools with
- [18] Hojjat Adeli, Samanwoy Ghosh Dastidar and Nahid Dadmehr, "A Wavelet-Chaos Methodology for Analysis of EEGs and EEG Sub-Bands to Detect Seizure and Epilepsy", IEEE Transactions on Biomedical Engineering, Vol. 54, No. 2, pp. 205-211, February 2007
- [19] M.Akin, M.A.Arserim, M.K.Kiymik, I.Turkoglu, "A New Approach for Diagnosing Epilepsy by using Wavelet Transform and Neural works", Proceedings 23rd Annual Conference – IEEE/EMBS Oct.25-28, 2001
- [20] Ganesan.M, Sumesh.E.P, Vidhyalavanya.R "Multi-Stage, Multi-Resolution Method for Automatic" International Journal of Signal Processing, Image Processing and Pattern Recognition, Vol 3, No 2, June, 2010
- [21] Sutrisno Ibrahim, Ridha Djemal, Abdullah Alsuwailem, and Sofien Gannouni, "Electroencephalography (EEG)-based epileptic seizure prediction using Entropy and K-nearest neighbor (KNN)" Communications in Science and Technology in 2017.
- [22] Alejandro Baldominos, Clara Ram´on-Lozano, "Optimizing EEG Energy-based Seizure Detection using Genetic Algorithms" IEEE in 2017.











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24\*7 Support on Whatsapp)