



IJRASET

International Journal For Research in
Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 10 Issue: V Month of publication: May 2022

DOI: <https://doi.org/10.22214/ijraset.2022.42606>

www.ijraset.com

Call:  08813907089

E-mail ID: ijraset@gmail.com

Design and Fabrication of Multi-Sieve Sand Sieving Machine

Himanshu Meshram¹, Nihal Bawankar², Yash Nikhar³, Danish Khan⁴, Labhesh Petkar⁵, Mohammad Kaif Abdul Aziz⁶, Ubed Khan⁷, Dr. M. Shakebuddin⁸

^{1, 2, 3, 4, 5, 6, 7} Student of Anjuman College of Engineering & Technology, Nagpur, India

⁸ Professor, Dept. of Mechanical Engineering, Anjuman College of Engineering & Technology, Nagpur, India

Abstract: *This paper presents the design and fabrication of a sand sieving machine with multiple sieves that can be changed according to the usage of the work. As we see at every construction site, sand is sieved by old hand-operated (mesh sieving) techniques. Where the siever of a particular size is kept at support from the ground and then sand is poured onto the siever and then manually the sand is sieved by the hand making the sand travel onto the siever and the leftover sediments will be left at one face and the sieved sand will be on another. This technique is time-consuming and for fine sand filtration, it will adequately take a much longer time to sieve. To overcome this problem there are many machines which were designed but only a few of them can be handled at work site. In our design, we use two siever plates which are kept one aside from the other which are hung by the chain of which on end is fixed with the main body. The sievers to which an offset shaft from the motor is attached are to be driven. This offset will create the torsional vibrations with the to and fro motion. This will create the charge particles to get sieved and the leftover charge will move forward and then it will be sieved onto the other siever and the leftover particles will discharge out of the machine. This will reduce the time of sand sieving compared to the hand-operated technique and hence the efficiency and profitability will increase.*

Keywords: *Sand, Sand Sieving Machine, Multi-Sieve, Motor Operated, Two Sieve, Mesh Plate, Screening, Vibrations.*

I. INTRODUCTION

Sand is very commonly used in construction. It also helps in providing bulk, strength, and stability to other materials such as concrete, mortar, render, cement, etc. Sand is also used as a base layer which is known as 'blinding'. It is laid above a layer of hardcore to provide a level, and dry surface for construction works. Sand is an essential element in the field of construction and hence sand has broad usage in various fields. Different size of sand is required for different type of work. At a particular worksite, more than one size of sand is used to complete the work. Similarly, at the construction sites, it is required to use different sizes of sand for different types of work. For plastering the wall, fine sand of range 0.075mm to 0.25mm is used, for finishing, fine graded sand is used. And similarly, the size of sand ranging from 0.25 to 5mm is used for wall reinforcement, grounding, or flooring. And hence it is required to sieve the sand accordingly. To date, majorly, the sand is sieved manually. Hand-operated sieving of sand takes a longer time to sieve the fine grade of sand. And for sieving different sizes of sand, different types of sieves are used, which is a bit tedious work to handle the two-three type of hand-operated sievers at a construction site. If the fine graded sand is required for the job, then it becomes a time-consuming work to sieve the sand because of manual operation are performed for several time to get the fine grade of sand from the coarse sand. To inculcate this problem, we designed and fabricate a multi-sieve sand sieving machine which can be used in any industry where sieving is required, just by changing the sieve plate or mesh plate. Where the multiple sieves can be used to sieve the desire size of sand. Just by changing the sieves, different types of items can also be sieved. This machine can be used in various industries such as marble powder industry, resin industry, etc for sieving the material just by changing the sieve plate accordingly.

II. OBJECTIVES

- 1) To make a machine that can sieve multiple sizes of sand grains depending on the usage at the site
- 2) To reduce the time that is consumed by a manual sand sieving technique
- 3) To increase the efficiency at the work site
- 4) To design and fabricate a machine that can be operated by unskilled labour too
- 5) To develop a machine that can be easily portable from one site to another

III. DESIGN



Figure 1 Design of Multi-Sieve Sand Sieving Machine




Figure 2 Drawing of Multi-Sieve Sand Sieving Machine

IV. CALCULATIONS

1) To find the mass of sand in one tasla (kg)

Volume of tasla having dimensional specification

Inner diameter = 547mm \approx 0.547m

Outer diameter = 525mm \approx 0.525m

Height = 200mm \approx 0.2

\therefore Volume of tasla = $0.03m^3$

<u>CONDITION OF SAND & DENSITY</u> (Density of Building Materials As Per IS 875 Part-1)		
SR NO	CONDITION OF SAND	DENSITY (kg/m ³)
1.	Dry	1540-1600
2.	Wet	1760-2000

Table 1 Condition of Sand & Their Respective Density

$$\text{Density } (\rho) = \frac{\text{Mass } (m)}{\text{Volume } (V)} \quad (\text{kg/m}^3)$$

Case 1 : Condition of sand = Dry

$$\begin{aligned} \therefore \text{Mass of sand} &= 1600 \times 0.03 \\ &= 48 \text{ kg} \sim 50 \text{ kg} \end{aligned}$$

Case 2 : Condition of sand = Wet

$$\begin{aligned} \therefore \text{Mass of sand} &= 2000 \times 0.03 \\ &= 60 \text{ kg} \end{aligned}$$

2) Calculation of lift on sling

$$\text{Tension in each sling} = \frac{\text{Weight}}{\text{Number of legs}} \times \text{L. A. F}$$

Considering weight of sand poured at a time = 50kg

L. A. F for 90° sling angle = 1

$$\therefore \text{Tension in each sling} = \frac{50}{2} \times 1$$

$$\text{Tension in each sling} = 25 \text{ kg}$$

3) Torque calculation

Taking motor of specification 960 rpm , 1 HP

$$1 \text{ HP} = 750 \text{ W}$$

$$\text{Torque } (T) = \frac{\text{Power}}{\omega}$$

$$T = \frac{60 \times P}{2\pi N}$$

$$T = \frac{60 \times 750}{2\pi \times 960}$$

$$T = 7.46 \text{ N.m}$$

4) Machine efficiency (η_{Machine})

$$\text{Power of motor} = 750 \text{ Watt} = 0.75 \text{ KW}$$

$$\text{Power for 1 hr} = 0.75 \times 1 = 0.75 \text{ KWhr}$$

$$\text{Unit Consumption} = 0.75 \text{ units}$$

$$\text{Working for 6 hours a day} = 0.75 \times 6 = \text{units per day}$$

$$\text{One month consumption} = 4.5 \times 30 = 135 \text{ units}$$

$$\text{Approx bill for a month} = 135 \times 10 = ₹1350$$

5) Manpower efficiency (η_{Manpower})

(Considering same amount of work done by the man power as compared to the machine)

$$\text{Daily wages} = ₹200$$

$$\text{Monthly wages} = ₹200 \times 30 = ₹6000$$

(*Note : Even the sand will be sieved by machine but the labour will be required to pour the sand into the machine , but at the same time labour can do another work at the site. This is how the efficiency at the work site will be increased at the same wages.)

6) Power Calculation (P)

$$\text{Power} = \text{Force} \times \text{Velocity}$$

$$\text{Considering velocity} = 0.5 \text{ m per sec}$$

$$\therefore \text{Power} = \text{mass} \times \text{acceleration due to gravity} \times \text{velocity}$$

$$\therefore P = 50 \times 9.81 \times 0.5 \quad \dots (\text{When mass} = 50 \text{ kg})$$

$$\therefore P = 245.25 \text{ watt}$$

$$\text{Taking factor of safety} = 3$$

* (As the conditination sand will change as per the atmosphere)

$$P = 150 \times 9.81 \times 0.5 \quad \dots (\text{When mass} = 150 \text{ kg})$$

$$\therefore P = 735 \text{ watt}$$

\therefore 750 watt motor is suitable for the power transmission

7) Torsional Force in Shaft

(Material of shaft \rightarrow Mild steel)

$$\text{Maximum tensile stress of mild steel } (\sigma_{\text{Tensile}}) = 525 \text{ MPa}$$

$$\text{Maximum shear stress of mild steel } (\sigma_{\text{shear}}) = \frac{525}{1.75} = 300 \text{ MPa}$$

$$\text{Diameter of shaft } (D) = 30 \text{ mm} = 0.03 \text{ m}$$

$$\text{Maximum Torque transmitted by circular shaft } (T_{\text{max}}) = \frac{60 \times P \times K_t}{2\pi N}$$

$$(\text{Taking } K_t = 1.5)$$

$$\therefore T_{\text{max}} = \frac{60 \times 750 \times 1.5}{2\pi N}$$

$$\therefore T_{\text{max}} = 11.2 \text{ N.m}$$

8) Torsional Vibration

$$E = 200 \text{ GN/m}^2 = 200 \times 10^9 \text{ N/m}^2$$

$$D = 30 \text{ mm} = 0.03 \text{ m}, L = 1.5 \text{ m}$$

$$\text{Moment of Inertia } (I) = \frac{\pi}{64} D^4$$

$$I = \frac{\pi}{64} \times 0.03^4 = 3.97 \times 10^{-8} \text{ m}^4$$

Static deflection (δ)

$$\delta = \frac{W a^2 b^2}{3EIL}$$

$$\delta = \frac{50 \times 9.81 \times 0.2^2 \times 1.3^2}{3 \times 200 \times 10^9 \times 3.97 \times 10^{-8} \times 1.5}$$

$$\therefore \delta = 9.256 \times 10^{-4} \text{ m}^4$$

Natural frequency of torsional vibrations (f_n)

$$f_n = \frac{0.4985}{\sqrt{\delta}}$$

$$f_n = \frac{0.4985}{\sqrt{9.256 \times 10^{-4}}}$$

$$f_n = 16.385 \text{ Hz}$$

9) Critical speed of shaft (N_c)

$$N_c = f_n \times 60$$

$$N_c = 16.385 \times 60$$

$$\therefore N_c = 983.07 \text{ rpm}$$

10) Range of speed (N)

$$N = \frac{N_c}{\sqrt{1.16}} \quad \text{or} \quad \frac{N_c}{\sqrt{0.84}}$$


$$N = \frac{983.07}{\sqrt{1.16}} \quad \text{or} \quad \frac{983.07}{\sqrt{0.84}}$$

$$\therefore N = 912.76 \text{ rpm} \text{ \& } N = 1072.617 \text{ rpm}$$

\therefore Range of speed is from 912.76 rpm to 1072.617 rpm

\therefore The selected speed of motor is sufficient to drive the load.

11) Natural frequency of transverse vibrations for a shaft subjected to number of point load (f_n)



Considering,

$$W_1 = 50 \text{ kg} = 50 \times 9.81 = 490.5 \text{ N}$$

$$W_2 = 35 \text{ kg} = 35 \times 9.81 = 343.4 \text{ N}$$

$$W_3 = 20 \text{ kg} = 20 \times 9.81 = 196.2 \text{ N}$$

$$W_4 = 10 \text{ kg} = 10 \times 9.81 = 98.1 \text{ N}$$

By Dunkerley's Method,

$$\frac{1}{f_n^2} = \frac{1}{f_1^2} + \frac{1}{f_2^2} + \frac{1}{f_3^2} + \frac{1}{f_4^2} + \dots + \frac{1}{f_s^2}$$

$$f_n = \frac{0.4985}{\sqrt{\delta_1 + \delta_2 + \delta_3 + \delta_4 + \dots + \delta_s}}$$

δ_s = Static point deflection

$$\delta = \frac{Wa^2b^2}{3EIL}$$

$$\delta_1 = \frac{490.5 \times 0.2^2 \times 1.3^2}{3 \times 200 \times 10^9 \times 3.97 \times 10^{-8} \times 1.5}$$

$$\delta_1 = 9.2801 \times 10^{-4} \text{ m}$$

Similarly,

$$\delta_2 = 2.5178 \times 10^{-3} \text{ m}$$

$$\delta_3 = 1.676 \times 10^{-3} \text{ m}$$

$$\delta_4 = 4 \times 10^{-4} \text{ m}$$

Transverse vibration at each point ,

$$f_n = \frac{0.4985}{\sqrt{\delta}}$$

$$f_1 = \frac{0.4985}{\sqrt{9.2801 \times 10^{-4}}}$$

$$f_1 = 16.364 \text{ Hz}$$

$$f_2 = 9.934 \text{ Hz}$$

$$f_3 = 12.18 \text{ Hz}$$

$$f_4 = 25 \text{ Hz}$$

According to Dunkerley's empirical formula, natural frequency of whole system is given by;

$$f_n = \frac{0.4985}{\sqrt{\delta_1 + \delta_2 + \delta_3 + \delta_4 + \dots + \delta_s}}$$

$$f_n = \frac{0.4985}{\sqrt{9.2801 \times 10^{-4} + 2.5178 \times 10^{-3} + 1.676 \times 10^{-3} + 4 \times 10^{-4}}}$$

$$f_n = 6.7085 \text{ Hz}$$

∴ Natural frequency of transverse vibration of whole system (f_n) = 6.7085 Hz

V. WORKING PRINCIPLE

A single phase 960rpm , 1HP motor is used to drive the shaft. The rotary motion provided by the motor to the main shaft is then connected to the another shaft having an offset which will drive the main sieve frame . The offset is given to the shaft connected with the sieves. This offset will create the torsional vibrations and transverse vibration as it will move back and forth / reciprocating . Due to this back and forth motion on the sieve, the sand will be sieved of the desired size from the mixture of sand.

VI. WORKING

- 1) Charge is poured on to the sieve
- 2) Electric supply is given to the motor.
- 3) Main shaft of the motor is attached further to another shaft which has an offset with main shaft which is connected to the sieves.
- 4) As the motor starts, the driving force will provide the back and forth motion on the sieve which will also experience the torsional vibrations.
- 5) Due to the torsional vibration , transverse vibrations and sliding motion, the charge will experience the motion which will result in meshing the charge from the sieves and the remaining charge will move further.
- 6) The desired sieved charges will then pass through H hopper into the collecting container.

VII. ADVANTAGES

- 1) Simple construction as it is not having any complicated mechanism.
- 2) Easily transported from one site to another as the weight of body is less.
- 3) Parts of the machine can be dismantle and transportation become easier.
- 4) Different types of material can be sieved just by replacing or changing the sieves.
- 5) Economical if produced at large scale.
- 6) No skilled labour is required.
- 7) Low maintenance is required as the machine is not having any complicated mechanism.

VIII. APPLICATION

This machine has a wide application in every filed where sorting of material is required.

- 1) At construction site, sorting of different size of sand for different type of work.
- 2) In agriculture, sorting of particular size of food grain , fruits, etc.
- 3) In metallurgy, sorting of different size of metal powder to refine the efficiency of mixing.
- 4) In food industry, sorting of various size of sugar, salt, food and fruit item.

IX. CONCLUSION

The continuity of the study lies in old traditional method of sand sieving technique with modern methods with the help of machine and motor operated. With the help of this machine, two size / grades of same material can be sieved off and hence reduce the human effort and simultaneously increases the profitability. This machine can be used in various industries just by changing the sieve of the required grade size. As the machine does not have typically constructive mechanism, the maintenance cost of the machine will be low. This sand sieving is portable as the parts of it can be dismantle and can be reassemble at the site easily.

REFERENCES

- [1] Design and Fabrication of multi purpose sieving machine | International Journal of Research in Engineering and Science (IJRES) : Volume 9 Issue 7 | 2021 | PP. 44-49
- [2] Design and Fabrication of Industrial Sand Screening Machine for Green Sand (International Journal of Research in Engineering, Science and Management : Volume-3, Issue-11, November-2020)
- [3] Design and Fabrication of Semi Automated Solar Powered Sand Sieving Machine (International Journal of Engineering Research & Technology (IJERT) : Vol. 8 Issue 11, November-2019)
- [4] Review on Multi level sand screening machine and analysis of vibration mechanism (IJARII : Vol-4 Issue – 3 -2018)
- [5] Design and development of automatic sieving machine for granular/powder materials (Recent Trends in Automation and Automobile Engineering : Volume 4 Issue 1)
- [6] Design construction and testing of dry sand sieving machine (J. Appl. Sci. Environ. Manage. Sept., 2012 : Vol. 16 (3) 241 – 243)
- [7] Review on multipurpose sieving machine (International Journal of Research Publication and Reviews, : Vol 2, no 12, pp 452-455, December 2021)



- [8] Design and fabrication of inclinable trommel sand sieve machine (6th Pacific-Asia Conference on Mechanical Engineering (6th PACME 2017))
- [9] Design and construction of Gari sieving machine (Dama Academic Scholarly Journal of Researchers | Pages: 04-22 Volume 6)
- [10] Design and fabrication of automated sand filter and waste separator machine (International Journal for Research in Applied Science & Engineering Technology (IJRASET) : Volume 9)
- [11] Design, Construction and performance evaluation of a horizontal sand sieving machine and heating machine (Eyere Emagbetere et al. / Advances in Engineering Design Technology : 3, 2021 pp. 86-97)
- [12] Automated Sand Sieving Machine with Three Sieves (JURNAL TEKNIK MESIN INSTITUT TEKNOLOGI PADANG :Vol. 6, No. 1, April 2016)
- [13] Design and development of an electronic sieving for sand separation using Node MCU System (Journal of Modern Mechanical Engineering and Technology, 2021, Vol. 8)
- [14] B.V.Verde, The Green Peristaltic Pump, 16 march 2014.
- [15] Matthew.P.Bowelr, Marco.B.Popovic, Bio Mechatronics, Kinematics and Dynamics, 2019.
- [16] Flahiff Daniel, Aqueduct bike purifies water as you pedal, 08 November 2008.
- [17] Haile Arefayne Shishaye, Design and evaluation of household horizontal slow sand filter, Current Journal of Applied Science and Technology, 01, 2017, pp.01-10.
- [18] Ipton and Josh, Trailer for adult passenger, 4 July 2007, bikeshophub.com.
- [19] Jyoshi Anil Kumar, V.S.Lakshmi Ravuri and V.Harshitha, Fabrication of a solar based sand sieving machine, International Journal of Current Engineering and Scientific Research, 04, 2017, pp.57-60.
- [20] J.Kumar and P.Sachithanandam, Experimental investigation on concrete with partial replacement of scrap rubber to granite stones as coarse aggregate, International Journal of Applied Engineering Research, 09 (22), 2014, pp-5733-5740.
- [21] J.Kumar, K.Sathishkumar and P.Dayakar, Effect of micro silica on high strength concrete, International Journal of Applied Engineering.
- [22] M.Ramarao and B.Mahesh, Design and fabrication of sand filter and separator petal powered, International Journal of Emerging Technologies in Engineering Research, 06 (03), 2018.
- [23] M.N.Nwigbo, J.N.Beredam, G.Dan-Orawari, A.S.Ayodele and H.Itékená, Fabrication and performance evaluation of a mechanical sieve shaker, International Journal of Engineering and Modern Technology, 03, 2017, pp.07-13.
- [24] Priyanka A.Jadhav and Dilip K.Kulkarni, Effect of replacement of natural sand by manufactured sand on the properties of cement mortar, International Journal of Civil and Structural Engineering, 03, 2013, pp.621-628.
- [25] Pranit S.Patil, Shubham S.Jagadale, Akshay G.Phadtare, Swapnil S.Patil, Archana A.Pawar and Rahul P.Suryawanshi, Multipurpose sand screening machine, International Advanced Research Journal in Science, Engineering and Technology, 04, 2017, pp.42-45.
- [26] G.Raja Kumar, M.Achudhan and G.Srinivasa Rao, Studies on corrosion behavior of borated stainless steel (304B) welds, International Journal of Applied Engineering Research, 09 (22), 2014, pp-7767-7772.
- [27] N.Swaminathan, P.Sachithanandam, Risk assessment in construction project, International Journal of Applied Engineering Research, 09 (22), 2014, pp-5552-5557.
- [28] M.M.Sai Karthik, Abhijeet Singh and B.Sandeep, Design and fabrication of sand sieving and cement mixing machine, International Journal of Engineering Science and Computing, 06, 2016, pp.2714-2716.
- [29] Stephen Tambari, G.I.Dan-Orawari, D.S.Aziaka and Ayejah Victor, Design analysis of a reciprocating cassava sieving machine, IOSR Journal of Mechanical and Civil Engineering, 12, 2015, pp.07-15.
- [30] V.Srinivasan, Analysis of static and dynamic load on hydrostatic bearing with variable viscosity and pressure, Indian Journal of Science and Technology, 06 (06), 2014, pp.4777-4782.
- [31] Vaibhawv.Patil, Sand screening and washing machine, International Journal of Innovative Research and Development, 02 (09), 2013, pp.208.
- [32] The analysis and design of pneumatic system by B W Anderson.
- [33] Bhandari V. B., Design of machine elements, eighteenth edition, MC graw-hill Companies, 2003
- [34] Khurmi R. S., Gupta J. k., A textbook of Machine design, first edition, S. chand publication, 1979



10.22214/IJRASET



45.98



IMPACT FACTOR:
7.129



IMPACT FACTOR:
7.429



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24*7 Support on Whatsapp)