



IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 10 Issue: III Month of publication: March 2022 DOI: https://doi.org/10.22214/ijraset.2022.40676

www.ijraset.com

Call: 🕥 08813907089 🔰 E-mail ID: ijraset@gmail.com



# Design and Implementation of Triboelectric Generator for energy generation

Berin Christo. J<sup>1</sup>, Elanthirayan. R<sup>2</sup>

<sup>1, 2</sup>Department of Electrical and Electronics Engineering, St. Joseph's College of engineering, Chennai, India

Abstract: Intelligent electronics, such as smart wearable electronic devices, implantable devices, wireless sensor networks, and so on, have significantly increased the development of renewable and sustainable power sources on a small scale. At the moment, batteries are used to power these electronic devices, which have a limited lifespan and cause environmental issues, and monitoring and replacing all of the batteries used for the wireless sensor networks distributed around the world is a massive and impossible task. Among these novel energy harvesting technologies, the triboelectric nanogenerator (TENG) has demonstrated significant potential to address power issues due to its advantages of high energy-conversion efficiency, high power output, good reliability, low cost, and environmental friendliness. In this paper, we examine the progress made in TENG as a flexible power source.

Keywords: Triboelectric nanogenerators, wireless sensor networks, hybrid energy cells.

#### I. INTRODUCTION

Triboelectric nanogenerators convert mechanical energy harvested from the environment into electricity, which can then be used to power small devices like sensors or to recharge consumer electronics. Except for the fact that piezoelectricity involves permanent electrostatic charge and triboelectricity involves temporary electrostatic charge, triboelectricity is unrelated to piezoelectricity. Triboelectricity is simply the frictional generation of a static electrical charge. The triboelectric effect describes the generation of frictional charge when certain materials are separated from a second material with which they were in contact. The triboelectricity is simply the frictional generation of a static electrical charge. The triboelectric between their surfaces. Triboelectricity is simply the frictional generation of a static electrical charge. The triboelectric effect describes the generation of a static electrical charge. The triboelectric between their surfaces. Triboelectricity is simply the frictional generation of a static electrical charge. The triboelectric effect describes the generation of a static electrical charge. The triboelectric effect describes the generation of frictional charges that occurs when certain materials become electrically charged after being charged.

The triboelectric charge is created by rubbing the two materials together, which increases the contact between their surfaces. The triboelectric effect is thought to be related to the phenomenon of adhesion, in which two materials stick together due to molecular attraction. Adhesion is not a chemical bond between atoms, but rather an electron exchange between different materials.,resulting in They are held together by electrostatic attraction. Friction is caused by the physical separation of adhered materials. Because electron transfer between materials is not immediately reversible, electrons on one material are in excess while electrons on the other are depleted, resulting in one material acquiring positive and the other negative charges. The triboelectric charge on the materials is eventually neutralised by free electrons from the atmosphere, and they return to their neutral uncharged state.

#### **II. WORK DESCRIPTION**

#### A. Triboelectric Effect

A Nanogenerator is a technology that converts mechanical/thermal energy generated by small-scale physical change into electricity. There are three types of nanogenerators: piezoelectric, triboelectric, and pyroelectric. Mechanical energy can be converted into electricity by both piezoelectric and triboelectric nanogenerators. Triboelectric nanogenerators convert mechanical energy harvested from the environment into electricity, which can then be used to power small devices like sensors or to recharge consumer electronics. Using the concept of electrostatic induction and the triboelectric effect, triboelectric nanogenerators can harvest mechanical energy with ease, cost-effectiveness, and robustness.

- B. Methods to generate triboelectric effect
- *1)* Vertical contact separation mode
- 2) Contact sliding mode
- 3) Single electrode mode
- 4) Freestanding mode



#### C. Polydimethylsiloxane

Polydimethylsiloxane (PDMS), also known as dimethylpolysiloxane or dimethicone, is a polymeric organosilicon compound that belongs to the silicone family. Because of its versatility and properties, PDMS is the most widely used silicon-based organic polymer.

#### D. PA6(Nylon6)

It's a polyamide that's semicrystalline. Unlike most other nylons, nylon 6 is formed by ring-opening polymerization rather than condensation polymerization, making it a special case in the comparison of condensation and addition polymers. Nylon 6 is derived from caprolactam, which has six carbons. When caprolactam is heated at 533 K in an inert nitrogen atmosphere for 4-5 hours, the ring breaks and polymerization occurs. The molten mass is then passed through spinnerets to form nylon 6 fibres.

#### **III. EQUATIONS FOR THE NANOGENERATOR**

A. Maxwell's equation for nanogenerators

$$\nabla . D = \rho$$

$$\nabla . B = 0$$

$$\nabla \times E = -\frac{\partial B}{\partial t}$$

$$\nabla \times H = J + \frac{\partial D}{\partial t}$$

$$J_D = \frac{\partial D}{\partial t} = \epsilon \frac{\partial E}{\partial t}$$

$$J_D = \frac{\partial D}{\partial t} = \epsilon \frac{\partial E}{\partial t} + \frac{\partial P_s}{\partial t}$$

$$\epsilon \nabla . E = \rho - \nabla . P_s$$

$$\nabla . B = 0$$

$$\nabla \times E = -\frac{\partial B}{\partial t}$$

$$\nabla \times H = J + \epsilon \frac{\partial E}{\partial t} + \frac{\partial P_s}{\partial t}$$

#### B. General theory for the polarisation Ps

The polarization Ps created by the electrostatic surface charges can be expressed by the following equation, when defining the charge density function  $\sigma s(r,t)$  on the media surface by a shape function of f(r, t) = 0.

Δ

$$\nabla P_s = -\sigma_s(r,t)\delta(f(r,t))$$

where the delta function  $\delta(f(\mathbf{r},t))$  is introduced to confine the media shape. Through solving the scalar electric potential from the surface charges

$$\begin{split} \emptyset_{s}(r,t) &= \frac{1}{4\pi} \int \frac{\sigma_{s}(r',t')}{|r-r'|} \\ P_{s} &= -\nabla \emptyset_{s}(r,t) \\ &= \frac{1}{4\pi} \int \sigma_{s}(r',t') \frac{r-r'}{|r-r'|^{2}} ds' + \frac{1}{4\pi c} \int \frac{\partial \sigma_{s}(r'',t')}{\partial t'} \frac{r-r'}{|r-r'|^{2}} ds' \end{split}$$



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 10 Issue III Mar 2022- Available at www.ijraset.com

C current transport equation for nanogenerators

#### **IV. FULL BRIDGE RECTIFIER**

The V–Q plot and the direct charging cycle's physical process The V-Q plot (a). The system's circuit diagram is shown in the inset of a. The dashed lines in a represent the cycle with the greatest energy output and the least resistance. (b) The physical process's schematic diagrams. The diodes drawn with solid and dashed lines in b represent the on and off states, respectively. (c)The direct charging cycles (the second and subsequent cycles) for various charging voltages.



Fig 1.V-I characteristics of Teng





Fig 3.Designed charging cycle



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 10 Issue III Mar 2022- Available at www.ijraset.com

#### V. SOFTWARE

#### A. Comsol Multiphysics

Polydimethysiloxane

Α.

The COMSOL Multiphysics® software brings a user interface and experience that is always the same, regardless of engineering application and physics phenomena. Add-on modules provide specialized functionality for electromagnetics, structural mechanics, acoustics, fluid flow, heat transfer, and chemical engineering.Choose from a list of Live Link products to interface directly with CAD and other third-party software. Deploy simulation applications with COMSOL Compiler<sup>™</sup> and COMSOL Server,

- 1) General-purpose simulation software based on advanced numerical methods.
- 2) Fully coupled Multiphysics and single-physics modelling capabilities.
- *3)* Complete modelling workflow, from geometry to postprocessing.
- 4) User-friendly tools for building and deploying simulation apps.

Engineers and scientists use the COMSOL Multiphysics® software to simulate designs, devices, and processes in all fields of engineering, manufacturing, and scientific research. COMSOL Multiphysics® is a simulation platform that provides fully coupled Multiphysics and single-physics modelling capabilities. The Model Builder includes all of the steps in the modelling workflow — from defining geometries, material properties, and the physics that describe specific phenomena to solving and postprocessing models for producing accurate results.

When you have developed a model, you can use the Application Builder to turn it into a simulation application with a dedicated user interface that can be used by collaborators and customers who are not experts in simulation software. To help keep your models and applications organized, the COMSOL Multiphysics® platform also includes the Model Manager, which is a tool for simulation data management that provides version control and efficient storage.

#### VI. MATERIAL SELECTION AND PROPERTIES

Set Recta	tings angle Jild Selected 👻 📕 Build All Objects 🐚	~ #
Label:	PDSM (bottom layer)	
• 0	bject Type	
Type:	Solid	•
▼ Si	ze and Shape	
Width	: 100	nm
Heigh	t: 5	nm
▼ Pc	osition	
Base:	Corner	-
x:	-100	nm
y:	0	nm
▼ Ro	otation Angle	



Mat	erial							
abel	I: Air							
G	eometric Entity	Selection						
eon	netric entity level:	Domain						,
elec	tion:	Manual						,
	2 3 4 5 6							
C N	Iverride Aaterial Propertie	5						
N N	override Aaterial Propertie Aaterial Contents	5						
N	Override Material Propertie Material Contents Property	5	Variable	Value	Unit	Property group		
C N	Verride Aaterial Propertie Aaterial Contents Property Relative permittiv	rs ;	Variable epsilonr_i	Value 1	Unit 1	Property group Basic		
N	Verride Aaterial Propertie Aaterial Contents Property Relative permittiv Coefficient of the	es ; ity rmal expansion	Variable epsilonr_i alpha_iso	Value 1 alpha_p(pA,	Unit 1 1/K	Property group Basic Basic		
C N	Verride Aaterial Propertie Aaterial Contents Property Relative permittiv Coefficient of the Mean molar mass	es ity mmal expansion	Variable epsilonr.j alpha.jso Mn	Value 1 alpha_p(pA 0.02897[kg/	Unit 1 1/K kg/mol	Property group Basic Basic Basic		
C N	Aterial Propertie Aaterial Contents Property Relative permittin Coefficient of the Mean molar mass Bulk viscosity	es ity mal expansion	Variable epsilonr_i alpha_iso Mn muB	Value 1 alpha_p(pA 0.02897[kg/ muB(T)	Unit 1 1/K kg/mol Pa-s	Property group Basic Basic Basic Basic		
C N	Vverride Aaterial Propertie Aaterial Contents Property Relative permittiv Coefficient of the Mean molar mass Bulk viscosity Relative permeab	es ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;	Variable epsilonr_i alpha_iso Mn muB mur_iso;	Value 1 alpha_p(pA, 0.02897[kg/ muB(T) 1	Unit 1 1/K kg/mol Pas 1	Property group Basic Basic Basic Basic Basic		
C N	Aaterial Propertie Aaterial Contents Property Relative permittiv Coefficient of the Mean molar mass Bulk viscosity Relative permeab Dynamic viscosity	ity iny imal expansion i ility	Variable epsilonr_i alpha_iso Mn mu8 mur_iso; mu	Value 1 alpha_p(pA 0.02897[kg/ muB(T) 1 eta(T)	Unit 1 1/K kg/mol Pas 1 Pas	Property group Basic Basic Basic Basic Basic Basic Basic		
C N	Aaterial Propertie Aaterial Contents Property Relative permittiv Coefficient of the Mean molar mass Bulk viscosity Relative permeab Dynamic viscosity Ratio of specific t	ts i ity mmal expansion i ility easts	Variable epsilonr_j alpha_iso Mn muB mur_iso ; mu gamma	Value 1 alpha_p(pA 0.02897[kg/ muB(T) 1 eta(T) 1.4	Unit 1 1/K kg/mol Pas 1 Pas 1 Ras 1	Property group Basic Basic Basic Basic Basic Basic Basic		
	Verride Aaterial Propertie Aaterial Contents Property Relative permittiv Coefficient of the Goefficient of the Goefficient of the Mean molar mass Bulk viscosity Relative permeabl Dynamic viscosity Ratio of specific h Electrical conduct	ity mail expansion ii iiity easts iivity	Variable epsilonr_j alpha_iso Mn muB mur_iso; mu gamma sigma_is	Value 1 alpha_p(pA 0.02897[kg/ muB(T) 1 eta(T) 1.4 0[S/m]	Unit 1 1/K kg/mol Pas 1 Pas 1 S/m	Property group Basic Basic Basic Basic Basic Basic Basic Basic		
	Verride Aaterial Propertie Aaterial Contents Relative permitti Coefficient of the Mean molar mass Bulk viscosity Relative permeab Dynamic viscosity Ratio of specific t Electrical conduct Heat capacity at d	ity ity mrail expansion it itity neats ivity roctant pressure	Variable epsilonr_j atpha_iso Mn muB mur_iso ; mu gamma sigma_is Cp	Value 1 alpha_p(pA	Unit 1 1/K kg/mol Pa-s 1 1 Pa-s 1 5/m J/(kg-K)	Property group Basic Basic Basic Basic Basic Basic Basic Basic Basic		
C N	Verride Aaterial Propertie Aaterial Contents Property Relative permittiv Coefficient of the Mean molar mass Bulk viscosity Relative permeab Dynamic viscosity Ratio of specific P Electrical conduct Heat capacity at o Density	ity ity ity ity itity itity meats ivity vonstant pressure	Variable epsilonr,i alpha,iso Mn mut_iso; mu gamma sigma_is Cp rho	Value 1 alpha_p(pA	Unit 1 1/K kg/mol Pas 1 Pas 1 S/m J/(kg-K) kg/m <sup>3</sup>	Property group Basic Basic Basic Basic Basic Basic Basic Basic Basic Basic Basic		
· N	Aterial Propertie Aaterial Propertie Aaterial Contents Property Relative permittie Coefficient of the Mean molar mass Bulk viscosity Relative permeab Dynamic viscosity Relative permeab Dynami	its in the second secon	Variable epsilonr, j alphajso Mn muB murjso mu gamma sigma, js Cp tho k.jso; kli	Value 1 alpha.p(pA 02897[kg/ muB(T) 1 eta(T) 1.4 0[S/m] Cp(T) ho(pA,T) k(T)	Unit 1 1/K kg/mol Pa-s 1 Pa-s 1 S/m J/kg-K) kg/m <sup>3</sup> W/(m-K)	Property group Basic Basic Basic Basic Basic Basic Basic Basic Basic Basic Basic Basic Basic		
· N	Aterial Propertie Aterial Propertie Aterial Contents Property Relative permittie Coefficient of the Mean molar mass Bulk viscosity Relative permeab Dynamic viscosity Ratio of specific to Electrical conduct Density Thermal conduct Speed of sound	ity ity mail expansion it ity meats ivity constant pressure ivity	Variable epsilonr_i_ alpha_iso Mn mur_iso mu gamma sigma_is Cp rho k_iso_kli c	Value 1 alpha.p(pA. 0.02897/lg/ muB(T) 1 eta(T) 1.4 0(S/m] Cp(T) rho(pA,T) k(T) cq(T)	Unit 1 1/K kg/mol Pa-s 1 Pa-s 1 S/m J/(kg-K) kg/m <sup>3</sup> kg/m <sup>3</sup> w/(m-K) m/s	Property group Basic Basic Basic Basic Basic Basic Basic Basic Basic Basic Basic Basic Basic Basic		

Fig 5.Dimension of Polydimethysiloxane



### International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 10 Issue III Mar 2022- Available at www.ijraset.com

Sett	ings	~ #
Recta	ingle ild Selected 👻 🛢 Build All Objects 🐚	
Label:	PA6 Nylon (top)	<b>_</b>
• Ob	oject Type	
Type:	Solid	•
▼ Siz	e and Shape	
Width:	100	nm
Height	5	nm
▼ Po	sition	
Base:	Corner	•
x:	-100	nm
y:	Y1+50	nm

#### Fig 6. Material property of PA6

Set	tings							*
Mate	erial							
Label	PDMS - Polydin	nethylsiloxane					E C	1
G	eometric Entity	Selection						
Geon	etric entity level:	Domain						
Selec	tion	Manual					-	
D C	7 8 Iverride Material Propertie	15						
* N	taterial Contents	1						
*	Property Relative permittiv Coefficient of the Heat capacity at a Density Thermal conducti Young's modulus	ity rmal expansion constant pressure vity	Variable epsilonr_i alpha_iso Cp rho k_iso; kli E	Value 2.75 9e-4[1/K] 1460[J/(kg* 970[kg/m^3] 0.16[W/(m* 750[kPa]	Unit 1 1/K J/(kg/K) kg/m <sup>3</sup> W/(mK) Pa	Property group Basic Basic Basic Basic Basic Basic Young's modulus and	Poisson's r	
	Poisson's ratio		nu	0.49	1	Young's modulus and I	Poisson's r	

Fig 7.Dimension of Polycaprolactam(PA6)

#### C. Material selection for Triboelectric effect





International Journal for Research in Applied Science & Engineering Technology (IJRASET) ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538

Volume 10 Issue III Mar 2022- Available at www.ijraset.com

#### VII. SIMULATION RESULTS

COMSOL Multiphysics have been instrumental in simulating triboelectric effect now let us see the simulation working and result The materials chosen are PDMS and PA6 due to their high positive and negative polarity.

Name	Expression	Value	Description
Y1	0.1[nm]	1E-10 m	

Fig 9. Initial parameters

<ul> <li>Size</li> </ul>	and Shape	
Width:	100	nm
Height:	5	nm

Fig 10.Dimensions of material



Fig 11.Simulation Diagram of Triboelectric generator

Parameter	name	Parameter value list	Parameter unit
Y1 vialineter hanne		range(0.1,-5,-45)	nm

Fig 12.Vertical Displacement



Fig 13.Result of Triboelectric Nanogenerator



Volume 10 Issue III Mar 2022- Available at www.ijraset.com

Message	$_{\rm es}$ $ imes$	Progress	Log	Table	1 X		
8.85 e-12	лито 8.5 е-1	850 0.85 e-1		1	i.	D	Ŧ
Y1 (nm)	Electr	ic potential	(V)				
-10.000	14.667						
-15.000	13.036						
-20.000	11.288						
-25.000	9.4083						
-30.000	7.3749						
-35.000	5.1604						
-40.000	2.7256						
		-					

Fig 14. Voltage Generated from Teng



Fig 15.Voltage Generation from Teng



Fig 16.Simulation before contact



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 10 Issue III Mar 2022- Available at www.ijraset.com



566



ISSN: 2321-9653; IC Value: 45.98; SJ Impact Factor: 7.538 Volume 10 Issue III Mar 2022- Available at www.ijraset.com

#### VIII. CONCLUSION

Finally, a flat-surfaced C-PDMS/PA6 TENG with greatly improved triboelectric performance was successfully fabricated using elaborately selected conductive carbon tape as electrodes. With an output voltage of 1760 V, a short-circuit current density of 240 mA m-2, and a maximum power density of 120 W m-2 in ambient conditions, the C-PDMS/PA6 TENG outperforms the micro-/nano-structure patterned, chemical functionalized, and charge injected TENGs. This research presents a promising simple and low-cost strategy for selecting and preparing electrode materials with special micro/nanostructures to interact with triboelectric layers to generate additional triboelectric charges for high-performance applications. performance TENGs. In addition, in consideration of the flexibility and anti-corrosive.

Triboelectric effect and triboelectric nanogenerator simulation and generation are completed. I learned COMSOL Multiphysics software and used it to simulate the triboelectric effect quality; carbon electrode-based TENGs have a broader application potential than other types of TENGs.

#### REFERENCES

- [1] I.Hussain et al., "Flexible Triboelectric Nanogenerator Based on Paper, PET and Aluminum," 2019 2nd International Conference on Computing, Mathematics and Engineering Technologies (iCoMET). IEEE, Jan. 2019. doi: 10.1109/icomet.2019.8673395.
- [2] U. Tronco Jurado, S. H. Pu, and N. M. White, "Dielectric-Metal Triboelectric Nanogenerators for Ocean Wave Impact Self-Powered Applications," IEEE Sensors Journal, vol. 19, no. 16. Institute of Electrical and Electronics Engineers (IEEE), pp. 6778–6785, Aug. 15, 2019. doi: 10.1109/jsen.2019.2912070.
- [3] M.-H. Liao, C.-C. Wu, W.-J. Su, S.-C. Chen, and M.-H. Lee, "The for the Device Performance in Triboelectric Nanogenerators," IEEE Transactions on Electron Devices, vol. 66, no. 10. Institute of Electrical and Electronics Engineers (IEEE), pp. 4478–4480, Oct. 2019. doi: 10.1109/ted.2019.2933697.
- [4] J. Li et al., "Triboelectric nanogenerators enabled internet of things: A survey," Intelligent and Converged Networks, vol. 1, no. 2. Institute of Electrical and Electronics Engineers (IEEE), pp. 115–141, Sep. 2020. doi: 10.23919/icn.2020.0008.
- [5] S. A. Shankaregowda, C. B. Nanjegowda, X.-L. Cheng, M.-Y. Shi, Z.- F. Liu, and H.-X. Zhang, "A Flexible and Transparent Graphene- Based Triboelectric Nanogenerator," IEEE Transactions on Nanotechnology, vol. 15, no. 3. Institute of Electrical and Electronics Engineers (IEEE), pp. 435–441, May 2016. doi: 10.1109/tnano.2016.2540958.
- [6] M. El-Mouloud Zelmat, M. Rizouga, A. Tilmatine, K. Medles, M. Miloudi, and L. Dascalescu, "Experimental Comparative Study of Different Tribocharging Devices for Triboelectric Separation of Insulating Particles," IEEE Transactions on Industry Applications, vol. 49, no. 3. Institute of Electrical and Electronics Engineers (IEEE), pp. 1113–1118, May 2013. doi: 10.1109/tia.2013.2251991.
- [7] J. He, Y. Liu, D. Li, K. Yao, Z. Gao, and X. Yu, "Stretchable Triboelectric Nanogenerators for Energy Harvesting and Motion Monitoring," IEEE Open Journal of Nanotechnology, vol. 1. Institute of Electrical and Electronics Engineers (IEEE), pp. 109–116, 2020. doi: 10.1109/ojnano.2020.3019425.
- [8] G. Min, L. Manjakkal, D. M. Mulvihill, and R. S. Dahiya, "Triboelectric Nanogenerator With Enhanced Performance via an Optimized Low Permittivity Substrate," IEEE Sensors Journal, vol. 20, no. 13. Institute of Electrical and Electronics Engineers (IEEE), pp. 6856–6862, Jul. 01, 2020. doi: 10.1109/jsen.2019.2938605.
- [9]K. Xia, Z. Zhu, H. Zhang, C. Du, R. Wang, and Z. Xu, "High Output<br/>Sensing System," IEEE Transactions on<br/>Nanotechnology, vol. 17, no. 6. Institute of Electrical and ElectronicsPoweredHeight<br/>Engineers1223, Nov. 2018.doi:n10.1109/tnano.2018.2869934.electronicsEngineersElectronics
- [10] W. Wang, X. Feng, K. Wang, and L. Li, "Triboelectric Nanogenerator: A Hope to Collect Blue Energy," 2019 4th International Conference on Control, Robotics and Cybernetics (CRC). IEEE, Sep. 2019. doi: 10.1109/crc.2019.00040.
- [11] Engineers (IEEE), pp. 435–441, May 2016. doi: 10.1109/tnano.2016.2540958.
- M. El-Mouloud Zelmat, M. Rizouga, A. Tilmatine, K. Medles, M. Miloudi, and L. Dascalescu, "Experimental Comparative Study of Different Tribocharging Devices for Triboelectric Separation of Insulating Particles," IEEE Transactions on Industry Applications, vol. 49, no. 3. Institute of Electrical and Electronics Engineers (IEEE), pp. 1113–1118, May 2013. doi: 10.1109/tia.2013.2251991.
- [13] J. He, Y. Liu, D. Li, K. Yao, Z. Gao, and X. Yu, "Stretchable Triboelectric Nanogenerators for Energy Harvesting and Motion Monitoring," IEEE Open Journal of Nanotechnology, vol. 1. Institute of Electrical and Electronics Engineers (IEEE), pp. 109–116, 2020. doi: 10.1109/ojnano.2020.3019425.
- [14] G. Min, L. Manjakkal, D. M. Mulvihill, and R. S. Dahiya, "Triboelectric Nanogenerator With Enhanced Performance via an Optimized Low Permittivity Substrate," IEEE Sensors Journal, vol. 20, no. 13. Institute of Electrical and Electronics Engineers (IEEE), pp. 6856–6862, Jul. 01, 2020. doi: 10.1109/jsen.2019.2938605.
- [15] K. Xia, Z. Zhu, H. Zhang, C. Du, R. Wang, and Z. Xu, "High Output Compound Triboelectric Nanogenerator Based on Paper for Self-Sensing System," IEEE Transactions on Nanotechnology, vol. 17, no. 6. Institute of Electrical and Electronics Engineers (IEEE), pp. 1217–1223, Nov. 2018. doi:n10.1109/tnano.2018.2869934.
- [16] W. Wang, X. Feng, K. Wang, and L. Li, "Triboelectric Nanogenerator: A Hope to Collect Blue Energy," 2019 4th International Conference on Control, Robotics and Cybernetics (CRC). IEEE, Sep. 2019. doi: 10.1109/crc.2019.00040.











45.98



IMPACT FACTOR: 7.129







INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089 🕓 (24\*7 Support on Whatsapp)