



IJRASET

International Journal For Research in
Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 12 **Issue:** VI **Month of publication:** June 2024

DOI: <https://doi.org/10.22214/ijraset.2024.63265>

www.ijraset.com

Call:  08813907089

E-mail ID: ijraset@gmail.com

Protective Measures from the Interference of Confining Animals to Farm Site

Mohd Vasique Hussain¹, Anshika Pandey², Arpita Singh Gond³

¹Faculty, ^{2,3}U.G Student, College Of Agricultural Engineering, J.N.K.V.V, Jabalpur, India

Abstract: A farm producing grains, vegetables and crops are required to be protected from unwanted interference of animals. It is necessary to demarcate the boundary between farms. Due to non-hindrance the crops are damaged by the roaming animals resulting in severe loss of manpower and money.

The research is aimed to resolve such consequences by the use of fencing at farm site. For the research purpose agricultural farm of College of Agricultural Engineering is considered.

A design of fencing is proposed as a protective measure and cost estimation is done to analyse the approximate cost for the designed fencing.

Keywords: Agriculture, farm, fencing, barbed wire, cost estimation.

I. INTRODUCTION

Fencing is a barrier extensively used for the protection of farms from the animals keeping them out of a particular area. India is an agricultural based country and most of the people are dependent on agriculture for their survival.

A agricultural land is highly susceptible to the roaming animals, large amount of crops are damaged and gets wasted by their activities.

Therefore a farm producing crops, grains or vegetables uses fencing to keep stray or wild animals away from the farm. Fencing may also be used to distinguish the boundary region between different farms. Various types of fencing are available but the selection of fencing is governed by its type and purpose of usage. Earth or masonry wall, dead or live hedges, ditches etc. are commonly used as fencing in India.

From the serviceability and feasibility point of view most of these fences are not effective on a permanent basis.

Wire fencing are getting employed on many large size mechanised farm. This fencing is proved to be most effective and depending on the construction and material there are various classification such as:

- 1) *Woven Mesh Type:* these are mostly used in general farms than any other type. These are suitable for large animals, cattle, buffaloes etc. They are properly galvanized and weather protected wires.
- 2) *Closed Mesh Type:* These may be considered as an ideal for poultry houses. The horizontal wires are made heavier than the vertical wire and are wrapped around the horizontal wires.
- 3) *Barbed Wire:* these are available in various standard sizes to meet the functional requirement. It generally made of two strands twisted together with one or two bits of wire wrapped around the strands. They are generally composed of plain and barbed wire alternately or the entire fence is made of barbed wire.
- 4) *Electric Fencing:* It consists of one or more strands of bare wire supported by insulators and connected to controller to form a barrier. It works on high voltage current between the fence wire and the earth. It is mainly used for confining dairy cattle.

II. METHODOLOGY

Site Selection: It is situated at College of Agricultural Engineering Jabalpur. The farm is a fertile land and is used for crop production. Due to interference of roaming animals the crops gets affected and sometimes damage therefore to avoid such circumstances a fencing system is proposed.



The fencing proposed for the farm site is barbed wire fencing. The barbed wire proposed is of 14 gauges. The pacing between the barbs used is between 7.5 cm to 15 cm. The length of wire available is of 160 m long. The height of fencing is taken as 1.8m having following properties:

Table 1: Wire Specification

| Ground and First wire | and | Frist and second wire | and | Second and third wire | and | Third and fourth wire | and | Fourth and fifth wire | and | Fifth and top wire |
|-----------------------|-----|-----------------------|-----|-----------------------|-----|-----------------------|-----|-----------------------|-----|--------------------|
| 15 cm | | 15 cm | | 15 cm | | 22.5 cm | | 30 cm | | 30 cm |

High angle iron posts are proposed for the barbed wire fence. These steel angles iron post are 1.8 m long and are supplied with pre-drilled holes for the line wire to go through.

III. CALCULATION

Area of farm = 4 hac.

Hence length of one side of square farm = 200 m

Perimeter of farm = 4 x 200 = 800 m

Assuming 1.8 m high angle post spaced 3 m apart with barbed wire of six lines.

Total number of post = 800/3 = 267 nos.

Cost of post @ Rs 70/post = Rs 18690/-

Cost of 4 corner post at Rs 125/post = 125 x 4 = Rs 500/-

Total length of barbed wire = 800 x 6 = 4800 m

Cost of wire @ Rs 250 / m = Rs 12000/-

Volume of earthwork for digging work of 267 pits = 267 x ¼ x ¼ x ½ = 8.34 m³

Cost of earthwork @ Rs 2/pit = 2 x 267 = Rs 534/-

Cost of concrete @ Rs 10/pit and filling = 267 x 10 = Rs 2670/-

Labour charge = Rs 2000/-

Cost of iron gate = Rs 2500/-

Table 1: Quantitative description of farm fence

| S.No | Description | Rate applied @ | Amount (Rs) |
|-------|-------------------------|----------------|-------------|
| 1 | Cost of straight post | Rs.70/post | 18690/- |
| 2 | Cost of corner post | Rs.125/post | 500/- |
| 3 | Cost of iron gate | Approximate | 2500/- |
| 4 | Cost of barbed wire | Rs.250/m | 12000/- |
| 5 | Cost of earth work | Rs.2/pit | 534/- |
| 6 | Cost of cement concrete | Rs.10/ pit | 2670/- |
| 7 | Labour charges | Approximate | 2000/- |
| Total | | | 38894/- |



IV. RESULT AND DISCUSSION

The total cost of fencing was found to be Rs.38894/- for 4 hectare of farm land, therefore the cost of fencing per running meter was Rs.48.62 / metre. The above fencing may be adopted for safety and security of farm from the roaming animals. The proposed design may be used for other farms and calculation may be used for finding the required design for different farm sites. The cost estimation may be used to get an approximate idea for analysis of amount to be required for adopting such method.

REFERENCES

- [1] T.P. Ojha, A.M. Michael "Principles of Agricultural Engineering Volume -1" Jain Brothers Publication, New Delhi
- [2] G K Mensuro, ZEF Manh Quyet Vu, ZEF c December 2009 Bonn Interdisciplinary Graduate School for Development Research.
- [3] W. Thomas, 'Electrical Fences poses a Threat' 2017
- [4] Doyle Y, Conroy R. Childhood farm accidents: A continuing cause for concern. Journal of the Society of Occupational Medicine 1989; 39(1): 35-37.
- [5] Farmsafe Australia. Child safety on farms: A framework for a national strategy. Moree: Farmsafe Australia, 1999.
- [6] Fragar L, Gibson C, Henderson A, Franklin R. Farmsafe Farms for Kids: Evidence Based Solutions for Child Safety on Australian Farms. Moree: Australian Centre for Agricultural Health and Safety, 2003
- [7] Hafez, E.S.E., Bouissou, M.F., 1975. The behaviour of cattle. In: Hafez, E.S.E. (Ed.), the Behaviour of Domestic Animals. Williams and Wilkins, Baltimore.



10.22214/IJRASET



45.98



IMPACT FACTOR:
7.129



IMPACT FACTOR:
7.429



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24*7 Support on Whatsapp)