



IJRASET

International Journal For Research in
Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 12 **Issue:** XII **Month of publication:** December 2024

DOI: <https://doi.org/10.22214/ijraset.2024.66029>

www.ijraset.com

Call:  08813907089

E-mail ID: ijraset@gmail.com

Stress Detection using Machine Learning and Deep Learning

Sunil Kumar Rawat¹, Ankit Kumar²

Dr. M.C. Saxena College of Engineering and Technology, Lucknow, India

Abstract: *Stress is a regular phenomenon in modern day international, and it causes human beings to respond to a selection of things, resulting in physiological and behavioral adjustments. If we maintain stress in our minds for too lengthy, it's going to have an effect on our our bodies.*

Many health situations related to pressure can be prevented if pressure is detected sooner. while a person is burdened, a sample may be detected the usage of various bio-signals such as thermal, electrical, impedance, acoustic, optical, and so forth, and stress degrees may be recognized the usage of these bio-indicators.

This paper makes use of a dataset that was obtained the use of a web of things (IOT) sensor, which brought about the gathering of records about a real-lifestyles state of affairs involving a person's intellectual fitness.

To achieve a pattern for strain detection, information from sensors inclusive of the Galvanic pores and skin reaction Sensor (GSR) and the Electrocardiogram (ECG) had been amassed.

The dataset will then be categorised the use of Multilayer Perceptron (MLP), choice Tree (DT), okay-Nearest Neighbor (KNN), assist Vector system (SVM), and Deep getting to know algorithms (DL).

Accuracy, precision, don't forget, and F1-rating are used to assess the statistics's performance. ultimately, selection Tree (DT) had the first-class performance where DT have accuracy 95%, precision ninety six%, recollect 96% and F1-rating ninety six% among all machine learning classifiers.

I. INTRODUCTION

Stress is something that concerns our lives. There are many variables in our day-to-day life that are tension. Human environments, like worksite, home, or society, may somehow inflict stress on a person.

According to Palmer [1], "Stress is defined as a complex psychological and behavioral condition when the person's demands are imbalanced and the way demands are met."

Also, the American Institute of Stress found that 80% of workers experience stress in their everyday work and need support in managing stress.

Based on Ahuja and Banga [2], study recorded major suicide cases among students aged 15-29 due to stress. There are 8934 cases recorded in 2015, and study was inspired to identify stress in early stages.

These figures and stress effects on people, which has been the leading cause of many diseases like hypertension, sleep deprivation, and others. Stress that cannot be adequately treated can lead to serious cases where one person committed suicide. This is vital to identify and control stress before it becomes severe.

Many researchers investigate stress detection in many fields. This paper will elaborate on stress identification based on five conditions using data obtained using IoT sensors. Early detection can help track tension, and different machine learning and deep learning approaches have been explored and compared.

II. RELATED RESEARCH WORKS

Many studies are being conducted to identify tension or depressed individuals. Table 1 shows some previous related research work focused on the stress detection scheme, where some researchers use the public dataset and some researchers collect their own dataset [3-12].

Table 1. Previous Related Research Works.

Ref	Title	Dataset	Result
[3]	Stress Detection with Machine Learning and Deep Learning using Multimodal Physiological Data	Public dataset WESAD dataset	Achieved accuracy 84.32% and 95.21% using RF, DT, AdaBoost, KNN, LDA, SVM and DL
[4]	Stress Detection through Speech Analysis using Machine Learning	Public Dataset Ryerson Audio-Visual Database of Emotional Speech and Song (RAVDESS) dataset	CNN- Achieved accuracy 94.26%-94.3%
[5]	Introducing WESAD, a Multimodal Dataset for Wearable Stress and Affect Detection	Public dataset WESAD dataset	Accuracy of 80% (three class) and 93% (two class) was achieved using RF, DT, AdaBoost, KNN, LDA, and SVM
[6]	A Machine Learning Approach for Stress Detection using a Wireless Physical Activity Tracker	Private Dataset Collected own dataset using FITBIT device and analysis using ANOVA	AIC- 782.8842 (Logit model) AIC- 781.6256 (Probit model) AIC-786.8999 (Complementary Log-Log model)
*lower AIC, the better of model			
[7]	Machine Learning and IoT for prediction and detection of stress	Private Dataset Collected own dataset and classified using Python	LR-66% SVM-68%
[8]	Machine Learning-based signal processing using physiological signals for stress detection.	Private Dataset Collected own dataset based on heart rate, EMG, GSR hand and foot data, respiration and classified using WEKA	KNN classifier- Achieved accuracy 92.06% SVM- Achieved accuracy 96.82%
[9]	Stress detection using wearable physiological sensors	Private Dataset Collected own dataset from BN-PPGED	SVM- Achieved accuracy 82%
[10]	Emotion Recognition Based on Multichannel Physiological Signals with Comprehensive Nonlinear Processing	Private Dataset Collected own dataset based on the ECG,GSR,EMG	KPCA reduce the features and GBDT for classifier- Achieved accuracy 93.42%
[11]	Emotion Recognition by Heart Rate Variability	Public Dataset MAHNOB dataset	SVM- Achieved accuracy 48.5%
[12]	Classification of Physiological Signals for Emotions Recognition using IOT	Private Dataset-SAID Dataset Collected own dataset using ECG and GSR SAID Dataset	ANN- Achieved Mean accuracy 75.8% and standard deviation of accuracy 11.38%

Abbreviations

RF=Random Forest, SVM=Support Vector Machine, KNN= k-Nearest Neighbour, DT=Decision Tree, AdaBoost =Adaptive Boosting, LDA= Linear Discriminant Analysis, DL=Deep Learning, LR= Logistic Regression, CNN=Convolutional Neural Network, AIC= Akaike information criterion ANN=Artificial Neural Network, KPCA=Kernel Principal Component Analysis, GBDT=Gradient Boosting Decision Tree ()

III. RESEARCH METHODOLOGY

The research methodology used to conduct the analysis for this paper is detailed below. The paper's primary contribution is the identification of stress using machine learning and deep learning. The flow diagram below illustrates the proposed work on stress detection using machine learning and deep learning. This can be summarized in five steps.




Figure 1. Flow diagram of stress detection.

A. Dataset Preparations

There are three method to collect data such as interview/questionnaire, sensor measuring method and collection of social media. This paper used dataset comes sensors were it been collected at Indian Institute of Information Technology (IITA). The dataset was gathered using a sensor included in the MySignals Healthcare Toolkit. MySignals is a forum for medical device and e-Health application creation. The MySignals toolkit includes an Arduino Uno board and a variety of sensor ports. The sensors were attached to the MySignals Hardware package (which includes an Arduino) and programmed using the Arduino SDK.




Figure 2. MySignals toolkit.

B. Dataset Acquisitions

The Galvanic Skin Response (GSR) and Electrocardiogram (ECG) sensors were used to collect data from 252 participants, a combination of male and female students ranging in age from 20 to 22 years. The tests took place in closed and quit locations. Each participant is required to watch 18 videos from a list of YouTube videos ranging in length from 2 to 5 minutes. Throughout the video playback, MYSIGNAL toolkits were used to record Galvanic Skin Response (GSR) and Electrocardiogram (ECG) sensors. Following that, participants were given a response form to complete about their emotional rate at the end of each video session. After pre-processing the raw data from MYSIGNAL, the Mean, Median, Standard deviation, Minimum reading, Maximum reading, Max Ratio, and Min Ratio are extracted to obtain the best features. Next after data collection and pre-processing, the processed data was analysed using a machine learning classifier to predict the users' mental states and to comprehend their physiological characteristics under various conditions. This dataset is referred to as the Stress Analysis using IOT Device Data Set (SAID).



Figure 3. Experiments Setup for each participant.

C. Classification Algorithm

The classification algorithms is method to detect stress level in SAID dataset which is been categorized into four classes as 0, 1, 2 and 3 as ‘Relax’, ‘Stressed’, ‘Partially Stressed’ and ‘Happy’ respectively as illustrated in Figure 4.




Figure 4. Count of each class for SAID dataset.

Classification algorithm been used in this paper are Multilayer Perceptron (MLP), Decision Tree (DT), K- Nearest Neighbor (KNN), Support Vector Machine (SVM) and Deep Learning (DL). The dataset is split into two parts: 70% for training and 30% for research. The following subsection will discuss the machine learning algorithms used in this experiment and how their parameters were set for each classifier.

1) *Multilayer Perceptron (MLP)*: MLP is the popular and mostly used in most research area. MLP has input and will be transmitted inside MLP layer called as hidden layer in one direction to be classified as output. There are no loops, thus it will not affect the output of each neurons. The parameter setting for MLP is summarized below using Table 2.

Table 2. MLP Parameter Setting.

Parameter	Parameter Setting
hidden_layer_sizes	100
activation	relu
mon learning_rate_init	0.001
solver	adam

2) *Decision Tree (DT)*: Decision tree builds classification models in the form of a tree structure. It breaks down a dataset into smaller and smaller subsets while at the same time an associated decision tree is incrementally developed. The final result is a tree with decision nodes and leaf nodes based on their class dataset [3]. The parameter setting for DT is summarized below using Table 3.

Table 3. Decision Tree Parameter Setting.

min_samples_leaf	1
min_samples_split	2
criterion	gini

3) *K- Nearest Neighbour (KNN)*: KNN is a class membership where it will group the dataset based on their classes whether it belong to group a or group b. KNN works by allocated data based on the nearest neighbours which one is its k closest neighbours (k is a positive number and a small number). If k = 1, then the data will be allotted to the group a or b based on closest neighbour [2]. Table 4 shows parameter setting for KNN.

Table 4. K- Nearest Neighbour Parameter Setting.

Parameter	Parameter Setting
n_neighbor	5
weights	uniform
leaf_size	30
metric	minkowsk

4) *Support Vector Machine (SVM)*: SVM works upon the ideal hyper plane and still effective in high dimensional spaces. In 2-Dimensional data, SVM will try to classify based on dataset classes [2]. Table 5 shows parameter setting for SVM.

Table 5. SVM Parameter Setting.

Parameter	Parameter Setting
C	1.0
kernel	rbf
degree	3
decision function shape	one-vs-rest ('ovr')

5) *Deep Learning (DL)*: Deep learning has many layers of the processing units for the input of the dataset. Each layer has massive sub-layers of hidden layers. This algorithm is not only for supervised but also applicable for unsupervised classification problem [3]. The deep learning layer architecture are show in Figure 5 below:

Layer (type)	Output Shape	Param #
dense_402 (Dense)	(None, 14)	210
dropout_58 (Dropout)	(None, 14)	0
dense_403 (Dense)	(None, 100)	1500
dropout_59 (Dropout)	(None, 100)	0
dense_404 (Dense)	(None, 4)	404

Total params: 2,114
 Trainable params: 2,114
 Non-trainable params: 0

Figure 5. Deep learning layer architecture.

D. Performance Evaluation

Several performance evaluation metrics are identified to be used to evaluate the performance of the stress detection model [13]. These metrics are accuracy, precision, recall and F1-Score are shown below:

$$Accuracy = \frac{True\ Positive + True\ Negative}{True\ Positive + True\ Negative + False\ Positive + False\ Negative} \tag{1}$$

$$Precision = \frac{True\ Positive}{True\ Positive + False\ Positive} \tag{2}$$

$$Recall = \frac{True\ Positive}{True\ Positive + False\ Negative} \tag{3}$$

$$F1\text{-Score} = 2 \times \frac{Precision \times Recall}{Precision + Recall} \tag{4}$$

IV. EXPERIMENTAL RESULTS AND DISCUSSIONS

The main goal of this paper is to detect stress level in SAID dataset. The dataset has been splitted into training dataset contain 70% and testing dataset contain 30% as shown in Figure 6. In this experiments Multilayer Perceptron (MLP), Decision Tree (DT), K-Nearest Neighbor (KNN), Support Vector Machine (SVM) and Deep Learning (DL) are been used and been detailed up in Table 2. Table 6 also shows that the accuracy has reached up 79% until 96% for SAID dataset. Based on the result from Table 6 below, Support Vector Machine (SVM) had the overall worst performance where SVM have accuracy 79%, precision 81%, recall 75% and F1-score 77%, whereas Decision Tree (DT) had the best performance where DT have accuracy 95%, precision 96%, recall 96% and F1-score 96% among all machine learning classifiers.




Figure 6. Training/Testing and Cross Validation use in these experiments to overcome overfitting problem.

Table 6. Experimental Result.

Classifier	Accuracy	Precision	Recall	F1-Score
Support Vector Machine (SVM)	79%	81%	75%	77%
K- Nearest Neighbor (KNN)	82%	79%	78%	78%
Multilayer Perceptron (MLP)	86%	84%	87%	85%
Deep Learning (DL)	91%	92%	91%	91%
Decision Tree (DT)	95%	96%	96%	96%

It can be concluded that using Decision Tree give the best result compared to other machine learning techniques. Decision Tree have several advantages such as the output are easy to read and assign specific values to each problem, decision path and the outcome of the output. Based on the learning curve it also show that using Decision Tree are suitable for this dataset where there is no under fitting and over fitting cases when training the model using Decision Tree algorithm.

From the previous study, Tiwari et.al, 2019 [12], using Artificial Neural Network as the classifier and getting result Mean of Accuracy 73.58% and Standard Deviation of ANN model accuracy is 11.38%. From this, we can make a conclusion that using other machine learning from our experiments are better compared to previous studies. By choose a better classifier could improve the efficiency when training the model.




Figure 7. Learning curve for training (Cross Validation=10) and confusion matrix using Decision Tree.

V. CONCLUSION

In this paper, it can conclude that using suitable classifier will get better result in accuracy, precision, recall and F1-Score. From experiments results, it shows some significant value where DT achieved the best resulting on accuracy 95%, precision 96%, recall 96% and F1-score 96%. The results prove that the using DT has a competitive performance compared to the others classifiers for detecting stress and non- stress and classifying stress levels. Further work can be done by using more classifier and applied 10- fold cross validation.

REFERENCES

- [1] Ahuja R and Banga A 2019 International Conference on Pervasive Computing Advances and Applications – PerCAA 2019 **125** 349-353
- [2] Bobade P and Vani M 2020 Proceedings of the Second International Conference on Inventive Research in Computing Applications (ICIRCA-2020) 51-58
- [3] Vaikole S Mulajkar S More A Jayaswal P and Dhas S 2020 International Journal of Creative Research Thoughts (IJCRT) **8** 5 2239-44
- [4] Padmaja B Rama Prasad V V and Sunitha K V N 2018 International Journal of Machine Learning and Computing **8** 1 33-38
- [5] Pandey P S 2017 2017 17th International Conference on Computational Science and Its Applications (ICCSA)
- [6] Sandulescu V Andrews S Ellis D Bellotto N and Mozos O M 2015 International Work-Conference on the Interplay Between Natural and Artificial Computation 526-532
- [7] Tiwari S Agarwal S Muhammad Syafrullah and Adiyarta K 2019 Proc. EECSI 2019 - Bandung, Indonesia **6** 107-111
- [8] Zainudin Z Shamsuddin S M and Hasan S 2019 The International Conference on Advanced Machine Learning Technologies and Applications (AMLTA2019) **921** 43-51



10.22214/IJRASET



45.98



IMPACT FACTOR:
7.129



IMPACT FACTOR:
7.429



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24*7 Support on Whatsapp)