



IJRASET

International Journal For Research in
Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 5 Issue: X Month of publication: October 2017

DOI: <http://doi.org/10.22214/ijraset.2017.10159>

www.ijraset.com

Call:  08813907089

E-mail ID: ijraset@gmail.com

High Performance Voltage Differencing Inverting Buffer Amplifier (VDIBA)

Rashi¹, Dr. Richa Srivastava²

¹Rashi, Electronics and Communication Engineering, AKGEC, Ghaziabad, India, 9760244264.

²Dr. Richa Srivastava, Electronics and Communication, AKGEC, Ghaziabad, India, 9999001159

Abstract: This paper presents Low Voltage bulk driven technique based low-voltage low-power variant of recently proposed an active element namely Voltage Differencing Inverting Buffered Amplifier (VDIBA). The proposed configuration operates at lower supply voltage 0.6V with the total quiescent power consumption of 1.36mW at the biasing current of 10 μ A. The simulations are performed using CADENCE 180 nm CMOS technology parameters with 0.6V supply voltage to validate the effectiveness of the proposed circuit.

Index: Terms: Low-Voltage, VDIBA, Low-Power, Analog Circuit Design.

I. INTRODUCTION

As the technology is scaling and demand of portable electronic equipments is growing day by day, it has motivated the researchers in developing low-voltage low-power analog signal processing circuits. Low-voltage low-power design involves various promising techniques so that the complete analog circuit could meet the proposed design requirements. Various low-voltage, low-power design techniques have been reported in many literatures explaining techniques like sub-threshold MOSFETs, level shifter approach, self-cascade approach, bulk driven approach and use of FG MOS instead of simple MOSFETs [2–11]. Bolek et al. [14] have introduced and explains behavioral model of new active element like Voltage Differencing Buffered Amplifier (VDBA), Voltage Differencing Current Conveyor (VDCC) Voltage Differencing Transconductance Amplifier (VDTA),. These active elements are obtained by replacement of current differencing unit in Current Differencing Buffered Amplifier (CDBA), Current Differencing Transconductance Amplifier (CDTA) etc. by the voltage differencing unit. The differential OTA at the input stage is used to generate the voltage difference in these newly introduced active elements. These above suggested topologies have simpler structure as well as increased electronic tunability. Recently, Nobert Herencsar et al. [1] have introduced to an active element VDIBA that has gained wide popularity due to its simpler structure consisting only six MOS transistors.

The input stage and the output stage of VDIBA consist of operational transconductance amplifier and unity gain inverting buffer respectively. Tunability feature of built-in OTA in these blocks is helpful for compensating the unwanted parameter variation caused because of PVT variations. Though these modifications are attention-grabbing and give advantage of advanced electronic management, they lack the characteristics of low voltage and low power active component. Therefore, the major aim of this paper is to introduce low-voltage low-power variant of typical VDIBA developed by using bulk driven technique that may well be utilized in more difficult applications.

The paper is organized as follows: basics of Bulk Driven Technique are given in Section II. New low-voltage low-power and high operating frequency variants of VDIBA are introduced and analyzed in Section III. Section IV deals with the simulation results and finally the paper is concluded in Section V.

II. BULK DRIVEN TECHNIQUE

Amplifiers operating at very low supply voltages are best for bio-medical and sensor applications where energy can be harvested from its environment. In biomedical devices such as ambulatory heart detectors and hearing aids very low power consumption is used to increase the battery life. There is equal importance for low voltage and lower power operation in portable applications as low voltage operation enables the use of lesser of batteries thereby being advantageous for size and weight considerations and the battery life gets improved by low power consumption. For low voltage the main idea is to make the circuit operate in the weak inversion region. There are various approaches like floating gate approach, self-cascode structures.

The principle of the bulk-driven technique is that the input is given on the body that is less than the threshold voltage and a voltage is being set on the gate terminal so as to form a channel. The thickness of the depletion zone i.e. the conduction channel is affected by the bulk voltage. A bulk-driven symmetrical OTA operating in weak inversion can result in both reduced power consumption

and high linearity. The utilization of this technique makes it conceivable to design low-voltage OpAmps with very large value of input CMRR and low power dissipation on the CMOS technologies.

In this technique, a fixed voltage is associated with the gate terminal and the input is given into the bulk terminal as shown in Fig.1. With the zero-bias voltage on the bulk terminal the transistors are in weak inversion. The two fundamental favorable circumstances of utilizing the bulk-driven system are that the bulk-driven differential sets in an OpAmp and incredibly enhance the transconductance and the threshold voltage of the transistor vanishes and both negative and positive bias voltages (VBS) are conceivable.




Fig.1- Block Diagram of Bulk Driven nMOS[1]





Fig.2 CMOS implementation of VDIBA

III. PROPOSED LOW-VOLTAGE LOW-POWER BULK DRIVEN BASED VDIBA

CMOS implementation and equivalent circuit symbol of standard VDIBA [2] is shown in Fig. 2 and 3 respectively. The input stage of VDIBA consisting transistors M1-M4 makes the OTA stage that converts the differential input voltage into current. The output stage fashioned by M5-M6 is a unity gain inverting buffer with M5 operating as nMOS load. The circuit has high impedance input ports of OTA i.e. p and n, a high impedance output port z and a lower impedance output voltage port w. Port relations of VDIBA are represented by following matrix where g_m is the transconductance parameter of OTA stage and β which is ideally unity; denotes the non-ideal voltage transfer gain between ports z and w.

The proposed configuration offers many attractive features such as low static power dissipation along with high output resistance of the first stage.



.Fig.2 CMOS implementation of VDIBA




Fig.3-Symbol of Standard VDIBA.




Fig.4Schematic of Improved VDIBA

The schematic of Improved VDIBA has been created by using virtuoso schematic composer as shown in Fig.4. For the simulations, DC power supply voltage shave been taken as $+V_{DD} = -V_{SS} = \pm 0.6V$. The bias current is set at $10\mu A$.

IV. RESULTS AND SIMULATION

The designed circuits are simulated using CADENCE in TSMC180nmCMOS technology using $\pm 0.6V$ powersupply. The Fig.5 shows the graph between the output current I_z and input voltages V_p and V_n . The linearity can be viewed which varies from $(-350mV) - (+350mV)$ where the biasing current is $10\mu A$




Fig.5 DC analysis of Improved VDIBA for I_z versus V_p, V_n

Table 1 Result of Proposed VDIBA

Parameter	Proposed VDIBA
Technology	180nm
Supply voltage	0.6V
Linearity	(-350+350)mV
Frequency	31.6MHz
Power dissipation	1.30mW

The Table.1 provides all the detailed results of simulations done on cadence of the proposed circuit.

Fig.6 shows the ac analysis of proposed VDIBA with the frequency of 31.6MHz.

Fig.6 AC Analysis of Improved VDIBA Fig.7 shows the power dissipation of proposed VDIBA which is 1.30mW.




Fig6 Power Dissipation of the improved VDIBA circuit

V. CONCLUSION

This paper presents Low Voltage Bulk driven based voltage differencing inverting buffered amplifier. It operates at a lower supply voltage and has reduced power dissipation. The proposed VDIBA is used in the realization of a low voltage filter applications and several attractive features such as independently tunable filter parameters, cascability and low sensitivity. Therefore, the proposed VDIBA may be useful in low voltage low-power analog signal processing or generation applications.

VI. ACKNOWLEDGMENT

I would like to thank Ajay Kumar Garg Engineering College for providing all the required resources for this work and their faculty members for their guidance.

REFERENCES

- [1] K.L.Pushkar, D.R. Bhaskar, Dinesh Prasad, 2014, "Voltage mode new universal biquad filter configuration using a single VDIBA", Circuits Syst Signal Process –springer, Vol. 33, pp. 275– 285.
- [2] Norbert Herencsar, Shahram Minaei, Jaroslav Koton, Erkan Yuce, Kamil Vrba, 2013, "New resistorless and electronically tunable realization of dual-output VM all-pass filter using VDIBA", Analog Integrated Circuit Signal Process –springer, Vol. 74, pp.141–154.
- [3] Siddharth Bhat, Shubham Choudhary and J. Selvakumar, 2016, "Design of Low Voltage CMOS OTA Using Bulk-Driven Technique", Indian Journal of Science and Technology, Vol.9, pp. 1-6.
- [4] Antaryami Panigrahi, Abhipsa Parhi, 2016, "A Gain Enhanced Low Voltage Bulk Driven Pseudo Differential OTA design in CMOS", International Conference on VLSI Systems, Architectures, Technology and Applications, Vol. 10, pp.1-5.
- [5] Maneesha Gupta, Richa Srivastava, Urvashi Singh, 2015 "Low voltage low-power FGMOS based VDIBA and its application as universal filter". Microelectron. J. Vol.46, pp.125–134.
- [6] S.S.Rajput, S.S.Jamuar, 2002. "Low voltage analog circuit design techniques" IEEE CAS Mag. Vol.2, No.1, pp.24–42.
- [7] Y.Haga, H.Zarehoseini, L.Berkovi, I.Kale, 2005 "Design of a 0.8V fully differential CMOS OTA using the bulk-driven technique", IEEE Int. Symp. Circuits Syst. 1, pp.220–223.
- [8] B. Aggarwal, M.Gupta, A.K.Gupta, 2013 "Analysis of low voltage bulk-driven self-biased high swing cascode current mirror", Microelectron. J. Vol.44, No.3, pp.225–235.



- [9] T.S.Lande, D.T.Wisland, T.Soether, Y.Berg, 1996 "FLOGIC-Floating gate logic for low-power operation", in: Proceedings of the 3rd IEEE International Conference on Electronics, Circuits and Systems, 2, pp.1041–1044.
- [10] R.Srivastava, M.Gupta, U.Singh, "Low-voltage FGMOS squarer divider based analog building blocks", International Journal of Electronics.
- [11] M.Gupta, R.Pandey, 2011 "Low-voltage FGMOS based analog buildingblocks",Microelectron.J.Vol42,No6,pp.903-912.
- [12] R.Srivastava, M.Gupta,U.Singh, 2014. "FGMOS transistor based low voltage and low powerfully programmable Gaussian function generator", Analog Integr. Circuits Signal Process. Vol 78, No1, pp. 245–252.
- [13] J.Lu, S.Young, I.Arel, J.Holleman, 2014 "AITOPS/W analog deep machine-learning engine with floating-gate storage in 0.13mm CMOS", in: Proceedings of the IEEE International Solid-State Circuits Conference Digest of Technical Papers (ISSCC), pp.504–505.
- [14] J.Lu, J.Holleman, 2013 "A floating-gate analog memory with bidirectional sigmoid updates in a standard digital process", in: Proceedings of the IEEE International Symposium on Circuits and Systems (ISCAS), pp.1600–1603.
- [15] E. Rodriguez-Villegas, 2006, "Low power and low voltage circuit design with the FGMOS transistor", IET Circuits, Devices and Systems Series, Vol.20, The Institution of Engineering and Technology, London, United Kingdom.
- [16] D.Bolek,R.Senani,V.Blojkova,Z.Kolka,2008, "Active elements for analog signal processing: classification, review, and new proposals", Radioengineering, Vol.17no.4,pp.15–32.
- [17] Rashi has received B.Tech degree in Electronics and Communication Engineering from Raj Kumar Goel Institute of Technology, Ghaziabad, India in 2014. This author is pursuing M.Tech in VLSI design from A.K.G. Engineering College, Ghaziabad Uttar Pradesh, India. Her major area of research work is Analog Circuit Design.
- [18] Dr Richa Srivastava has received her degree of B.TECH in Electronics and communication Engineering and M.Tech in VLSI DESIGN from Banasthali University. She is currently an Assistant professor in AKG Engineering college, Ghaziabad.



10.22214/IJRASET



45.98



IMPACT FACTOR:
7.129



IMPACT FACTOR:
7.429



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24*7 Support on Whatsapp)