



# **iJRASET**

International Journal For Research in  
Applied Science and Engineering Technology



---

# **INTERNATIONAL JOURNAL FOR RESEARCH**

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

---

**Volume: 7      Issue: VII      Month of publication: July 2019**

**DOI: <http://doi.org/10.22214/ijraset.2019.7105>**

**[www.ijraset.com](http://www.ijraset.com)**

**Call:  08813907089**

**E-mail ID: [ijraset@gmail.com](mailto:ijraset@gmail.com)**

# A Review on Use of Turbulators in Heat Exchanger

Shailendra Payasi<sup>1</sup>, Prashant Sharma<sup>2</sup>, Arvind Kumar Namdev<sup>3</sup>

<sup>1</sup>Research scholar, <sup>2,3</sup>Astt. Professor, Department of Mechanical Engineering, University Institute Of Technologyrajiv Gandhi Proudyogiki Vishwavidyalaya, Bhopal (M. P.), India

**Abstract:** In order to enhance the heat transfer rate to flowing medium inside the heat exchanger various turbulence generators viz delta, ribs, baffles and winglets are considered as an effective technique. There are two methods to enhance the heat transfer inside the heat exchanger that is active one and passive one. Tabulator is one of the passive approaches which are used for improvement in heat transfer. Here in the work a review on turbulators used in heat exchanger was done. It includes the different types of turbulators used and there different design optimization.

**Keywords-** Heat exchanger, turbulators, review, process parameters

## I. INTRODUCTION

A Heat Exchanger may be stated as a device which transfers energy from a hot fluid to a cold fluid, either maximum or minimum rate within least investment as well as operating cost. In this process never two fluids mixed with each other. Heat exchanger is the main unit in action that gives the efficiency as well as security to numerous of the processes. In such type of job we have to estimate the enactment of the heat exchangers of different types that is tubular, plate and shell & tube. All these heat exchangers may be functioned in both parallel as well as counter flow arrangements. The heat exchanger is accomplished amongst hot and cold water. This device offers a thermal energy flow among two or more fluids at some temperatures. Shell and tube heat exchangers are most useful type of heat exchanger likewise utilized in an extensive range of industrial uses like power generation, heat recovery in wastage system, engineering firms, cooling and refrigeration, space applications, petrochemical activities and many different areas.

## II. USE OF TURBULATOR IN DIFFERENT AREAS

The core purpose of a turbulator in a heat exchanger is to: Clamp the pipe in location averting slumped, both in manufacture and operation. Preclude the possessions of steam starvation, which is augmented with fluid velocity as well as the heat exchanger length. This upsurges fluid velocity and the effective heat transfer co-efficient of the exchanger. In a stationary blender, turbulator are utilized to lessen the tangential constituent of velocity which effect vortex creation therefore promotes mixing. In a chemical reactor, turbulators are always devoted to the inner walls to endorse intercourse and consequently increase heat transfer and possibly chemical reaction rates.

### A. Types of Turbulators

Employment of turbulator is obvious on the source of volume, cost and their capability to advance provision to the tube packs and straight. Turbulators with Longitudinal Current (utilized in a two-passage shell), Impingement turbulators (utilized for keeping the pack when arrival velocity is larger), Turbulators with Orifice, Single segmental, Double segmental, Support/Blanking turbulators and DE resonating (unmatched) turbulators utilized to decrease tube vibration.

### B. Installation of Turbulators

As stated, turbulators considered with the apprehension of provision and liquid direction in heat exchangers. In this method it is spirited that they are spread out properly at the fitting. The least turbulator arrangement is the better with 50.9 mm or one of the fifth of the internal shell distance. The extreme turbulator arrangement is reliant on physique and tubes size. The Tube-shaped exchanger industrialists association putting the strategies. There are correspondingly divisions with a no pipes in frame analysis that disturbs the satisfactory arrangement with in the design.

## III. EXISTING WORK

Many of the researchers have work on heat exchanger to increase the performance of heat exchanger using different methods. Researchers use different type of turbulators to increase the performance of heat exchanger. Some of the research works in the field of heat exchanger were conclude here in the blow section.

Sheikholeslami et.al (2018) Impact of distinctive and perforated uneven helical turbulators on flow and in transfer of heat in an air to water double pipe heat exchanger are practically analysed. According to the practical facts, relationships among Nusselt number, friction factor and performance of thermal parameter are accessed as functions of distinct constraints. Non-dominated Sorting Genetic Algorithm II is in action to get the maximum high efficiency of designed heat exchanger. Practical steps are being showed to examine flow to be turbulent and transfer of heat in an air to water heat exchanger prepared with usual and perforated intermittent helical turbulators. Impacts of the Reynolds number, ratio of open area and ratio of pitch on loss in pressure and transfer of heat enhancement are observed. Relationships among Darcy factor, Nusselt number and performance of thermal parameters are obtained.

Zhouhang Li et.al (2017) Helical coils have gained ever more interest in the area of carbon dioxide of supercritical range with Rankine cycles through the past era due to the dense assembly and great rate of heat transfer. Previous analyses basically concentrated on influence of operational conditions and with the gravitational up thrust, and are not satisfactory to properly comprehend the behavior of supercritical carbon dioxide gas heaters with helically coiled. Impact of few different main elements, such as the alignments of coil and roughness of inner wall, on full enactment that's been rarely stated and is still uncertain to date. In this work we filled such opening with a solid to fluid conjugate model of heat transfer where supercritical turbulence flow is explained by the Shear Stress Transport k-u functions. Impact of coil alignments and inner rib roughness on transfer of heat of supercritical carbon dioxide which have been inspected in helical coiled tubes with different dimensionless curvature  $d$ . Consequences describes that the alignment impact was thoroughly correlated to the effect of gravitational buoyancy.

Ali et.al (2017) This paper defines the thermal analysis of reclined parallel to surface of the ground and upright at right angle to surface of the ground, slinky horizontal ground heat exchangers wit ground about the sprawled horizontal ground heat exchangers due to extraction of heat, as well as the influence of deviation in temperature of ground on reclined horizontal ground heat exchangers performance. The thermal performance improvements by intermittent operations of ground heat exchangers are also discussed. Moreover, the allocations of temperature of the unobstructed ground and temperature of the environs are also taking into account. The evaluated unobstructed temperature of ground data delivers a useful needle of the installation of ground heat exchangers at an appropriate deepness for heating as well as cooling purposes.h changed water rates of mass flow in the reheating manner of constant and discontinuous actions. A copper tube like an outer area secured with low density polyethylene has been designated as the tube material of the heat exchanger identified as ground. The practical thermal enactments of slinky horizontal ground heat exchangers standing and reclined orientation being taken into account in altered modes of heating. The practical outcomes defines the differences of the enactments of standing and reclined orientation, impacts on temperature of ground on reclined horizontal ground heat exchangers are also discussed.

Pawar et.al (2016) In past few eras many of the mechanical, practical and mathematical models are being existed on shell with tube in combination tube heat exchanger by several scholars. In the firms where shell and tube heat exchangers are utilized for various applications example for heat recovery waste, oil refineries and so on. This analysis concentrated on the practical research of shell and tube heat exchanger with distinguished type of turbulators. The shell and tube heat exchanger with segmental turbulators and flower turbulators are calculated, made-up and verified. In a shell and tube heat exchanger associated to segmental and helical turbulator, flower turbulator provides recovered thermal as well as hydraulic performance. Also production of flower turbulators is liberal as comparable to helical turbulator. Practical outcomes shows that the shell side coefficient of heat transfer in flower turbulators increases up to 34-45% than the segmented turbulators at identical shell side Reynolds number as well as at tube side velocity of about 0.88 m/s. drop in pressure in flower turbulators is quite lower than segmented turbulators. Drop in Pressure reduces up to 21-29%. Beneath the equal operating system that is at the similar shell side Reynolds number and at tube side velocity of about 0.88 m/s.

Murthy et.al (2016) Improving surfaces of heat transfer are utilized in many engineering functions such as, air conditioning equipment, heat exchangers and many more areas. Both active and inactive methods that is being examined on improvement of heat transfer. Passive heat transfer method is one of the utmost important methods that are utilized. In the zone of heat transfer, studies have been made out over numerous of years for the growth of convective heat transfer improvement methods. The additives used in the base fluid as water or ethylene glycol is one of the methods functioned to expand the heat transfer. In the current studies an effort being made to represent a perilous analysis on inactive methods which are utilized in order to develop the performance of heat transfer. Addition of swirl flow apparatus or metallic additions improve the convective heat transfer with swirl into the fluid motion and troubling the boundary layer at the surface of the tube due to repeated variations in the surface parameters.

Sheikholeslami et.al (2016) The turbulent hydrothermal study of forced convection in a heat exchanger of double pipe is existed practically. Now perforated turbulators are used in annulus area. Hot water generates the cold air in the outer tube warmer. Different quantities of ratio of pitch, ratio of open area and Reynolds number are deliberated. Relationships for Nusselt number, performance



of thermal and darcy factor of friction are tested. Impacts of perforated circular ring on stream type and thermal treatment in a heat exchanger of water to air are observed. The effect of pitch ratio, thermal conductivity Reynolds number on hydrothermal activity are calculated. Relationships of Nusselt number and friction factor have been provided.

Bandos et.al (2016) The method to get the key to the determinate source as cylinder model for the heat exchangers with ground at a distinct concealed depths that are taking into account the capacity of heat inside them and permits random rate of heat changes are obtained. Logical evaluations for the temperature of the ground taking average are justified by integrating the particular results over the cylinder source as depth for vertical and time dependent modifications of the heat rate. Fresh results for mean temperature replies from ground heat exchanger modelled as finite cylinder source of uniform heat flow implanted into the semi-infinite zone on a distance  $D$  from its surface being existed in a solo integral pattern. Although the response of mean temperature from the finite cylinder source getting the ones from the different models in the middle and long lasting scales, correspondingly, the planned fundamentals shorting the recognized issue of discontinuity in the time interval, where finite-curvature and -depth contributions are significant.

Sheikholeslami et.al (2016) Effect of perforated and distinctive helical fin on hydrothermal action in water to air heat exchanger is obtained. Water as well as air moving over inner and outer pipes, correspondingly. Influence of ratio of pitch, Reynolds number and ratio of open area are studied. Empirical formulations for performance of thermal parameter, Darcy factor and Nusselt number are achieved. Impacts of perforated fins with helical coil on current type as well as thermally treated water to air heat exchanger are scrutinized. The impacts of Parental number and Reynolds number on hydrothermal behavior are analyzed. Relationships among Nusselt number, friction factor and heat transfer coefficient have been estimated. Results reveal that loss in pressure and Nusselt number reduces with enhance of pitch ratio. The slope of temperature over the hot wall rises with rising in velocity of the inlet air.

Serageldin et.al (2016) In the current paper we analyses the thermal behavior of an Earth-Air Heat Exchanger utilized for heating as well as cooling purposes and is explored under Egyptian weather situations. The soil temperature contour as well as the temperature variation of moving air through horizontal Earth-Air Heat Exchanger is practically examined. Also, a calculated model based on non-uniform, one-dimensional and quasi-state is established for conservation of energy equation while, the standard model is useful to find the turbulence kinetic energy of the moving fluid. The statistically advanced model and computational fluid dynamics calculation conclude the validation against investigational outcomes. In this analysis, the variation in temperature of moving air from side to side horizontal Earth-Air Heat Exchanger practically considered. A numerical model relied on non-uniform, one dimensional and quasi-state conservation of energy equation established for moving fluid. Eventually, three dimensional, steady as well as double accuracy computational fluid dynamics fluent calculative model acquired to envisage the temperature of air.

Wang et.al (2016) In the analysis of multi-stream plate-fin heat exchangers, selection of surface and layer pattern maximizing are examined as two self-determining issues and still continue at the experimental phase, that develops an impediment for maximizing the performance. The layer maximization model with eleven constraints for the geometrical space is assembled by utilizing an inherited procedure hybrid with an eccentric search procedure. There are two cases that have been maximized in firms with this model, and the consequences are estimated by three tools. The chief inferences of the current work are as follows, The difference in temperature and drop in pressure are familiarized into the optimization model of the corresponding layer arrangement ring, by means of which the impact of the drop in pressure on the multi-stream plate-fin heat exchangers is considered with the heat transfer efficiency.

Vahidifar et.al (2015) This analysis examines characteristics of heat transfer and the drop in pressure of a horizontal double pipe heat exchanger with wire coil enclosures. The magnification of coefficient of heat transfer in the heat exchanger decreases the weight, size and heat exchanger cost. When an article is engaged in a boundary layer, it disturbs the flow pattern and changes the velocity as well as temperature contours. The change is influenced by the development of jets and stirs in the boundary layer as it varies transfer and coefficients of friction on the wall. The current investigational analysis concentrated on the analysis of the transfer of heat and drop in pressure among the wire coil and rings insert in smooth tube with  $Re=5000-25000$  and prandtl number=0.7. The circular cross sectional wire coil as well as rings is implanted in the tube. Wire coil and rings inserts tube produced amazing rise in both heat transfer and drop in pressure in contrast with the smooth tube comparative to the pitches and wire thickness. Wire coil turns as a whirl flow, with rotating flow being place over the central core flow, which generates centrifugal force.

Roslim et.al (2015) This object informs about the inquiry on the things of porous twisted plate as enclosure to improve performance of heat transfer and flow parameter for a single fixed tube. The real fixed tube of the boiler is utilized and implanted with simple and porous twisted plates. The accumulating outcome is associated with the simple tube without any supplement. The final consequences describe that formation of holes changed the flow pattern and then creating secondary flow and forthcoming to

turbulence flow. The temperature variation and characteristic of heat transfer of the porous surface twisted plate as inserts in fitted tube are presented in this article. The result obtained was discussed and proved that porous surface twisted plate enhanced the rate of heat transfer inside the tube. The selection on twisted plate surface geometry plays a dynamic role in improving the rate of heat transfer. Porous surface area of the twisted plate has higher surface temperatures at all axial locations along the tube. The bulk temperatures distribution indicates the overall of heat that taken away is increased linearly for both inserts and without insert.

Freidoonimehr et.al (2015) The main objectives of this analysis is to represent double the value for the difficulty in magneto hydrodynamic Jeffery Hamel Nano-fluid flow in other than parallel walls. To get it, we occupy a new logical method, Predictor Homotopy analysis method. This active method is an adept to determine all outlets of the multiple solutions all together. Additionally, comparison of the Predictor Homotopy analysis method results with mathematical outcomes gained by the shooting method attached with a Runge-Kutta integration method exemplifies the high precision for this method. In this analysis, Predictor Homotopy Analysis Method as a new logical method is functional to derive the difficulty of magneto hydrodynamic Jeffery–Hamel Nano fluid flow in other than parallel walls for the divergent as well as convergent networks. This practical method is very commanding particularly for those boundary conditions problems which confess multiple solutions and also able to compute all divisions of the results all together.

Jassim et.al (2015) The analysis gives a fresh design for inactive cooling system by utilizing wind catcher of an earth to air heat exchanger. Rise in space of wind-catcher and supply natural lighting, executes part of wind-catcher into the earth. After we start that wind-catcher which are utilized in conventional construction for long times are missing in modern housing after the appearance of automated freshening and due to the quantity of air given are few that do not meet the restrictions of thermal relief necessities of the modern person. The analysis are marked at calculating the presentation of wind-catcher of an earth to air heat exchanger in refining the inner atmosphere and decreases energy intake in the hot dry parts, Rise in wind-catcher space in the initial stage did not attain a usual level of thermal relief during the day because of solar radiation and at high air temperature. The next part, the system wind-catcher of an earth to air heat exchanger has donated to the lessening of air temperature 18oC which is about 37% of the external air temperature.

Sheikholeslami et.al (2015) Economic reasons material and energy saving leads to make efforts for making more efficient heat exchange. The heat transfer improvement methods are extensively utilised in various applications in just like the heating procedure to make probable deduction in weight as well as size or improve the heat exchangers performance. These methods are categorized as active and inactive methods. The active method uses exterior power whereas the inactive method does not require any exterior source. The inactive methods are acceptable associated with the active methods due to the whirl supplements in Production process are viable and are effortlessly engaged in present heat exchanger. Addition of whirl flow manoeuvres improve the convective heat transfer by making whirl in to the mass flow and disturbing the boundary layer at the surface of the tube with recurring modifications in the surface models. In the current studies an effort is being made to inform valuable inactive methods that are utilized in order to improve the performance of heat transfer. The coefficients of heat transfer of the coiled pipes with higher pitches are lower than those with lesser pitches; and the impact of pitch on Nusselt number is more noticeable in higher temperatures.

#### IV. CONCLUSION

In the review paper discussion has been done on use of different types of turbulators in heat exchanger. Through literature it is found that use of turbulators increases the performance of heat exchanger. Due to use of turbulators the flow inside the heat exchanger get enhance and due to this there is enhancement in heat transfer. So it is concluded that turbulators play very important role in heat exchanger, especially in compact heat exchange.

#### REFERENCES

- [1] M. Sheikholeslami, M. Gorji-Bandpy, D.D. Ganji, Experimental study on turbulent flow and heat transfer in an air to water heat exchanger using perforated circular-ring, *Experimental Thermal and Fluid Science* 70 (2018) 185–195.
- [2] Zhouhang Li, Yuling Zhai a, Dapeng Bi c, Kongzhai Li a, \*, Hua Wang a, Junfu Lu, Orientation effect in helical coils with smooth and rib-roughened wall: Toward improved gas heaters for supercritical carbon dioxide Rankine cycles, *Energy* 140 (2017) 530e545.
- [3] Ahmed A. Serageldin, Ali K. Abdelrahman, Shinichi Ookawara, Earth-Air Heat Exchanger thermal performance in Egyptian conditions: Experimental results, mathematical model, and Computational Fluid Dynamics simulation, *Energy Conversion and Management* 122 (2016) 25–38.
- [4] Pooja J. Pawar, Rupesh J. Yadav, Experimental investigation of shell-and-tube heat exchanger with different type of turbulators, Accepted 15 June 2016, Available online 20 June 2016, Special Issue-5 (June 2016).
- [5] Shankara Murthy. H.M, Dr. Ramakrishna.N.Hegde, A critical review of combined augmentation techniques used for heat transfer enhancement in heat exchangers, *National Conference on Advances in Mechanical Engineering Science (NCAMES-2016)*.
- [6] M. Sheikholeslami, M. Gorji-Bandpy, D.D. Ganji, Effect of discontinuous helical turbulators on heat transfer characteristics of double pipe water to air heat exchanger, *Energy Conversion and Management* 118 (2016) 75–87.



- [7] Tatyana V. Bandos, Alvaro Campos-Celador, Luis M. Lopez-Gonzalez, Jose M. Sala-Lizarraga, Finite cylinder-source model for energy pile heat exchangers: Effect of buried depth and heat load cyclic variations, *Applied Thermal Engineering* 96 (2016) 130–136.
- [8] M. Sheikholeslami, D.D. Ganji, Heat transfer enhancement in an air to water heat exchanger with discontinuous helical turbulators; experimental and numerical studies, *Energy* 116 (2016) 341e352.
- [9] Serageldin S.M Experimental study on heat transfer enhancement in a tube using counter/co-swirl generation, Volume 2, Issue 3, March 2016 ISSN 2319 – 4847
- [10] Zhe Wang, Yanzhong Li, A combined method for surface selection and layer pattern optimization of a multistream plate-fin heat exchanger, *Applied Energy* 165 (2016) 815–827
- [11] S. Vahidifar, M. Kahrom, Experimental Study of Heat Transfer Enhancement in a Heated Tube Caused by Wire-Coil and Rings, *Journal of Applied Fluid Mechanics*, Vol. 8, No. 4, pp. 885-892, 2015.
- [12] Muhammad Khairi Roslim, Suhaimi Hassan and Aklilu Tesfamichael, Experimental investigation on heat transfer enhancement by using porous twisted plate as an insert in a fitted tube, vol. 10, no 21, november, 2015 issn 1819-6608.
- [13] N. Freidoonimehr, M. M. Rashidi, Dual Solutions for MHD Jeffery–Hamel Nano-Fluid Flow in Non-parallel Walls Using Predictor Homotopy Analysis Method, *Journal of Applied Fluid Mechanics*, Vol. 8, No. 4, pp. 911-919, 2015
- [14] Jamal Abed Al Wahid Jassim, Sustainable Design of Wind-catcher of an Earth-to-Air Heat Exchanger in Hot Dry Areas, *International Journal of Scientific & Engineering Research*, Volume 6, Issue 4, April-2015 ISSN 2229-5518.
- [15] Mohsen Sheikholeslami, Mofid Gorji-Bandpy, Davood DomiriGanji, Review of heat transfer enhancement methods: Focus on passive methods using swirl flow devices, *Renewable and Sustainable Energy Reviews* 49 (2015) 444–469.





10.22214/IJRASET



45.98



IMPACT FACTOR:  
7.129



IMPACT FACTOR:  
7.429



# INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24\*7 Support on Whatsapp)