



# IJRASET

International Journal For Research in  
Applied Science and Engineering Technology



---

# INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

---

**Volume: 7      Issue: VIII      Month of publication: August 2019**

**DOI: <http://doi.org/10.22214/ijraset.2019.8061>**

**[www.ijraset.com](http://www.ijraset.com)**

**Call:  08813907089**

**E-mail ID: [ijraset@gmail.com](mailto:ijraset@gmail.com)**

# Electronic Components Inventory Model for Deterioration Items with Distribution Centre using Genetic Algorithm

Satyendra Kumar<sup>1</sup>, Ajay Singh Yadav<sup>2</sup>, Navin Ahlawat<sup>3</sup>, Anupam Swami<sup>4</sup>

<sup>1</sup>Research Scholar, Mewar University, Chittorgarh, Rajasthan.

<sup>2</sup>Department of Mathematics, SRM Institute of Science and Technology, Delhi-NCR Campus Ghaziabad, Uttar Pradesh, India.

<sup>3</sup>Department of Computer Science, SRM Institute of Science and Technology, Delhi-NCR Campus Ghaziabad, Uttar Pradesh, India.

<sup>4</sup>Department of Mathematics, Government Post Graduate College, Sambhal, Uttar Pradesh, India.

**Abstract:** *Electronic Components Distribution centre inventory model is developed for decaying items with ramp type demand and the effects of inflation using Genetic Algorithm. The Electronic Components Distribution centre has unlimited capacity. Here, we assumed that the inventory holding cost in Electronic Components Distribution centre is higher. Shortages in inventory are allowed and partially backlogged and it is assumed that the inventory deteriorates over time at a variable deterioration rate. Cost minimization technique is used to get the expressions for total cost using Genetic Algorithm and numerical example is also used to study the behavior of the model.*

**Keywords:** *Inventory model, Distribution centre, Deterioration rate, Ramp type demand, Inflation, Genetic Algorithm.*

## I. INTRODUCTION

In the current market, the explosion of choice due to fierce competition means that no company can resist inventory because there are a variety of alternative products with additional features. In addition, there is no dry cut recipe, with which the need can be determined exactly. Therefore, when an enterprise requires an inventory, it must be preserved so that the physical attributes of inventory elements can be preserved and protected. How organizations Distribution centre its stocks depends critically on its ability to achieve the ultimate goal of inventory management. An organization collects the same stocks in different ways to achieve different results, even generating profits and losses. Materials Distribution centre ultimately turns out to be the core of the overall inventory management practice. Electronic Components Distribution centre containers are Distribution centre for the Distribution centre and Distribution centre of goods and the provision of other related services to encourage distributors and / or manufacturers to maintain products in a scientific and systematic manner, in order to that they regain their original value, quality and utility preserve. It is an integral part of an industrial unit. It acts as the custodian of all materials required by the industrial unit and supplier materials as needed. Sometimes the total requirement for an item is such that the supplier is more likely to buy than he can Distribution centre it in his Electronic Components Distribution centre. You could have been influenced by the offer of a reduced price for the stock if you bought at least a certain amount. Or you can expect a season of strong sales and you want to be prepared in advance so you do not lose the chance to make big profits. Another may be an impending strike, subcontracting or lockout that may threaten a recovery period. He may want to prepare for this period by buying more than he can actually Distribution centre in his own Electronic Components Distribution centre. In busy markets such as supermarkets, community markets, etc., Distribution centre space for items is limited. If an attractive discount is available for bulk purchases, or if the purchase cost of the goods is greater than other costs related to inventory or demand for very large items or if there are problems with frequent purchases, management decides to buy a lot of items. Save time. These items cannot be Distribution centre in the existing warehouse in the booming market. In this case, an additional Distribution centre of Electronic Components is rented on a rental basis for the Distribution centre of surplus items.

The PSO algorithm is based on the social behavior of birds. This algorithm first creates a random population. Each individual called particle is given a speed and a small social network. For all particles, the values of the fitness or objective function are evaluated. On the basis of physical condition in relation to the PSO has no cross / mutation, but the personal optimum for each individual, the overall optimum in the total population and the neighborhood optimum found by the neighbors of each individual are Distribution centre for speed and position update each. This process is repeated until the maximum generations or convergence is reached.

## II. LITERATURE REVIEW

Yadav and Swami (2018) analyzed a integrated supply chain model for deteriorating items with linear stock dependent demand under imprecise and inflationary environment. Yadav and Swami (2018) discuss a partial backlogging production-inventory lot-size model with time-varying holding cost and weibull deterioration. Yadav, et., al. (2018) presented a supply chain inventory model for decaying items with two ware-house and partial ordering under inflation. Yadav, et., al. (2018) proposed an inventory model for deteriorating items with two warehouses and variable holding cost. Yadav, et., al. (2018) analyzed a inventory of electronic components model for deteriorating items with warehousing using genetic algorithm. Yadav, et., al. (2018) discuss a analysis of green supply chain inventory management for warehouse with environmental collaboration and sustainability performance using genetic algorithm. Yadav and kumar (2017) presented a electronic components supply chain management for warehouse with environmental collaboration & neural networks. Yadav, et., al. (2017) analyzed a effect of inflation on a two-warehouse inventory model for deteriorating items with time varying demand and shortages. Yadav, et., al. (2017) discuss an inflationary inventory model for deteriorating items under two storage systems. Yadav, et., al. (2017) proposed a fuzzy based two-warehouse inventory model for non instantaneous deteriorating items with conditionally permissible delay in payment. Yadav (2017) analyzed a analysis of supply chain management in inventory optimization for warehouse with logistics using genetic algorithm. Yadav, et., al. (2017) discuss a supply chain inventory model for two warehouses with soft computing optimization. Yadav, et., al. (2016) presented a multi objective optimization for electronic component inventory model & deteriorating items with two-warehouse using genetic algorithm. Yadav (2017) analyzed a modeling and analysis of supply chain inventory model with two-warehouses and economic load dispatch problem using genetic algorithm. Yadav, et., al. 2018 discuss a particle swarm optimization for inventory of auto industry model for two warehouses with deteriorating items. Yadav, et., al. (2018) analyzed a hybrid techniques of genetic algorithm for inventory of auto industry model for deteriorating items with two warehouses. Yadav, et., al. (2018) discuss a supply chain management of pharmaceutical for deteriorating items using genetic algorithm. Yadav, et., al. (2018) analyzed a particle swarm optimization of inventory model with two-warehouses. Yadav, et., al. (2018) presented a supply chain management of chemical industry for deteriorating items with warehouse using genetic algorithm.

## III. ASSUMPTIONS AND NOTATIONS

In developing the mathematical model of the inventory system the following assumptions are being made:

- 1) A single item is considered over a prescribed period T units of time.
- 2) The demand rate  $D(t)$  at time  $t$  is deterministic and taken as a ramp type function of time i.e.  

$$D(t) = (u_0 + \omega - 2)e^{-(\lambda_0 + \omega_1 - 2)t}, (u_0 + \omega - 2) > 0, (\lambda_0 + \omega_1 - 2) > 0$$
 The replenishment rate is infinite and lead-time is zero.
- 3) When the demand for goods is more than the supply. Shortages will occur. Customers encountering shortages will either wait for the vender to reorder (backlogging cost involved) or go to other vendors (lost sales cost involved). In this model shortages are allowed and the backlogging rate is  $\exp[-(\delta_0 + \omega_2 - 2)t]$ , when inventory is in shortage. The backlogging parameter  $(\delta_0 + \omega_2 - 2)$  is a positive constant.
- 4) The variable rate of deterioration in Electronic Components Distribution centre is taken as  $(\theta + \omega_2 - 2)(t) = (\theta + \omega_2 - 2)t$ .  
 Where  $0 < (\theta + \omega_2 - 2) \ll 1$  and only applied to on hand inventory.
- 5) No replacement or repair of deteriorated items is made during a given cycle.
- 6) The Electronic Components Distribution centre has unlimited capacity.

In addition, the following notations are used throughout this paper:

$Y_{ECDC}(t)$	The inventory level in Electronic Components Distribution centre at any time $t$ .
T	Planning horizon.
$(r_0 + \omega_3 - 2)$	Inflation rate.
$\zeta_{EHC}$	The holding cost per unit per unit time in Electronic Components Distribution centre.
$\zeta_{ECDC}$	The deterioration cost per unit.

- $\zeta_{ECSC}$  The shortage cost per unit per unit time.
- $\zeta_{ECLS}$  The opportunity cost due to lost sales.
- $\zeta_{ECOC}$  The replenishment cost per order.
- $ECDC_{TC}(t_1, T)$  Electronic Components Distribution centre Total Cost

#### IV. FORMULATION AND SOLUTION OF THE MODEL

The inventory level at Electronic Components Distribution centre is governed by the following differential equations:

$$\frac{dY_{ECDC}(t)}{dt} + (\theta + \omega_2 - 2)(t)Y_{ECDC}(t) = -(u_0 + \omega - 2)e^{-(\lambda_0 + \omega_1 - 2)t}, \quad 0 \leq t < t_1 \tag{1}$$

With the boundary condition  $Y_{ECDC}(0) = 0$ , the solution of the equation (1) is

$$Y_{ECDC}(t) = (u_0 + \omega - 2) \left\{ \begin{aligned} & \left[ (t_1 - t) - \frac{(\lambda_0 + \omega_1 - 2)}{2} (t_1^2 - t^2) \right] \\ & + \frac{(\theta + \omega_2 - 2)}{6} (t_2^3 - t^3) \end{aligned} \right\} e^{-(\theta + \omega_2 - 2)t^2 / 2}, \quad t_1 \leq t \leq t_2 \tag{2}$$

The total average cost consists of following elements:

##### A. Ordering Cost Per Cycle In Electronic Components Distribution Centre

$$ECDC_{OC} = \zeta_{ECOC} \tag{3}$$

##### B. Holding Cost Per Cycle In Electronic Components Distribution Centre

$$ECDC_{HC} = \zeta_{EHC} \left[ \int_0^{t_1} Y_{ECDC}(t) e^{-(r_0 + 2)t} dt \right]$$

$$= (\zeta_{EHC})(u_0 + \omega - 1) \left[ \begin{aligned} & \left[ \frac{t_1^2}{2} - \frac{(3(\lambda_0 + \omega_1 - 2) + (r_0 + 2))}{6} t_1^3 \right. \\ & + \left( \frac{(\theta + \omega_2 - 2)}{12} + \frac{(\lambda_0 + \omega_1 - 2)(r_0 + \omega_3 - 2)}{8} \right) t_1^4 \\ & \left. - \left( \frac{(r_0 + \omega_3 - 2)(\theta + \omega_2 - 2)}{20} - \frac{(\lambda_0 + \omega_1 - 2)(\theta + \omega_2 - 2)}{30} \right) t_1^5 \right] \end{aligned} \right] \tag{4}$$

##### C. Cost Of Deteriorated Units Per Cycle In Electronic Components Distribution Centre

$$ECDC_{DC} = \zeta_{ECDC} \left[ \begin{aligned} & \int_0^{t_1} (\theta + \omega_2 - 2)t Y_{ECDC}(t) e^{-(r_0 + \omega_3 - 2)t} dt \\ & + \int_{t_1}^{t_2} (\theta + \omega_2 - 2)t Y_{ECDC}(t) e^{-(r_0 + \omega_3 - 2)(t + t_1)} dt \\ & + \int_{t_2}^{\mu} (\theta + \omega_2 - 2)t Y_{ECDC}(t) e^{-(r_0 + \omega_3 - 2)(t + t_1)} dt \end{aligned} \right]$$

$$= \zeta_{ECDC} (\theta + \omega_2 - 2) \left[ \begin{array}{l} \left( \frac{t_1^2}{2} - \frac{(r_0 + \omega_3 - 2)t_1^3}{3} + \frac{(\theta + \omega_2 - 2)t_1^4}{8} \right) + (u_0 + \omega - 2)e^{-t_1(\lambda+r)} \\ \left[ \begin{array}{l} \frac{t_2^3}{6} - \frac{(r_0 + \omega_3 - 2)t_2^4}{12} + \frac{(\theta + \omega_2 - 2)t_2^5}{40} \\ - \frac{(r_0 + \omega_3 - 2)(\theta + \omega_2 - 2)t_2^6}{36} - \frac{t_1^2}{6}(3t_2 - 2t_1) \\ - \frac{(\theta + \omega_2 - 2)t_1^2(5t_2^3 - 2t_1^3)}{60} - \frac{(r_0 + \omega_3 - 2)t_1^3(4t_2 - 3t_1)}{12} \\ - \frac{(r_0 + \omega_3 - 2)(\theta + \omega_2 - 2)t_1^3(2t_2^3 - t_1^3)}{36} \\ - \frac{(\theta + \omega_2 - 2)\mu^4(5t_2 - 4t_1)}{40} \end{array} \right] \end{array} \right] \quad (5)$$

D. Shortage Cost Per Cycle In Electronic Components Distribution Centre

$$ECDC_{SC} = \zeta_{ECSC} \left[ \int_{t_2}^T -Y_{ECDC}(t)e^{-(r_0+\omega_3-2)(t_2+t)} dt \right]$$

$$= \frac{-(u_0 + \omega - 1)\zeta_{ECSC} e^{-((r_0+\omega_3-1)t_2+(\lambda_0+\omega_1-1)t_1)}}{(\delta_0 + \omega_2 - 1)} \left[ \int_{t_2}^T e^{-((r_0+\omega_3-1)+(\delta_0+\omega_2-1))t} dt - e^{-(\delta_0+\omega_2-1)t_2} \int_{t_2}^T e^{-(r_0+\omega_3-1)t} dt \right]$$

$$= \frac{(u_0 + \omega - 2)\zeta_{ECSC} e^{-((r_0+\omega_3-2)t_2+(\lambda_0+\omega_1-2)t_1)}}{(\delta_0 + \omega_2 - 2)(r_0 + \omega_3 - 2)[(\delta_0 + \omega_2 - 2) + (r_0 + 2)]} \left[ \begin{array}{l} (\delta_0 + \omega_2 - 2)e^{-((\delta_0+\omega_2-2)+(\lambda_0+2))t_2} \\ + e^{-((r_0+2)T} \left\{ \begin{array}{l} (r_0 + \omega_3 - 2)e^{-((\delta_0+\omega_2-2)T} \\ - \left[ \begin{array}{l} (\delta_0 + \omega_2 - 2) \\ + (r_0 + \omega_3 - 2) \end{array} \right] e^{-((\delta_0+\omega_2-2)t_2} \end{array} \right\} \end{array} \right] \quad (6)$$

E. Opportunity Cost Due To Lost Sales Per Cycle In Electronic Components Distribution Centre

$$ECDC_{LS} = \zeta_{ECLS} \int_{t_2}^T (u_0 + \omega - 2)(1 - e^{-(\delta_0+\omega_2-2)t}) e^{-(\lambda_0+\omega_1-2)t_1} e^{-(r_0+\omega_3-2)(t_2+t)} dt$$

$$= \frac{\zeta_{ECLS} (u_0 + \omega - 2) e^{-((\lambda_0+\omega_1-2)t_1+(r_0+\omega_3-2)t_2)}}{(r_0 + \omega_3 - 2)((\delta_0 + \omega_2 - 2) + (r_0 + \omega_3 - 2))} \left[ \begin{array}{l} e^{-((r_0+\omega_3-2)t_2} \left\{ \begin{array}{l} [(\delta_0 + \omega_2 - 2) + \\ (r_0 + \omega_3 - 2)] \\ - (r_0 + \omega_3 - 2) e^{-((\delta_0+\omega_2-2)t_2} \end{array} \right\} \\ - e^{-((r_0+\omega_3-1)T} \left\{ \begin{array}{l} [(\delta_0 + \omega_2 - 2) \\ + (r_0 + \omega_3 - 2)] \\ - (r_0 + \omega_3 - 2) e^{-((\delta_0+\omega_2-2)T} \end{array} \right\} \end{array} \right] \quad (7)$$

Therefore, the total average cost per unit time of our model is obtained as follows

$$ECDCTC(t_1, T) = \frac{1}{T} [ECDC_{OC} + ECDC_{HC} + ECDC_{DC} + ECDC_{SC} + ECDC_{LS}] \tag{8}$$

$$\begin{aligned}
 & \left\{ \zeta_{ECOC} \right\} + \left\{ (\zeta_{EHC}) (u_0 + \omega - 2) \left[ \frac{t_1^2}{2} - \frac{(3(\lambda_0 + \omega_1 - 2) + (r_0 + 2))}{6} t_1^3 \right. \right. \\
 & \left. \left. + \left( \frac{(\theta + \omega_2 - 2)}{12} + \frac{(\lambda_0 + \omega_1 - 2)(r_0 + \omega_3 - 2)}{8} \right) t_1^4 \right. \right. \\
 & \left. \left. - \left( \frac{(r_0 + \omega_3 - 2)(\theta + \omega_2 - 2)}{20} - \frac{(\lambda_0 + \omega_1 - 2)(\theta + \omega_2 - 2)}{30} \right) t_1^5 \right] \right\} \\
 & + \left\{ \zeta_{EADC} (\theta + \omega_2 - 1) \left[ \left( \frac{t_1^2}{2} - \frac{(r_0 + \omega_3 - 2)t_1^3}{3} + \frac{(\theta + \omega_2 - 2)t_1^4}{8} \right) + (u_0 + \omega - 2)e^{-t_1(\lambda+r)} \right] \right. \\
 & \left. \left[ \left( \frac{t_2^3}{6} - \frac{(r_0 + \omega_3 - 2)t_2^4}{12} + \frac{(\theta + \omega_2 - 2)t_2^5}{40} \right) \right. \right. \\
 & \left. \left. - \frac{(r_0 + \omega_3 - 2)(\theta + \omega_2 - 2)t_2^6}{36} - \frac{t_1^2}{6} (3t_2 - 2t_1) \right. \right. \\
 & \left. \left. - \frac{(\theta + \omega_2 - 2)t_1^2 (5t_2^3 - 2t_1^3)}{60} - \frac{(r_0 + \omega_3 - 2)t_1^3 (4t_2 - 3t_1)}{12} \right. \right. \\
 & \left. \left. - \frac{(r_0 + \omega_3 - 2)(\theta + \omega_2 - 2)t_1^3 (2t_2^3 - t_1^3)}{36} \right. \right. \\
 & \left. \left. - \frac{(\theta + \omega_2 - 2)\mu^4}{40} (5t_2 - 4t_1) \right] \right\} \\
 & + \left\{ \frac{(u_0 + \omega - 2)\zeta_{EASC} e^{-(r_0 + \omega_3 - 2)t_2 + (\lambda_0 + \omega_1 - 2)t_1}}{(\delta_0 + \omega_2 - 2)(r_0 + \omega_3 - 2)[(\delta_0 + \omega_2 - 2) + (r_0 + 2)]} \right. \\
 & \left. \left[ e^{-(\delta_0 + \omega_2 - 2)(r_0 + 2)t_2} \left\{ (r_0 + \omega_3 - 2) e^{-(\delta_0 + \omega_2 - 2)T} \right. \right. \right. \\
 & \left. \left. - \left[ (\delta_0 + \omega_2 - 2) \right. \right. \right. \\
 & \left. \left. \left. + (r_0 + \omega_3 - 2) \right] e^{-(\delta_0 + \omega_2 - 2)t_2} \right\} \right] \right\} \\
 & + \left\{ \frac{\zeta_{EALS} (u_0 + \omega - 2) e^{-(\lambda_0 + \omega_1 - 2)t_1 + (r_0 + \omega_3 - 2)t_2}}{(r_0 + \omega_3 - 2)((\delta_0 + \omega_2 - 2) + (r_0 + \omega_3 - 2))} \right. \\
 & \left[ e^{-(r_0 + \omega_3 - 2)t_2} \left\{ \left[ (\delta_0 + \omega_2 - 2) + \right. \right. \right. \\
 & \left. \left. \left[ (r_0 + \omega_3 - 2) \right. \right. \right. \\
 & \left. \left. \left. - (r_0 + \omega_3 - 2) e^{-(\delta_0 + \omega_2 - 2)t_2} \right\} \right. \right. \\
 & \left. \left[ -e^{-(r_0 + \omega_3 - 2)T} \left\{ \left[ (\delta_0 + \omega_2 - 2) \right. \right. \right. \right. \\
 & \left. \left. \left. + (r_0 + \omega_3 - 2) \right] \right. \right. \right. \\
 & \left. \left. \left. - (r_0 + \omega_3 - 2) e^{-(\delta_0 + \omega_2 - 2)T} \right\} \right] \right\} \tag{9}
 \end{aligned}$$

To minimize the total cost per unit time, the optimal values of  $t_1$  and  $T$  can be obtained by solving the following equations simultaneously

$$\frac{\partial ECDCTC}{\partial t_1} = 0 \tag{9}$$

$$\text{and } \frac{\partial ECDCTC}{\partial T} = 0 \tag{10}$$

provided, they satisfy the following conditions

$$\text{and } \left. \begin{aligned} \frac{\partial^2 ECDCTC}{\partial t_1^2} > 0, \frac{\partial^2 ECDCTC}{\partial T^2} > 0 \\ \left( \frac{\partial^2 ECDCTC}{\partial t_1^2} \right) \left( \frac{\partial^2 ECDCTC}{\partial T^2} \right) - \left( \frac{\partial^2 ECDCTC}{\partial t_1 \partial T} \right)^2 > 0 \end{aligned} \right\} \tag{11}$$

Therefore, numerical solution of these equations is obtained by using the software MATLAB 7.0.1.

**V. GENETIC ALGORITHM ELECTRONIC COMPONENTS DISTRIBUTION CENTRE INVENTORY CONTROL**

Which shows the steps to optimize the analysis? Initially, overstocks and stocks of different suppliers in the Electronic Components Distribution centre are represented by zero or non-zero values. Zero means that the contributor does not need to monitor the Electronic Components Distribution centre Inventory, while non-zero data requires control of the Electronic Components Distribution centre Inventory. Nonzero data indicates inventory and bottleneck. The surplus amount is expressed in a positive value, and the deficit amount is in a negative value. The first process is clustering, which combines either higher or lower stocks, and stocks that are neither excessive nor insufficient. This is done simply by grouping zero and non-zero values. For this, we use the Economic Dispatch algorithm. After performing the process of distribution of the economic burden using a genetic algorithm, the work begins with a genetic algorithm, which is the core of our work. To distribute the economic load using a genetic algorithm instead of generating a random population of random chromosomes, a random chromosome is generated at each iteration point for a subsequent operation.

The total production cost and the error has to be minimized which leads to the maximization of fitness function

*A. Chromosome*

A randomly generated initial chromosome is created by keeping stocks at the lower and upper limits for all participants in the blood supply chain, plants, and distribution centers. As we know, the chromosome consists of genes that determine the length of the chromosomes. The inventory of each member of the chromosome is called the chromosome gene. A randomly generated initial chromosome is created by keeping stocks at the lower and upper limits for all participants in the blood supply chain, plants, and distribution centers. As we know, the chromosome consists of genes that determine the length of the chromosomes. The inventory of each member of the chromosome is called the chromosome gene.

Chromosome 1				
87	85	-79	-69	50
Chromosome 2				
88	92	89	75	-59

Fig. 2 Random specimen created for genetic operation

These types of chromosomes are produced for genetic surgery. Initially, only two chromosomes are generated, and one random chromosome value is generated from the next generation. The resulting chromosomes are then used to determine the number of entries in the database contents using the select count () function. The function indicates the number of occurrences / repetitions of the corresponding inventory for ten items that will continue to be used in the format function.

*B. Selection*

The selection operation is the first genetic operation responsible for selecting the most appropriate chromosome for the subsequent genetic operation. This is achieved by providing a rating based on the form calculated for each of the predominant chromosomes. Based on this classification, the best chromosomes are selected for the subsequent procedure.

**C. Fitness**

Formatting functions ensure that evolution proceeds to optimization by calculating the form value for each person in the population. A fitness score assesses each person’s performance in a population.

$$U(i) = \log\left(1 - \frac{MP}{Mq}\right) \quad i= 1,2,3,4,5,6,7LL, n$$

Where, MP is the number of counts that occurs throughout the period.

Mq is the total number of inventory values obtained after clustering.

n is the total number of chromosomes for which the fitness function is calculated.

A fitness function is performed for each chromosome, and the chromosomes are sorted according to the result of the fitness function. Subsequently, the chromosomes of the genetic operation are crossed and mutated.

**D. Crossover**

In this study, the intersection operation uses the intersection operator of one point. The first two chromosomes in the marriage pool are selected for the operation of crossing. The intersection operation performed for the sample case is shown in Figure 3 below.

Before Crossover				
87	79	-69	68	78
86	-76	-68	71	81
After Crossover				
96	91	57	-41	70
-90	86	-70	74	72

Fig.3. Chromosome representation

The genes on the right side of the intersection point in both chromosomes are exchanged, and a crossing operation takes place. After the operation, two new chromosomes are obtained.

**E. Mutation**

Newly acquired chromosomes during a crossing operation are forced to mutate. A mutation creates a new chromosome (see Image below).

Before Mutation				
91	-82	78	85	-77
After Mutation				
91	80	-79	-58	75

Fig. Chromosomes subjected to operation

This is done by randomly generating two points and then exchanging between both genes.

The mutation operation produces new chromosomes that are not like the chromosomes originally produced. After receiving a new chromosome, another random chromosome number is generated. Then again, the process repeats over a series of iterations, while both chromosomes exposed to the process are determined by the result of the fitness function. Each number of iterations gives a better chromosome, and this is considered the best solution for controlling blood counts. If the number of iterations increases, then the resulting solution is very close to the exact solution. The greater the number of iterations in the ideal optimal solution. At some point, using the help genetic algorithm, which will be the best stock, may occur in the predictions of the members of the blood supply chain from past records, and, consequently, losses due to the preservation of excess reserves and deficit can be reduced in the next few days. ,



**VI. NUMERICAL ILLUSTRATION**

To illustrate the model numerically the following parameter values are considered.

$(u_0 + \omega - 2) = 220$  units,  $\zeta_{ECOC} =$  Rs. 220 per order,  $(r_0 + \omega_3 - 2) = 2.25$  unit,  $(\lambda_0 + \omega_1 - 2) = 0.24$  unit,  $\zeta_{ECHC} =$  Rs. 20.10 per unit,  $\theta = 0.204$  unit,  $t_1 = 0.24$  year,  $\zeta_{ECLS} =$  Rs. 8.20 per unit,  $(\delta_0 + \omega_2 - 2) = 0.22$  unit,  $T = 2$  year,

Then for the minimization of total average cost and with help of software. the optimal policy can be obtained such as:

$t_2 = 2.99$  year,  $S = 276.8991$  units and E.C.D.C.T.C. = Rs.2326.28 per year.

Comparison of the optimization methods GA to enhance Electronic Components Distribution centre Inventory in presence of FACTS device is presented in this section. The control parameter values for all the optimization algorithms are given below

GA: real coded,

Population=60

Generations=600

Crossover probability=1.0

Mutation probability=0.2

**VII. SENSITIVITY ANALYSIS**

Table:-1 Effect on optimal solution for distinct values of demand parameter  $(u_0 + \omega - 2)$

% change in $(u_0 + \omega - 2)$	$(u_0 + \omega - 2)$	T	TCECDC
-20	252.5	282.65	2250.53
-15	254	282.57	2249.35
0	256.7	282.55	2248.23
15	258	282.85	2248.00
20	250.2	282.75	2247.98

Table:-2 Effect on optimal solution for distinct values of demand parameter  $(\lambda_0 + \omega_1 - 2)$

% change in $(\lambda_0 + \omega_1 - 2)$	$(\lambda_0 + \omega_1 - 2)$	T	TCECDC
-20	20.62	232.65	2380.53
-15	20.62	232.57	2379.35
0	20.7	232.55	2368.23
15	20.72	231.85	2358.00
20	20.72	231.75	2347.98

Table:-3 Effect on optimal solution for distinct values of backloging parameter  $(\delta_0 + \omega_2 - 2)$

% change in $(\delta_0 + \omega_2 - 2)$	$(\delta_0 + \omega_2 - 2)$	T	TCBBS
-20	20.43	222.65	2898.53
-15	20.49	222.57	2897.34
0	20.53	222.55	2996.23
15	20.55	230.85	2996.00
20	20.54	230.75	2995.98

Table:-4 Effect on optimal solution for distinct values of selling price ( $\zeta_{BLS}$ )

% change in $\zeta_{ECLS}$	$\zeta_{ECLS}$	T	TCECDC
-20	224.5	252.65	2478.53
-15	224.9	252.57	2477.35
0	225.0	252.55	2476.23
15	225.2	252.85	2476.20
20	225.9	252.75	2475.98

Table:-5 Effect on optimal solution for distinct values of deterioration parameter ( $\theta + \omega_2 - 2$ )

% change in $(\theta + \omega_2 - 2)$	$(\theta + \omega_2 - 2)$	T	TCECDC
-20	20.00	272.65	2308.53
-15	20.62	272.57	2307.35
0	20.7	272.55	2306.23
15	20.72	270.85	2306.00
20	20.74	270.75	2305.98

Optimization of control Electronic Components Distribution centre inventory in Electronic Components Distribution centre supply chain management using genetic algorithms is analyzed using MATLAB. Inventory levels for three different participants in the Electronic Components Distribution centre supply chain, ordering cost, holding cost, Deterioration cost, shortage cost and lost sales cost are created using the MATLAB script. This generated data set is used to evaluate the performance of a genetic algorithm. Some examples of the data sets used in the implementation are listed in Table 6. Table 6 lists about 5 records that are assumed to be records for the past period.

Table 6.: - Lists about 5 records that are assumed to be records for the past period

S.N.	Ordering cost	Holding cost	Deterioration cost	Shortage cost	lost sales cost
1	66	15	46	-49	66
2	-70	25	47	56	66
3	74	35	-55	58	66
4	75	-45	57	62	66
5	-79	46	-60	53	-51

Table: -7 Genetic Algorithm (GA) model optimal solution

P	WW	GA			
	OPT	BEST	MAX	AVG	STD
1	2225.20	5272.20	3272.20	3262.20	1252.20
2	2252.22	5272.22	3272.22	3262.22	1252.22
3	2252.22	5272.22	3273.22	3263.22	1253.22
4	2252.23	5272.23	3273.23	3263.23	1253.23
5	2252.24	5272.24	3273.24	3263.24	1253.24
6	2252.54	5273.54	3274.54	3264.54	1254.54
7	2252.58	5273.58	3274.58	3264.58	1254.58

### VIII. OBSERVATIONS

- A. Table 1 shows the effect of demand parameter  $(u_0 + \omega - 2)$  on T and on *TCECDC* from this, we have noticed that an increase in demand parameter  $(u_0 + \omega - 2)$  shows a reverse effect of decrement in T and the same effect of increment in *TCECDC*
- B. Table 2 presents the effect of demand parameter  $(\lambda_0 + \omega_1 - 2)$  on T and on *TCECDC* It is noticed that with an increment in demand parameter  $(\lambda_0 + \omega_1 - 2)$ , values of 'T' increase while value of *TCECDC* decreases.
- C. Table 3 presents the deviation of backloging parameter  $(\delta_0 + \omega_2 - 2)$  at distinct points and it is noticed that as backloging parameter  $(\delta_0 + \omega_2 - 2)$  increases, the values of T and *TCECDC* decrease.
- D. Table 4 lists the variation in selling price  $\zeta_{ECLS}$  and from this; we have noticed that an increment in selling price shows maintains a reverse effect of decrement in *TCECDC*.
- E. Table 5 shows the deviation of deterioration parameter  $(\theta + \omega_2 - 2)$  at distinct points and it is noticed that as deterioration parameter  $(\theta + \omega_2 - 2)$  increases, the values of and 'T' decrease while *TCECDC* increases.

### IX. CONCLUSION

This study incorporates some realistic features that are likely to be associated with the Electronic Components Distribution centre inventory of any material using Genetic Algorithm. Decay (deterioration) overtime for any material product and occurrence of shortages in inventory are natural phenomenon in real situations using Genetic Algorithm. Electronic Components Distribution centre Inventory shortages are allowed in the model using Genetic Algorithm. In many cases customers are conditioned to a shipping delay, and may be willing to wait for a short time in order to get their first choice using Genetic Algorithm. Generally speaking, the length of the waiting time for the next replenishment is the main factor for deciding whether the backloging will be accepted or not using Genetic Algorithm.

The willingness of a customer to wait for backloging during a shortage period declines with the length of the waiting time using Genetic Algorithm.

Thus, Electronic Components Distribution centre inventory shortages are allowed and partially backordered in the present chapter and the backloging rate is considered as a decreasing function of the waiting time for the next replenishment using Genetic Algorithm. Demand rate is taken as exponential ramp type function of time, in which demand decreases exponentially for some initial period and becomes steady later on using Genetic Algorithm. Since most decision makers think that the inflation does not have significant influence on the inventory policy, the effects of inflation are not considered in some inventory models. However, from a financial point of view, an inventory represents a capital investment and must complete with other assets for a firm's limited capital funds using Genetic Algorithm.

Thus, it is necessary to consider the effects of inflation on the inventory system. Therefore, this concept is also taken in this model. From the numerical illustration of the model, it is observed that the period in which inventory holds increases with the increment in backloging and ramp parameters while inventory period decreases with the increment in deterioration and inflation parameters. Initial inventory level decreases with the increment in deterioration, inflation and ramp parameters while inventory level increases with the increment in backloging parameter using Genetic Algorithm.

The total average cost of the system goes on increasing with the increment in the backloging and deterioration parameters while it decreases with the increment in inflation and ramp parameters. The proposed model can be further extended in several ways. For example, we could extend this deterministic model in to stochastic model. Also, we could extend the model to incorporate some more realistic features, such as quantity discount or the unit purchase cost, the inventory holding cost and others can also have taken fluctuating with time using Genetic Algorithm.



## REFERENCES

- [1] Yadav, A.S. and Swami, A. (2018) Integrated Supply Chain Model For Deteriorating Items With Linear Stock Dependent Demand Under Imprecise And Inflationary Environment. *International Journal Procurement Management*, Volume 11 No 6.
- [2] Yadav, A.S. and Swami, A. (2018) A partial backlogging production-inventory lot-size model with time-varying holding cost and weibull deterioration *International Journal Procurement Management*, Volume 11, No. 5.
- [3] Yadav, A.S., Swami, A. and Kumar, S. (2018) A supply chain Inventory Model for decaying Items with Two Ware-House and Partial ordering under Inflation. *International Journal of Pure and Applied Mathematics*, Volume 120 No 6.
- [4] Yadav, A.S., Swami, A. and Kumar, S. (2018) An Inventory Model for Deteriorating Items with Two warehouses and variable holding Cost *International Journal of Pure and Applied Mathematics*, Volume 120 No 6.
- [5] Yadav, A.S., Swami, A. and Kumar, S. (2018) Inventory of Electronic components model for deteriorating items with warehousing using Genetic Algorithm. *International Journal of Pure and Applied Mathematics*, Volume 119 No. 16.
- [6] Yadav, A.S., Johri, M., Singh, J. and Uppal, S. (2018) Analysis of Green Supply Chain Inventory Management for Warehouse With Environmental Collaboration and Sustainability Performance Using Genetic Algorithm. *International Journal of Pure and Applied Mathematics*, Volume 118 No. 20.
- [7] Yadav, A.S., and Kumar, S. (2017) Electronic Components Supply Chain Management for Warehouse with Environmental Collaboration & Neural Networks. *International Journal of Pure and Applied Mathematics*, Volume 117 No. 17.
- [8] Yadav, A.S., Taygi, B., Sharma, S. and Swami, A. (2017) Effect of inflation on a two-warehouse inventory model for deteriorating items with time varying demand and shortages *International Journal Procurement Management*, Volume 10, No. 6.
- [9] Yadav, A.S., Mahapatra, R.P., Sharma, S. and Swami, A. (2017) An Inflationary Inventory Model for Deteriorating items under Two Storage Systems *International Journal of Economic Research*, Volume 14 No.9.
- [10] Yadav, A.S., Sharma, S. and Swami, A. (2017) A Fuzzy Based Two-Warehouse Inventory Model For Non instantaneous Deteriorating Items With Conditionally Permissible Delay In Payment, *International Journal of Control Theory And Applications*, Volume 10 No.11.
- [11] Yadav, A.S., (2017) Analysis Of Supply Chain Management In Inventory Optimization For Warehouse With Logistics Using Genetic Algorithm *International Journal of Control Theory And Applications*, Volume 10 No.10.
- [12] Yadav, A.S., Swami, A., Kher, G. and Kumar, S. (2017) Supply Chain Inventory Model for Two Warehouses with Soft Computing Optimization *International Journal of Applied Business and Economic Research* Volume 15 No 4.
- [13] Yadav, A.S., Mishra, R., Kumar, S. and Yadav, S. (2016) Multi Objective Optimization for Electronic Component Inventory Model & Deteriorating Items with Two-warehouse using Genetic Algorithm *International Journal of Control Theory and applications*, Volume 9 No.2.
- [14] Yadav, A.S., (2017) Modeling and Analysis of Supply Chain Inventory Model with two-warehouses and Economic Load Dispatch Problem Using Genetic Algorithm *International Journal of Engineering and Technology (IJET)* Volume 9 No 1.



10.22214/IJRASET



45.98



IMPACT FACTOR:  
7.129



IMPACT FACTOR:  
7.429



# INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24\*7 Support on Whatsapp)