



iJRASET

International Journal For Research in
Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 3

Issue: V

Month of publication: May 2015

DOI:

www.ijraset.com

Call:  08813907089

E-mail ID: ijraset@gmail.com

Compare results of restoration of Motion Blurred Images using Non Blind Techniques

Shaili¹, Garima Garg²

¹M.Tech student, ²Assistant Professor

^{1,2} Samalkha Group of Institution

Abstract: Image deblurring and restoration has been of great importance nowadays. Image recognition becomes difficult when it comes to blurred and poorly illuminated images and it is here image restoration come to picture. In this paper, we will examine various existing techniques are compared with the proposed PDE techniques and are shown that results are of better quality than these techniques. The comparison is done on the basis of the calculated PSNR for different techniques and for various noises.

The aim or objective of this thesis “Comparative Analysis of Various Techniques for Non-Blind Restoration of Images” is designed to compute approximation of true images when a blurred image and some information about blurring is given.

I. IMPORTANCE OF POINT SPREAD FUNCTION (PSF)

The quality of the deblurred image is mainly determined by knowledge of the PSF. the fundamental task of deblurring is to deconvolve the blurred image with the PSF that exactly describes the distortion

A. Non-Blind Deblurring

In this technique we have prior knowledge of PSF. It is just reverse process of blurring process.

In this section we introduce the different techniques of image deblurring.

The objective of this paper is:-

To compare the various deblurring techniques for the non-blind image deblurring. We are comparing various techniques like

- 1) Wiener Filter ,Median Filter
- 2) Horizontal deblurring algorithm
- 3) Vertical deblurring algorithm
- 4) combination of both algorithms

We are performing non blind deblurring for motion blurred images.

We have compared the results for various deblurring techniques on the PSNR values.

- 1) *Weiner Filter:* The method is founded on considering image and noise as random process and objective is to find an estimate of deblurred image of the uncorrupted image such that mean square error between them is minimized. The simplest approach is to restore the original image simple by dividing the transform of degraded image by degradation function.

$$F(u, v) = F(u, v) + N(u, v) / H(u, v)$$

- a) *Order Statistics Filters:* These are the spatial filters whose response is based on the ordering of the pixels contained in the image area and compassed by the filter. The response of the filter at any point is determined by ranking result.

$$F_1(x, y) = \text{median}\{g(s, t)\} \quad (4.2) F_1(x, y) = \max\{g(s, t)\}$$

$$(4.3) F_1(x, y) = \text{mean}\{g(s, t)\}$$

(4.4)

- b) *PDE Method:* From the 1-D flux partial conservative equation

$$\partial g / \partial t = -v \partial g / \partial x$$

Also analytically the general solution of this equation is a wave propagating in the positive x-direction is $g=f(x-vt)$ which models our image blurring process.

After discretization of this scheme by FTCS(Finite Time Centered Scheme) we get

International Journal for Research in Applied Science & Engineering Technology (IJRASET)

$$\left(\frac{g_j^{n+1} - g_j^n}{\Delta t} \right) = -v \left(\frac{g_{j+1}^n - g_{j-1}^n}{2\Delta x} \right)$$

$$I_t = I_t - (v\Delta t) \frac{\partial g}{\partial x} + \frac{(\Delta x)^2}{2} \frac{\partial^2 g}{\partial x^2}$$

2) *The Horizontal Deblurring Algorithm:* The Algorithm for this scheme is as follows:-

- a) Read the original image of size mxn.
- b) Introduce the motion blur in x direction to get g (x, y, t) or alternatively we can directly have the blurred image g (x, y, t).
 It =g(x, y): Initial Image

c) Set dx=0. 1,dt = 0.1

d) for t=1:niterations

$$I_t = I_t - (v\Delta t) \frac{\partial g}{\partial x} + \frac{(\Delta x)^2}{2} \frac{\partial^2 g}{\partial x^2}$$

e) Display the image

3) *The Vertical Deblurring Algorithm:* The Algorithm for this scheme is as follows:-

- a) Read the original image s of size mxn.
- b) Introduce the motion blur in y direction to get s(y, x, t) or alternatively we can directly have the blurred image s(y, x, t).
 Id =s(y, x): Initial Image

c) Set dy=0. 1,dt = 0.1

d) for t=1: n iterations

$$I_d = id - (v\Delta t) \frac{\partial s}{\partial y} + \frac{(\Delta y)^2}{2} \frac{\partial^2 s}{\partial y^2}$$

e) Display the image

4) *The Combined Deblurring Algorithm:* The Algorithm for this scheme is as follows:-

- a) Initial Image I = K(x,y)
- b) Set dx=0.1,dt=0.1, no_iterations=50, v_x =1
 For t=1: no_iterations

$$I = I - (v_x \Delta t) \frac{\partial k}{\partial x} + \frac{(\Delta x)^2}{2} \frac{\partial^2 k}{\partial x^2}$$

c) R=I

Set dy=0.1,dt=0.1, num_iterations=50, v_y =1

$$R = R - (v_y \Delta t) \frac{\partial I}{\partial y} + \frac{(\Delta y)^2}{2} \frac{\partial^2 I}{\partial y^2}$$

d) Get R and display as final deblurred Image.


e)

II. RESULTS

Result Median Filter(Horizontal Blur)


PSNR Value=44.7412

International Journal for Research in Applied Science & Engineering Technology (IJRASET)




Results Median Filter (Vertical Blur)

PSNR value=26.6929



Results Median Filter (Combine Blur)


PSNR Value=18.2979



Results Weiner Filter (Horizontal Blur)


PSNR Value= 10.2344

International Journal for Research in Applied Science & Engineering Technology (IJRASET)




Results Weiner Filter (Vertical Blur)

PSNR Value = 11.1457



Results Weiner Filter (Combine Blur)


PSNR Value = 8.3513



Results PDE(Horizontal Blur)


PSNR Value = 37.8898

International Journal for Research in Applied Science & Engineering Technology (IJRASET)




Results PDE(Vertical Blur)

PSNR Value = 38.3336



Results PDE(Combine Blur)

PSNR Value = 13.2344



International Journal for Research in Applied Science & Engineering Technology (IJRASET)

III. CONCLUSION

In this research various methods for noise reduction have been analyzed. In the analysis, various well-known measuring metrics have been used. The results show that by using the PDE noise reduction is much better compared to other methods. The PDE technique is much efficient than these for the motion blurring. The vertical deblurring shows the better results than horizontal and combined deblurring in PDE.

REFERENCES

- [1] Rajeev Srivastava, Harish Parthasarthy, JRP Gupta and D. Roy Choudhary, "Image Restoration from Motion Blurred Image using PDEs formalism", IEEE International Advance Computing Conference, 2009.
- [2] Many V. Afonso, Jose M. Bioucas-Dias and Mario A.T. Figueiredo, "Fast Image Recovery Using Variable Splitting and Constrained Optimization", IEEE Transactions on Image Processing, 2010.
- [3] A. Beck and M. Teboulle, "A fast iterative shrinkage-thresholding algorithm for linear inverse problems", SIAM Journal on Imaging Sciences, 2009.
- [4] J. Bioucas-Dias and M. Figueiredo, "A new TwIST: two-step iterative shrinkage/thresholding algorithms for image restoration", IEEE Transactions on Image Processing, 2007.
- [5] J. Bioucas-Dias and M. Figueiredo, "An iterative algorithm for linear inverse problems with compound regularizers", IEEE International Conference on Image Processing, 2008.
- [6] A. Chambolle, "An algorithm for total variation minimization and applications," J. Math. Imaging Vis, 2004.
- [7] M. Figueiredo and R. Nowak. "An EM algorithm for wavelet-based image restoration." IEEE Transactions on Image Processing, 2003.
- [8] T. Goldstein and S. Osher, "The split Bregman algorithm for L1 regularized problems", SIAM Journal on Imaging Sciences, 2009.
- [9] E. Esser, "Applications of Lagrangian-based alternating direction methods and connections to split-Bregman", Technical Report 09-31, Computational and Applied Mathematics, University of California, Los Angeles, 2009.
- [10] S. Wright, R. Nowak, M. Figueiredo, "Sparse reconstruction by separable approximation, IEEE Transactions on Signal Processing, ,2009.
- [11] Gonzalez C. Rafeal, Woods Mackwills C. Richard, "Digital Image Processing", London: Pearson Education, 2002.
- [12] Biegler, L., "Real-Time PDE-Constrained Optimization", SIAM- Journal on Imaging Sciences, 2007.
- [13] Chunlin Wu, "Augmented Lagrangian Method for Total Variation Restoration with Non-Quadratic Fidelity", SIAM- Journal on Imaging Sciences, 2008.



10.22214/IJRASET



45.98



IMPACT FACTOR:
7.129



IMPACT FACTOR:
7.429



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24*7 Support on Whatsapp)