



# IJRASET

International Journal For Research in  
Applied Science and Engineering Technology



---

# INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

---

**Volume: 9      Issue: IV      Month of publication: April 2021**

**DOI: <https://doi.org/10.22214/ijraset.2021.33692>**

**[www.ijraset.com](http://www.ijraset.com)**

**Call:  08813907089**

**E-mail ID: [ijraset@gmail.com](mailto:ijraset@gmail.com)**

# Implementation of Floating Building for the Areas with the Rising Sea Level Problems

Prasoon Sharma<sup>1</sup>, Tauseef Rahi<sup>2</sup>

<sup>1</sup>Student, <sup>2</sup>Faculty Member, Faculty of Architecture and Planning, Abdul Kalam Technical University, Lucknow, India

**Abstract:** For quite a long time, the coastline has been the concentration for assortment of exercises including enterprises, farming, amusement and fisheries. All the significant urban communities in India have created along the coastline. Over the previous hundreds of years, the water level expanded almost eight crawls in the water front region and the researchers propose a steady expansion in water level because of climatic change. There are two main considerations for water level ascent, liquefying of ice sheets and warm development of water.

These variables are the aftereffect of an Earth-wide temperature boost which can't be changed without any problem. The water level ascent will have different effects like moving from seaside zones, regular flooding, dissolve water shores; the net outcome will be movement from this thickly populated zones.

India is a peninsular country three sides covered with water. It faces a hefty rainstorm season that causes enormous scope obliteration all through the country. Enduring waterways like Ganga, Brahmaputra, and so forth consistently causes flooding in north India and typhoons and substantial rainstorm are the purpose behind flood in southern pieces of India. India is the one of the weak country for climatic change. It should attempt to give flood confirmation, protected and moderate designs for all residents. This report will investigate and records the different methods of securing and establishing a reasonable living climate for coastline and costal inhabitants. This will record the projection water level ascent and in change in environment will expand the frequencies of flood. This exposition will address the inquiries like "How could a construction sits in ground can get by during floods?" The methods to give low flood occupants Amphibious lodging working both in land and water. Amphibious Architecture is financially savvy and safe option for perpetual static height and it is accomplished by light establishments.

**Index Terms:** Amphibious Architecture, Aquatecture, Buoyancy, Buoyant plates, Architecture.

## I. INTRODUCTION

Aquatecture is defined as a design transformation typology used to alleviate and oversee flooding (long and present moment). With this typology, water and engineering configuration can join to create dynamic and solid alleviation arrangements.

- 1) The primary game-plan includes rethinking three principle living frameworks: a home, an area, and a private pinnacle to oppose annihilation of rising water levels and to proceed with city-condo inhabitation. Notwithstanding versatile structure configuration, supporting frameworks will be coordinated all through influenced regions. Frameworks like elective energy creation, elective cultivating, blended utilized industry, elective transportation, and water filtration zones will be fused.
- 2) With the assistance of Aquatecture, options in contrast to relinquishing our costal front urban areas are given.
- 3) Due to the adaptability of site area that Aquatecture permits, this intercession can fill in as a drawn out arrangement and way of life inside current and projected flood inclined regions around the planet.
- 4) The want to live adjoining mirrors our social legacy and notable settlement examples, and we keep on expanding on flood fields and other flooding-inclined regions.
- 5) However, waterfront safeguards, for example, the waterway obstructions in the Netherlands and the levee framework in New Orleans, have demonstrated inadequate with regards to a radical ascent in sea level.
- 6) More than 20M individuals will confront the disastrous annihilation with Global Sea Level Rise.
- 7) In request to shield our networks against rising sea levels and flooding, long haul ways to deal with building configuration should be viewed as that will give elective dwelling freedoms to waterfront occupants.
- 8) As much as 90% of the 100 biggest urban areas on the planet are situated on water. Besides, these urban communities have a significant measure of water in the actual city, as lakes, streams, trenches, harbors sounds or open seas. Aquatecture is defined as an architectural adaptation typology used to mitigate and manage flooding (long and short term). With this typology, water and architectural design can unite to produce dynamic and reliable mitigation solutions.

**A. Need For Study**

Environmental Change: A Global Crisis Our reality is definitely evolving. Inside the recent years, environmental change has become a developing concern around the world. The different methods of obliteration forced on our current circumstance are focused to be the impetus to these changes. A significant expansion in tropical storm action, observable variances in temperature, and a convergence in CO2 discharges have all been noted worries for some. One of the essential feelings of dread originating from a dangerous atmospheric deviation is that not exclusively will climate designs become more extreme and capricious, yet our seas will rise and annihilate our coastlines, structures, homes, and networks around the world.



Figure 1.2.1: visible change in costal lines



Figure 1.2.2: Flooding Effects

As indicated by environment researchers, ocean level ascent is "Perhaps the main effects of worldwide environmental change." Sea level has been ascending in the course of recent years, and a dangerous atmospheric deviation is required to build the yearly rate by two to multiple times.

Fundamental Contributions to Sea Level Rise. The tremendous field of ice that has described the Arctic Ocean is anticipated to "totally dissolve far quicker than anybody has envisioned, and will positively be gone before the century is out." Current projections of ocean level ascent "ought to be of rising ocean level into significant worry for seaside zones and little islands." The primary flooding of sink territories of the nation as well. Supporter of worldwide ocean level ascent is relied upon to come from warm Variations which the coasts will encounter development of sea water, trailed by an expanded softening of glacial masses and ice covers.

## Regions Vulnerable to Sea Level Rise




Figure 1.2.4: World map showing regions Vulnerable to rising sea levels

*B. Need For Study Regarding The Indian Subcontext And In Respect To Cities Like Mumbai And Kolkata*

The wonder of rising oceans has been noticed everywhere on the world, including India, and its effect investigated in an extraordinary report distributed by the United Nations' Intergovernmental Panel on Climate Change (IPCC)

- 1) Is India ready to tackle the dangers occurring due to SLR? The country's coastline stretches 7,500-odd km and runs past nine states, including state capitals. The east coast, hemmed by the Bay of Bengal, is often pelted by cyclones, and the hitherto placid Arabian Sea on the west warmed up to brew four cyclones last year — a first in over a century. A fifth of India's population lives along the coast; Mumbai, one of its biggest cities, thrusts into the Arabian Sea rather gingerly.
- 2) Four most prominent Indian cities, viz. Chennai, Kolkata, Mumbai and Surat, are at the highest risk of submerging under water due to rising sea levels by the end of the century. Furthermore, several Indian islands are also likely to become completely uninhabitable.
- 3) According to the Special Report on the Ocean and Cryosphere in a Changing Climate (SROCC), prepared by the Intergovernmental Panel on Climate Change (IPCC) and released on Wednesday, September 25, sea levels could rise by a meter by the year 2100.
- 4) Four Indian cities -- Chennai, Kolkata, Mumbai and Surat -- are among the 45 global port cities where even a 50cm-increase in sea levels will lead to major flooding. In fact, the extreme sea level events that occurred once in a century in the past will be experienced by these cities every year by 2050.
- 5) Water is the one element that defines and wrecks Mumbai. For a city that is home to an estimated 20 million people, Mumbai stands on shifty ground. Carved out of the Arabian Sea almost 200 years ago, the city was born when seven neighbouring islands were merged through engineering exercises into a single landmass. The prospect of the sea denting the land reclaimed from it is real for Mumbaikars.
- 6) Kapil Gupta, professor, department of civil engineering at the Indian Institute of Technology, Bombay, uses an analogy for the low-lying areas of the city — a bathtub. "We've filled up the low-lying areas with earth and later raised multistore buildings on it, thereby reducing the holding capacity of those areas. When the water level rises, the bathtub will overflow," says Gupta, one of the review editors of the chapter on 'Sea level rise...' in the IPCC report.
- 7) Rising sea levels will also make a lot of islands completely uninhabitable. According to Anjal Prakash, the coordinating lead author of the IPCC report, islands like Andaman & Nicobar and the Maldives will have to be evacuated completely, as increased water levels will cause tremendous flooding and extreme climatic events like cyclones.

*C. Recent Floodings Occurred Due To Climate Change*

The results happening because of the environmental change are affecting individuals and occupants around the world. While heaps of people stay uninformed of the extent of environmental change and ocean level ascent, dangers are continually being presented. On a worldwide scale, the quantities of environment borne dangers are quickly rising. "By and large, 250 million individuals a year are influenced by environment related catastrophes."

In Asia itself almost 66 million inhabitants experienced harm or obliteration of their homes by floods in 2007. "In November 2007, Mexico's Tabasco state was overwhelmed by a flood, having all harvests demolished and influencing in excess of 2,000,000 individuals directly."13 In the United States, "Storm Katrina murdered in excess of 1,600 individuals, obliterated 200,000 Gulf Coast homes, and uprooted roughly 1 million individuals."

*D. Future Effects Caused Due To Climate Change*

As the temperature of planet tending to rise continuously, it is predicted that an average sea level increase will vary between 7 to about 36 centimeters by the year of 2050, and by 9 and 69 centimeters up to the year of 2080. Up to the year 2100, the levels are estimated to be approximately 22 inches higher than they are right now.

An increase of such devastating levels could inundate coastal areas, erode beaches and increase offshore flooding and storm surge. The effects all over the planet can be apocalyptic.

*E. Aim*

The aim is to implement cost effective methods for building better flood resilient building that can be implemented accordingly and in an amphibious manner.

#### *F. Objectives*

The research fulfils the following objectives:

- 1) The basic aim of the project is the initiative to the floating architecture in India.
- 2) Designing a habitat that could serve as a long-term solution for continuous sea level rise. Its not only about making an intervention for a separate community but defining systems to make self sufficient & independent community that could survive on its own due to flexibility, potentials, location & technology. Because in the future there will be fewer resources to fulfil the necessities of growing population.

#### *G. Research Questions*

Can aquatecture counter the Side effects faced by the commoners of the areas with rising sea level issues faced by the coastal cities of India?

#### *H. Research Hypothesis*

Study of various flood resilient and cost-effective methods for the construction of such amphibious buildings that can withstand the rising sea level issues like over flooding.

#### *I. Methodology*

After selection of project, it is important to make the method which can help me out to the right direction and lead me to the understanding and designing of the project. So, me into given below sequence;



Figure.4.5.1: Method (Author)

**J. Case Study Methodology**

- 1) To initiate analysis each case study will be assessed in 2D & 3D, followed by the creation of an exploded view diagram. Hence the exploded view diagram will become crucial for the understanding, not only of the individual parts, but also of the relationship among parts and the structure as a whole.
- 2) In the later phase I will compare the data collected, synthesize it in the form of a matrix (Appendix). Utilizing the framework, I will actually want to characterize which Architectural components become more adaptable in structures intended for flood-inclined zones. The investigation of the various blends among adaptable and static building components will signalize elective structures for human inhabitation of the floodplain. This assessment shows that specific mixes straightforwardly identify with ideas of flood strength, going past the formation of constructions genuinely ready to withstand flooding.

**K. Scope of Work**

- 1) The venture will help in building adaptable and versatile local area that will both react to the rising ocean level and water propelled natural surroundings.
- 2) The undertaking will be a mix of biomimicry, Architecture, and flood inclined local area.
- 3) Data assortment on the standards of gliding/lightness, and how they help in planning coasting natural surroundings.
- 4) To use procedures of parametric design to handily control and alter structures to accomplish ease and adaptability in the structure masses.
- 5) Providing the subtleties of elective energy creation and water filtration zones.



Figure.4.6.1:Image of Gateway of India during a flood in Mumbai (Author)

**L. Limitations**

- 1) High-cost orientation for the inhibitors results into limiting the project orientation towards this society specifically which can afford it.
- 2) Materials to be used for construction of such building types is one of the biggest selection problems that an individual designer faces while assessment of such building designing.

Implementation of such building design is limited to an individual number of user accessibility which tend to be another limitation of this study.

**II. LITERATURE REVIEWS**

**A. Coastal Regulation Guidelines Revised Edition 2019 Source**

The Ministry of Environment, Government of India.

- 1) According to the CRZ S.O. 114(E) presently, consequently, in exercise of the force gave by Clause (d) of sub-rule (3) of Rule 5 of the Environment (Protection) Rules, 1986, and any remaining forces vesting for its sake, the Central Government thusly announces the waterfront stretches of oceans, narrows, estuaries, springs, streams and backwaters which are affected by flowing activity (in the landward side) up to 500 meters from the High Tide Line (HTL) and the land between the Low Tide Line (LTL) and the HTL as Coastal Regulation Zone; and forces with impact from the date of this Notification, the accompanying limitations on the setting up and development of ventures, tasks or cycles, and so on, in the said Coastal Regulation Zone (CRZ).

- a) The distance from the High Tide Line will apply to the two sides on account of streams, springs and back waters and might be adjusted dependent upon the situation for motivations to be recorded while setting up the Coastal Zone Management Plans. Nonetheless, this distance will not be not exactly
- b) [100] meters or the width of the spring, stream or backwater whichever is less. The distance up to which advancement along streams, brooks and backwaters is to be directed will be administered by the distance up to which the flowing impact of ocean is knowledgeable about waterways, springs or back-waters, by and large, and ought to be obviously distinguished in the Coastal Zone Management Plans.]
- 2) *Disallowed Activities:* The accompanying exercises are announced as denied inside the Coastal Regulation Zone in particular:
  - a) Setting up of new businesses and extension of existing ventures, with the exception of those straightforwardly identified with water front or straightforwardly requiring foreshore offices;
  - b) Assembling or taking care of or capacity or removal of dangerous substances as determined in the Notifications of the Government of India in the Ministry of Environment and Forests No. S.O. 594(E) dated 28th July 1989, S.O. 966(E) dated 27th November, 1989 and GSR 1037(E) dated fifth December, 1989;
  - c) Setting up and extension of fish preparing units including warehousing (barring incubator and common fish drying in allowed zones);
  - d) Setting up and extension of units/system for removal of waste and effluents, aside from offices needed for releasing treated effluents into the water course with endorsement under the Water (Prevention and Control of Pollution) Act, 1974; and aside from storm water channels;
  - e) Release of untreated squanders and effluents from ventures, urban communities or towns and other human settlements. Plans will be executed by the concerned experts for eliminating the current practices, assuming any, inside a sensible time span not surpassing a long time from the date of this warning;
  - f) Unloading of city or town squander for the motivations behind land filling or something else; the current practice, assuming any, will be eliminated inside a sensible time not surpassing a long time from the date of this Notification;
  - g) Unloading of debris or any losses from nuclear energy plants;
  - h) Land recovery, financing or upsetting the regular course of ocean water with comparative deterrents, aside from those needed for control of seaside disintegration and support or getting free from streams, channels and ports and for avoidance of shoals and furthermore aside from flowing controllers, storm water depletes and structures for anticipation of saltiness entrance and for sweet water re-energize;
  - i) Mining of sand, rocks and other bases materials, aside from those uncommon minerals not accessible external the CRZ territories;
  - j) Reaping or drawls of ground water and development of components in this way inside 200 m of HTL; in the 200 m to 500 m zone, it will be allowed just when done physically through common wells for drinking, cultivation, agribusiness and fisheries;
  - k) Development exercises in biologically touchy regions as indicated in Annexure-I of this Notification;
  - l) Any development movement between the LTL and HTL aside from offices for conveying treated effluents and waste water releases into the ocean, offices for conveying ocean water for cooling purposes, oil, gas and comparative pipelines and offices fundamental for exercises allowed under this Notification; and dressing or adjusting of sand rises, slopes characteristic highlights including scene charges for beautification, sporting and other such reason, besides as allowable under the Notification.

#### B. *Amphibious Housing In Netherlands (Trabitzsch, 2006)*

The book is also known by the name of Architecture and urbanization on water. A book originally by Anne Loes Nillesen and Jeroen Singelenberg that basically terms to explain the trends and experimental analysis in the architecture and its close proximity to the substantial water bodies. It technically is impossible to imagine our existence, spatial orientation and planning without any close proximity to any water source, and this book in overall reveals the existence of the amphibious housing and its progression in respect to the current worldly scenario.

#### C. *About The Book*

Existence of the human kind alongside the river banks and above the existing water bodies has termed out to be the biggest attraction from the beginning of the times. Here comes the country of Netherlands with their polders, dikes and waterways, boasting a unique tradition of water comprehend-ability in these terms.

Climatic changes and urban expansion for this densely populated delta are great, which is a foremost a driving force for the experimentation with such innovative ideas of variable forms of housings and organizational principles.

*D. About The Authors*

Anne loes Nillesen Graduated from the Delft University of Technology with a degree in Architecture and Urban Development. In 2005, she founded D.EFAC. To Architecture and urban planning. Assignments vary from floating and amphibious homes and pavilion to master plan for a residential district on the water.

**III. LITERATURE STUDIES**

*A. Individual Housing Unit Floating Homes, Berlin, Germany, 2002-2005 (Trabitzsch, 2006)*

Summary

- 1) The oceanic structure project by the Hamburg architect pairs Förster + Trabitzsch, "Gliding Homes," insists living on the water to be a reasonable choice. Its material range of glass, steel, and wood, make a tone of straightforwardness and reflectivity to associate the living space with the encompassing water.
- 2) A rich lodging unit isolated into 4 essential sorts to be specific:
  - a) *Type A*: 60 m<sup>2</sup> of living space, including a consolidated parlor and kitchen, a room and present-day washroom as standard.
  - b) *Type B*: The Floating Homes B-Type brags around 130 m<sup>2</sup> space, offering two stories of room with unending inside choices.
  - c) *Type C*: The C-Type flaunts a dynamite outside and an extensive, light-overwhelmed inside – with a discretionary two stories. The usable space can be adaptability acclimated to set out various open doors for remarkable get-togethers.
  - d) *Type D*: The Floating Homes D-Type offers 117 m<sup>2</sup> of space to allow you to build up your very own home. Your feeling of opportunity on the water would now be able to be brought into your new living space: The inside dividers can be deftly situated, permitting you to customize your living space essentially



Figure III.1.2: Tree house school section

- 3) *Critique*: The home is floating on hollow concrete pontoon system. Although this strategy is good to prevent water damage, the home is susceptible to rocking and drifting, producing possible lack of comfort and vulnerability.

*4) Water Houses, Ijburg*

Ijburg, Amsterdam (Hund, 2018)

- a) *Project*: Water Houses.
- b) *Area*: Approx. 275 sq. Mt.
- c) *Architect*: Marlies Rohmer & Floris Hund.
- d) *Location*: Ijburg.



Figure 6.2.1: Side view of the housing



- 5) *Summary:* Waterbuurt-West is located in Amsterdam’s new-built district Ijburg built on artificial islands in the Ijmeer. Residents of the Waterbuurt with a boat or their floating terrace, and there are many, can sail to both the historic canals and open water in a short time
- 6) *Critique*
  - a) *Pro:* Usage of an unprecedented area that might have been left abundant without any usage.
  - b) *Con:* The community’s isolated location suggest exclusiveness and luxury living. The adaptive re-use strategy relates to the mitigation of rising sea levels, however, its location makes it hard for transitions to occur for Typical front view of the complete housing group surrounding communities.

*B. Community on The Water by Architect- MVRDV, Silodam, Amsterdam (MVRDV, 2018)*

*1) About Project*

- a) *Project:* Silodam
- b) *Architect:* MVRDV
- c) *Area:* 19,500 sq. meters ( 165 Dwelling ).
- d) *Location:* Amsterdam, Netherlands.




Figure 6.3.1: Typical Floor Plans of the Buildings.

- 2) *Summary:* Silodam is outfitted with 157 lofts, specialty units, Silodam by MVRDV Silodam by MVRDV and public spaces. The condos are various sizes and are stacked to make inside associated neighborhoods. Occupants can stroll through the structure, passing various veneers and rooftop tops, under the structure through the corridor to the porch, or along the marina where boats can be moored

- 3) *Critique:* Pro: The joining of blended utilized industry takes into consideration the advancement of a local area. The Silodam isn't just a spot to live, yet it gives, occupations, and public spaces. Additionally, the area of Silodam is gainful to elevate advances from land to amphibian living in case of a rising ocean/waterway level emergency.

Comparative Analysis/ Inferences

PARAMETER S	INDIVIDUAL HOUSING UNIT Floating Homes, Berlin, Germany	WATER HOUSES, Ijburg	COMMUNITY ON THE WATER, Silodam
AREAS COVERED (IN SQ. MTS.)	60 and 130	275	19,500.
HOUSING TPOLOGY	Individual housing units dwelled over water body in cluster format.	Same as the individual housing units from Berlin, Germany.	Vertical housing unit comprising of
Limit number of students per class	Classrooms for 20-25 students (55sqmt)	-	Classrooms for 20-25 students.
Ventilation	Proper ventilation	Proper ventilation	Proper ventilation

Table III.4.1: Literature study comparative analysis/ inferences

- The first and the foremost inference generated after the study of Costal Regulation Guidelines (CRZ) is that the construction of any building is completely prohibited anywhere by , the Central Government hereby declares the coastal stretches of seas, bays, estuaries, creeks, rivers and backwaters which are influenced by tidal action (in the landward side) up to 500 meters from the High Tide Line (HTL) and the land between the Low Tide Line (LTL) and the HTL as Coastal Regulation Zone.
- Proper disposal system for the waste generated by the usage of buildings should be treated and disposed properly without mixing them into the sea or adjacent water body .
- Construction of storage or manufacturing units anywhere near 100 mts. of the sea shore or river edges is prohibited by the CR guidelines.
- For any construction related to the defense organizations requirements the permissions are allotted by the Ministry of Forest and Environment, Govt. of India.
- The basic four zones developed by the Costal Regulation Guidelines are general classification of the areas which can be accessed completely or partially by the government according to their specific characteristics matching to the respective Costal Regulation Zones. For ex. : Category 1 handles the areas with some specific characteristics which make that particular zone more important and that it needs to be conserved.
- Costal cities like Mumbai, Kolkata, Surat, etc. come under the Category 2 of the Costal Regulation Zones and are either controlled by the Municipal Corporation of that locality or any governing Urban development Authority.
- Areas like Andaman and Nicobar Island, Lakshadweep Islands are most remote and least disturbed islands across the country and are categorized under the Category 4 of the CRZ.
- The prohibited and restricted construction across the costal stretch are generally assessed and governed by the Government of India, Ministry of Forest and Environment India.
- Countries like Netherlands, Germany, Canada, America all are understanding the side effects of the climate change and are taking a special interest in implementation of various new construction strategies such a high pile foundation, amphibious building style, etc. to withstand with the rising sea level issues.
- For example Water houses from Ijburg tend to be an effective example for the problem of the rising sea level the costal cities of Indian subcontinents.

Intervention of flood resilient tactics for costal cities like Mumbai and Kolkata can be permissible and can be approved by either the Governing Municipal corporations or the development Authorities of the respective cities in our country too.

#### IV. CASE STUDIES

##### A. Buoyant Foundation Project (Project)

- 1) *Water Type:* Salt Water
- 2) *Type:* Amphibious
- 3) *Lightness Material:* Sub-outline EPS Blocks
- 4) *Size:* 700 sq. ft
- 5) *Points of Interest:* Retain existing, it is less expensive than static height
- 6) *Drawback:* Visible EPS establishment framework

The Buoyant Foundation Project (BEP) is a non-productive examination program coordinated by Dr. Elizabeth in 2006. It was the initial step to apply land and/or capable establishment to the current home in to forestall flooding. The common style of in south of is called as shotgun comprise of a thin rectangular edge.

To test the light test has been fitted with land and/or capable sub edge. It is connected to the underside of backing the gliding blocks made of Expanded Polystyrene Foam (EPS). The stub outline is connected to the vertical direction post found toward the edge of project outside from the ground to oppose the horizontal power by wind and streaming. At the point when flood happens the gliding squares will lift the square.

The vertical shafts will ensure go to other spot due to rising. The development and the fitting interaction of straightforward and essentially works like a gliding dock.

The interaction starts with penetrating a shaft into the ground and embedding the vertical shafts. A steel outline is built by utilizing the c channel is then moved 4 to 5 feet to alter the pipes and utility lines. The pipes what's more, utility is made in two strategies (1) Self-fixing „break away“ association that distinction gas and sewer line when begins to ascend because of rising (2) since a long time ago, curled lines that can extend alongside the .EPS blocks are associated with the sub edge and afterward the edge is associated to then brought down where it lays on 3 to 4 feet from ground. A large portion of the materials are lightweight materials. So it tends to be introduced by two people itself without any apparatuses.

In 2007 a group of Louisiana State undergrads and staff effectively developed and test a light establishment project. The completed venture has effectively exhibited the capacity of a current to rise and fall with the flood and guarantee the security of occupants during flood. The light base permit to secure their vernacular homes and keep up their local character. This methodology is thought of more affordable than the static rise.

##### B. The Float House. (Fenuta, 2015)

- 1) *Water Type:* Salty Water
- 2) *Building Type:* Amphibious
- 3) *Light Material:* GFRC covered EPS blocks
- 4) *Size:* 970 sq. ft.
- 5) *Bit of Leeway:* Maintains Neighbourhood character.
- 6) *Weakness:* Residents can't stay in during flood.

a) *Summary:* The Float house was created to address the issues and financial plan of families in New Orleans. The glide is a pre-assembled, reasonable lodging that can be embraced in flooding zone. UCLA students and workforce and Architects from Mayne's and Morphosis firm made this first floating house in United States. The float house keep up the vernacular style of shotgun in New Orleans. This sits on the pre-assembled base comprised of extended polystyrene froth covered with glass fiber fortified cement. It has an entryway patio which looks like the way of life of the city and furthermore gives availability to older and impaired individuals. The 4 feet base incorporates all the electrical, plumbing lines and permits the drift during the flood condition. The base was pre-assembled and afterward positioned in the site. The buoy is associated with the vertical post that are associated with solid heap each determined 45 feet into ground. The vertical and solid cushions on which the base sits are developed nearby and permit to rise 12 feet as level ascents. The dividers, window, entryways are pre-assembled and afterward collected in site.

C. *The Floating Homes (Massbommel, 2007)*

Netherland, Massbommel

- 1) *Water Type:* Fresh Water
- 2) *Building Type:* Amphibious
- 3) *Light Material:* PVC blocks, wood and pre-cast concrete blocks with metals.
- 4) *Size:* 1000 sq. ft.
- 5) *Bit of Leeway:* Maintains Neighbourhood character.
- 6) *Weakness:* High construction costs at the stakes.

Netherland is situated on the delta and experience flooding from waterways and from storms. Most people group in Netherland are ensured with dykes, levees and flood entryways. However, some rustic towns are situated outside of these flood insurance structures. One of those rustic town is Massbommel situated along Meuse River. In 2005 Dutch government conceded authorization for development of "versatile structure procedures" in 15 destinations along the, which brought about "Amphibious Strucures". The authorization was given to the Architects also, Engineers from Factor Architecten and the worker for hire and undertaking designer Dura Vermeer to build 34 Amphibious Houses and 14 Floating houses.

PARAMETERS	BOUYANT FOUNDATION PROJECT	THE FLOAT HOUSE	THE FLOATING HOMES
Location	Vietnam, Mekong River Delta	New Orleans, USA	Netherland, Massbommel
Area (In sq. ft.)	700	970	1000
Building Type	Amphibious	Amphibious	Amphibious
Materials used for Building construction.	Light weight materials for the construction of super structure and for the foundation part EPS (Expanded polystyrene Foam) comprised structure at the foundation level	Light weight prefabricated built structure basically out of light weight metal and fibre particle mix boards along with energy efficient panels.	Prefabricated concrete blocks made out of concrete along with metal mesh and wood reinforcement at base which tends to be airtight and for super structure the use of metal along with wood again for better elevation options. Steel poles for the anchorage are assembled at the edges of the built structure.
Efficiency facilities available for the conditions of Flooding.	Water borne debris barrier, along with solar panels and emergency generators are available in the built prototype structure. The built structures are sometimes preinstalled with water electricity generation options too in conditions of client's demands	The architects of the building were expecting high LEED scores since the building was designed in such a manner that the energy consumption of building was brought to zero annual cost.	The built structure are provided with emergency electricity supply space where the electricity is generated and stored using the solar electricity generation plants and other than that a special compartment in the houses are provided which generally tend to store amenities for such flooding conditions.
Foundation Type	Pile Foundation up to a depth of 3 to 4 ft. from ground level is introduced for the mooring with the help of which the building is maintained to stop at one single position.	Conc. Post sitting at the mooring poles which tend to stay around 12 ft high above the ground and piled to around 20 ft. under the ground lvl.	Pre-constructed concrete hulls were brought along to the site and assembled with the light weight houses which are placed at 6 pile foundation placed at a conc. Block where the piles go up to a depth of 30 to 40 ft. from the ground level
Availability of circulation decks.	No such circulation decks are provided since the units tend to be available at relatively low costing too.	A 3 ft. wide circulation deck is provided around the built periphery of the house.	Available since the houses tend to exist in cluster form where the cluster comprises of minimum of 2 houses

Table IV.5.1: Case study comparative analysis/ inferences

## V. DESIGN RECOMMENDATIONS

There are sure standards to be followed to plan an amphibious house to be bearable, utilitarian and charming. These house should be an important substitution for typical home. The home should be versatile and adaptable. This home ought to supplant the current home and just as it ought to likewise ready to drift with the environmental change. To make the float during flood condition and make it retreats cautiously after the flood is a difficult cycle for the modellers to plan. To satisfy this part as a working and alluring amphibious home certain models has been recognized: Capability to glide, coast line, light establishment stature computation, Structure type and utility access.

### A. Capability of Floating

The most basic plan direction factor which choose whether the home will in reality will actually want to skim during flooding conditions. As found in the past models with the backings of the securing shafts and the straightforward computation of the light establishment the can make to coast during flood. In the event that the complete load of the whole home including the dead and live load of the house ought to be not exactly the volume of the water then the house can drift.

### B. Foundation

Foundation is the significant piece of the design to help the light weight structure and to float during flooding condition. Profound establishment are the primary part that move loads into more profound layer of earth material than a shallow establishment. Profound establishment incorporates pile foundation with driven pile, penetrated shafts, and miniature piles and grouted set up piles. Construction configuration engineers are liable for figuring the heap configuration load and for giving other underlying subtlety. With the site seismicity and the considered burden the underlying designer ought to figure and determine the establishment strategy also, material for the proposed site condition.

### C. Float Line

The float line is the line that indicates when the structure will start to float. As indicated by light guideline, if an item uproots a volume of which loads a more prominent than the item then it will drift. In like manner if an article uproot a volume of that weighs not exactly the item then the design won't coast. The structure will have a static square or rectangular establishment the volume of can be changed exclusively by the tallness of the structure. This implies that if the level ascents the volumes additionally extends, so if the level ascents the design with less weight than the will drift.

### D. Structure Type

To make the construction float the chose material ought to be of light weight material. The establishment is comprised of a solid frame or of some other material and the design over the establishment which will float ought to be comprised of light weight material. These material ought to likewise be verification material and ought to advance protection and other inactive warming and cooling strategy to be feasible design.

## VI. MATERIAL ANALYSIS

Materials of the structure play the important role in the amphibious dwellings. Since the structure is near the water and salt water will cause the materials to corrode. Designer should take a special concentration on the selection of the material. By the above mentioned case studies few materials are discussed in this following chapter. Some of the materials are EPS blocks, pontoons, barges, GFRC coating, Concrete, Ferro cement, and Bamboo.

### A. EPS BLOCKS (<http://espa.org.au/about-eps-in-building/block/>)

Extended Polystyrene (EPS) or Extruded Polystyrene (XPS) is a Geofoam that is fabricated into an enormous lightweight squares. The squares changes in size however are generally in 2m x 0.75m x 0.75m. These geofoam is a light weight void fill. It is utilized in numerous applications for example, light weight fill, green rooftop fill, compressible considerations, and warm protection and in some cases it is utilized in waste too. It chips away at the standards with geocombs which has been characterized as "any made material peaked by an expulsion cycle that outcomes in an end result that comprises of various open finished cylinders that are stuck, reinforced, melded or on the other hand packaged together."

### B. PONTOONS (Hall, 2005)

Pontoons are framed in Orsta Marina Systems in 2003 in Netherland is an approved producer of barges. It is a main producer and installer of pontoon prepared and floating embankments for recreation and business applications with more than 3000 finished activities. Boats is an air filled design accommodating lightness. Polystyrene is generally utilized as the centre material in drifting docks and barges. It is financially savvy has great floatation properties and is east to cut into custom barge profiles.

### C. Barges

A flat bottom boat that is built on the rivers and canals for the movement of heavy goods is called a barge. Some Barge boats cannot be used by its own so they need to be towed or pushed by the towboats. On the British canal system the term barges is used for describing a boat wider than a narrow boat and people who move barges are also known as lighter men.

### D. Ferro Cement

Ferro cement is the technique for applying a combination of concrete, sand and water in layers on wire cross section and steel fortification. It is light in weight than the solid and furthermore it is waterproof because of its concrete substance and application strategies. It is an arrangement of fortified mortar or mortar applied over layer of metal cross section, woven extended metal or metal filaments and firmly dispersed slim steel bars, for example, rebar. Metals ordinarily utilized is iron or some sort of steel. It is utilized to develop moderately slender, hard, solid surfaces and designs in numerous shapes like bodies for boats, shell rooftops and water tanks. It is begun in France at 1840.

## VII. CONCLUSION

By seeing how to oversee water and plan in its nearness, the tremendous size of the test of flooding that we are confronting turns out to be clear. Environment change and it is numerous impacts including expanding level, more extreme precipitation and increment in flood hazard is as of now being felt in numerous spots of India and it is a genuine impact that will be estimated in many years. This is the time period inside which arranging, plan and improvement ought to be created. The structure and places that we make in the following ten a long time will frame the foundation of a land amphibious way of life for next couple of many years and past. To get ready for the future, fashioners and manufacturers should not glance at the constraint of water yet at the chances it presents. In this dissertation the impact of environmental change also, the significance of the water abodes to reaction to environmental change is talked about and impacts are figured it out.

Amphibious structures are demonstrated low effect flood security technique that gives a local area upgraded flood flexibility and improves its capacity to recuperate from fiasco. When flooding happens the water staying vertically ascends with the water levels to remain securely above water at that point settles once more into places as the water retreats. Fruitful amphibious establishment framework are working in the Netherland, New Orleans and Bangladesh, they can give flood insurance that is more dependable and more helpful than the lasting static heights.

This paper has demonstrated the steadiness and usefulness of existing amphibious homes also, its significance in India. With the reference of the diverse contextual analyses and itemized portrayal of the structure material the development procedure of the amphibious designs. Economical and minimal effort amphibious design can be underlying India by utilizing locally accessible material, for example, bamboo and so forth as utilized in Bangladesh. These occupants can likewise resemble ordinary occupants ashore in light of the fact that generally similar conveniences as a structure ashore can be given including warming, cooling and ventilation. The waterfront improvement can be created by building up these amphibious homes. Nature of these constructions is moreover kept up same as the structure on the land. The expanded appeal of living on the following quite a while of fearing immersion demonstrates that the populace feels that rising levels are not to be dreaded however to adjust with the evolving environment.

## BIBLIOGRAPHY

- [1] Architects, M. M. (2010). <http://morphopedia.com/projects/float-house>>.
- [2] Environment, M. O. (n.d.). Coastal Regulation Guidelines.
- [3] Fenuta. (2015). E. Amphibious Architectures: The Bouyant Foundation Project in Post ktrina, New Orleans.
- [4] Hall, M. (2005). Whats a pontoon.
- [5] <http://espa.org.au/about-eps-in-building/block/>. (n.d.). Block- Expanded Polyester Australia.
- [6] <http://floodlist.com/tag/india>. (n.d.). India Floods and Flooding.
- [7] <https://www.ipcc.ch/organization/organization.shtml>. (n.d.). Intergovernmental pnel on climate change.



- [8] Hund, M. R. (2018). an overview of water community of Ijburg. Arch Daily.
- [9] Massbommel. (2007). Amphibious Housing in Netherlands.
- [10] Mishra, G. (n.d.). Application of Ferro-Cement in Construction.
- [11] MVRDV. (2018). Lanka Learning Center / feat.collective. Arch Daily.
- [12] olthuis, K. a. (n.d.). Float : Building on water ro combat urban congestion and climate change. amsterdam.
- [13] Project, B. F. (n.d.). <http://www.bouyantfoundation.org/>>.
- [14] Trabitzsch, F. (2006). Forster Trabitzsch Architects.
- [15] Wikipedia. (2018). Floods in India.



10.22214/IJRASET



45.98



IMPACT FACTOR:  
7.129



IMPACT FACTOR:  
7.429



# INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24\*7 Support on Whatsapp)