



iJRASET

International Journal For Research in
Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 9 Issue: VI Month of publication: June 2021

DOI: <https://doi.org/10.22214/ijraset.2021.35958>

www.ijraset.com

Call:  08813907089

E-mail ID: ijraset@gmail.com

Implementation of Hybrid Algorithm in Cluster Head using Neural Networks

Pooja S¹, Sahana B²

¹Department of ECE, RV college of Engineering, Bangalore-560059, India

²Professor, Department of ECE, RV college of Engineering, Bangalore-560059, India

Abstract: A Neural Network is a data processing system consisting of large number of simple, highly interconnected processing elements. In this paper a graphical convention is utilized where hubs are orchestrated in the form of cluster. An epic methodology is presented for choice of group head by the utilization of fake neural organization to expand organization's lifetime in WSN and calculation of steering convention dependent on neural organizations (NNs). In the proposed work, a standard burned-through energy is used for the choice of bunch head and and steering convention LEACH is used. The leftover energy is utilized for making group head and for the determination of bunch head using Neural Network. In the proposed system Using LEACHNN algorithm Throughput, packet delivery ratio ,energy is improved by 20%

Keywords: WSNs, LEACH, Neural Network, CH selection, Residual energy

I. INTRODUCTION

Remote Sensor Networks (WSNs) are being utilized in wide reach of potential applications. This organization comprises of SNs which are able of observing and preparing the information from a specific geographical location and sends a similar information to the far off location which is called as Base Station (BS).

WSNs comprise of little, modest, asset compelled gadgets that impart among one another utilizing a multihop remote Correspondence Every hub of WSN is called as sensor hub (SN) which comprises of a sensor, installed processor, restricted memory, low-power radio, and normally worked with battery. Every SN is liable for detecting an ideal occasion locally and for transferring a distant occasion detected by different SNs with the goal that the occasion is accounted for to the objective through BS. As Sensor hubs have restricted energy, applications and conventions for WSNs have to be painstakingly intended for optimized utilization of energy for delaying the organization life time. The summed up perspective on WSNs, which comprises of a BS, Cluster Heads (CHs) and SNs conveyed in a geological area is displayed in fig 1.




Fig.1. Generalised view of WSN

II. THE STRUCTURE OF SUB-CLUSTER IN WSN

The sub-Cluster design of WSN comprises of the organization hubs are partitioned into a few groups. Each bunch comprises of a group head hub (CH) and a few individuals from the hub (MN) part. This MN speaks with the group head CH and again CH establishes a significant level virtual spine which is liable for bunches of information combination and information sending between group [3]. Since a bigger energy utilization in the group head hub, a repeating approach to choose bunch head hubs in the organization hubs is utilized for adjusting energy utilization. The sub-bunch inside the group structure and the information stream between bunches is displayed in fig.2 [4].




Fig.2 the cluster structure of WSN

WSN was intended to boost the organization lifetime as a definitive objective, subsequently making every hub however much as could be expected is critical to adjust the energy utilization. In the grouping calculation, the energy utilization of the bunch head hub is for the most part a lot higher than ordinary, it probably makes group head hub pass on rashly in light of energy misfortune. To stay away from the present circumstance, one route is to utilize bunch head pivot component. Every hub of each cluster head pivot occasionally. The leftover energy of every hub is pretty much as close as conceivable [5].

Group head turn instruments are regularly free of the bunching calculation, and bunching calculations supplement one another. Normal component of group head pivot is two sorts latent and dynamic. The detached kind prompts a fixed time stretches that requires a limit an incentive for lingering energy, hub number, etc. Both detached and dynamic group head turn system chooses the fitting boundaries of the calculation [4]. In the event that the bunch head pivot is excessively continuous, it's anything but a ton of extra overhead and organization disturbance; if group head turn recurrence is excessively low, it might cause a few hubs run out of energy rashly. Along these lines, just a sensible trade off can accomplish the most ideal organization lifetime.

Bunching component is broadly utilized in WSNs for planning different energy proficient conventions in WSNs. Low Energy Adaptive ClusterIng Hierarchy (LEACH) convention is the most regularly utilized convention [4].

A. Routing Protocol Leach

LEACH Protocol is broadly utilized convention for the progressive engineering of WSNs by allowing to monitor the force by partitioning the organization into bunches called bunches, and each gathering choose a particular hub named as Cluster-Head (CH) liable for the correspondence with the Base Station (BS). Calculation of LEACH runs in adjusts, each round is created on two stages as displayed in Fig.3.



Fig. 3 Phases of LEACH

Drain, fundamentally a self-coordinating, versatile grouping convention, utilizes balanced energy load dissemination among the SNs in the WSN. The activity of LEACH is separated into various rounds and each round is partitioned into two stages as: arrangement and consistent state stage. Consistent state stage is in every case since a long time ago contrasted with the set-up stage to limit the overhead [6].

In this LEACH convention, the SNs arranges themselves into neighborhood bunches, with one hub as group head (CH) and rest will go about as standard hubs. To drag out the lifetime of the organization, LEACH Includes randomized revolution of the great energy CH and performs nearby information combination to send the measure of information being sent from the CHs to the BS. In the event that BS is far away from the organization, the energy of CHs will be influenced as just CHs are straightforwardly speaking with the BS. Set of groups will be distinctive for various time Interval and the choice to turn into a CH relies upon the measure of energy left at the SN. The different units in LEACH convention comprises of transmitter and collector [18].

Each round of the LEACH convention is characterized by the set-up and consistent stages. In set-up stage, CH for the current round communicates a promotion message to the remainder of the SNs. The SNs should keep their beneficiaries on and dependent on the got signal strength of the ad, every non-CH hub chooses to which group it has a place for this round. On the off chance that ties happen, an arbitrary CH Is chosen. In consistent stage, the energy of all Cluster Members (CMs) can be diminished utilizing rest mode enactment and now information transmission can start. when the CH has all the information from the CMs, the CH totals and intertwined the information to the BS. After a certaIn tIme, which is resolved deduced, the following round starts with every SN deciding whether It ought to be a CH for this round.

III. PROPOSED ALGORITHM

The proposed calculation dependent on the Neural Networks has the choice of CH relying upon the measure of residual energy. for the purpose of Improving the grouping in steering convention LEACH, particularly for the period of choosing the Cluster-Head (CH). The proposed method chooses the CH for the hub with the most significant level of the energy. In this manner the energy could be more monitored, thus the lifetime of the organization could be broadened.

The proposed model is made out of three layers. First layer is the info layer with two hubs in that one is utilized for the energy and other one for the Bias. Second layer is the secret layer with four hubs and Transfer work which is utilized here is sigmoid capacity. The last layer is the yield layer with one hub that can take as a worth "1" for the hub chose as CH or "0"




Fig:4 Flowchart of the proposed technique

IV. SIMULATION AND RESULTS

This simulation is done in the network simulator-2, the tool provides an efficient way to compare the performance parameters of DSR, Neural network and LEACH. The fig 5 shows random cluster head selection using proposed algorithm.




Fig:5 cluste rhead selection using proposed algorithm

A. Packet delivery ratio

Packet delivery ratio is a vital factor to quantify the exhibition of directing convention in any organization. The Packet conveyance proportion is the proportion of number of parcels got at the objective to the quantity of bundles sent from the source. The exhibition is supposed to be better when the bundle conveyance proportion is high. Numerically it tends to be displayed in condition (1) From fig 6 PDR is less in filter than the Proposed framework.

$$PDR = \frac{\sum_{i=1}^M CBR - Received}{\sum_{i=1}^M CBR - sent} \quad (1)$$




Fig:6 Packet delivery Ratio: Existing system: 260, Proposed system: 175

B. Throughput

It is the quantity of parcels/bytes got by source per unit time. It's anything but an Important measurement for dissecting network conventions. Throughput is number of effectively got parcels in a unit Interval of time. By and large Throughput is addressed in bps (bits each seconds). Throughput is less In filter than the looked at framework (Proposed framework).



Fig:7 Throughput of Existing system: 19.00obps, Proposed system: 41.00obps

C. Residual Energy

The residual energy calculated using the equation (2)

$$E_n = E_{\text{initial}} - E_{\text{consumed}} \quad (2)$$

The comparison between the residual energy of the existing system and proposed system is shown in fig.8. Energy graph of existing system 7.5000 and Proposed system 9.6000



Fig : 8 Energy graph of existing system 7.5000 and Proposed system 9.6000

Improvement: Dynamically chose CH .Energy is significant boundary in the determination of CH System is planned with versatile sink which assists with forestalling save a lot of energy and more productive conveyance of bundles to sink.

V. CONCLUSION

This paper portrays a system of collection in directing show LEACH using the computation of Neural Networks. The results shows that by apportioning the power of the energy, the lifetime of the association sensors was extended. The proposed calculation is examined on different variables including number of hubs dead to number of rounds, energy utilization of the conventions, bunch head development, number of hubs kicking the bucket as for number of rounds and the absolute number of bundles shipped off the base station and the group head. It has been seen that Enhanced LEACH with ANN convention gives better outcomes in contrast with LEACH conventions, for example the utilization of counterfeit neural organization are improving the lifetime of the organization somewhat.

REFERENCES

- [1] Kaur Jaspreet and Rai Dr. M.K, "Dynamic Clustering in Wireless Sensor Network," vol. I, Mar. 2013.
- [2] Abu Alsheikh Mohammad, Lin2 Shaowei, Niyato Dusit, and Tan Hwee-Pink, "Machine Learning in Wireless Sensor Networks: Algorithms, Strategies, and Applications," , 19 Mar 2015.
- [3] Eldhose Elby K and G Jisha, "Active Cluster Node Aggregation Scheme in Wireless Sensor Network Using Neural Network," no. 1603-1608, 2016.
- [4] Fei Zesong et al., "A Survey of Multi-Objective Optimization in Wireless Sensor Networks: Metrics, Algorithms and Open Problems," 13 September 2016.
- [5] Jaladi Aarti Rao, Khithani Karishma, Pawar Pankaja, Malvi Kiran, and Sahoo Gauri, "Environmental Monitoring Using Wireless Sensor Networks(WSN) based on IOT.," vol. I, Jan2017.
- [6] Devi Rita, Kumar Amit, and Dhawan Vinay, "A Node Prioritization Based Load Balancing Approach To Improve Cluster Head Selection In Wireless Sensor Network," vol. III, no. 8 – 12, February 2017.
- [7] Xiaopeng WANG, "Improved Routing Protocol of Wireless Sensor Network Based on Wavelet Neural Network," , 2016.
- [8] Husain Rashid and Vohra Dr. Rajan, "A Survey on Machine Learning in Wireless Sensor Networks," vol. III, Jan 2017.
- [9] Karunanayake Piumika, Könsgen Andreas, and Förster Anna, "Poster Abstract: Adaptive Protocol Parameters for Wireless Sensor Networks using Machine Learning," , July 2017.
- [10] Ahmad, Khan Zaki and Samad Abdus, "A Study of Machine Learning in Wireless Sensor Network," vol. IV, July-August 2017.
- [11] Sharma Vartika, Raj Sharma Kritika, and Sharma Susheva, "Simulated Annealing Based Neural Network for Dynamic Clustering In Wireless Sensor Network," vol. III, 2014.
- [12] LeCun Yann, Bengio Yoshua, and Hinton Geoffrey, "Deep learning," vol. 521, 2015.
- [13] Jangra Ajay, Swati, Richa, and Priyanka, "Wireless Sensor Network (WSN): Architectural Design issues and Challenges," vol. III, no. 9, 2010.
- [14] Al-Karaki Jamal N. and Kamal Ahmed E., "Routing Techniques in Wireless Sensor Networks: A Survey," , 2004.
- [15] Rajkumar, B A Vani, Jadhav Kiran, and Vidya S, "Wireless Sensor Networks Issues and Applications," vol. III, no. 1667- 1673, Sept-Oct 2012.
- [16] Cordina Mario and James, Debono Carl, "Applying an SOM Neural Network to Increase the Lifetime of Battery-Operated Wireless Sensor Networks," no. 25, 2010.
- [17] Singh Inderjeet, Pooja, and Varsha, "Neural Network based LEACH Clustering Algorithm in WSN," vol. VI, February 2017.
- [18] Farah Sanhaji et al., "Clustering Based on Neural Networks in Wireless Sensors Networks," in International Conference on Computing and Wireless Communication Systems (ICWCS), Larachi, 2017.



10.22214/IJRASET



45.98



IMPACT FACTOR:
7.129



IMPACT FACTOR:
7.429



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24*7 Support on Whatsapp)