



# **iJRASET**

International Journal For Research in  
Applied Science and Engineering Technology



---

# **INTERNATIONAL JOURNAL FOR RESEARCH**

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

---

**Volume: 5      Issue: IV      Month of publication: April 2017**

**DOI: <http://doi.org/10.22214/ijraset.2017.4075>**

**[www.ijraset.com](http://www.ijraset.com)**

**Call:  08813907089**

**E-mail ID: [ijraset@gmail.com](mailto:ijraset@gmail.com)**

# Numerical Analysis of Three-Dimensional Squeezing Nanofluid Flow in a Rotating Channel on a Lower Stretching Porous Wall

Dr. Anuradha. S<sup>1</sup>, Harianand. N<sup>2</sup>

<sup>1</sup>Professor and Head, <sup>2</sup>Research scholar, Department of Mathematics, Hindusthan College of arts and science

**Abstract:** Unsteady 3D rotating Nano fluid flow of an Incompressible electronically conducting viscous fluid between two infinite horizontal plane walls investigated Numerically, The governing Navier stokes equations are converted into ordinary differential equations by using similarity transformation. Runge kutta method sixth order by using mathematical software is used to solve the complete system of nonlinear ODE. The non dimensional parameters characteristic parameter of the flow, rotation parameter, the magnetic parameter, nano particle volume fraction, the suction parameter analyzed numerically and graphically with comparison of analytical result.

## I. INTRODUCTION

Nano fluid is a liquid covering nanometer-sized elements (having diameter less than 100nm), named nanoparticles. The nanoparticles are classically made up of metals, oxides and carbides or carbon nanotubes. Owing to the vast number of submissions in chemical as well as motorized engineering procedures such as the production of thin plastic sheets, insulating materials, paper fabrication, and other various procedures, this paper pays specific care to the study of rotating flow over stretching surfaces [1]. Bachok et al. [2] employed a numerical, Keller-Box technique for steady Nano fluid flow over a porous rotating disk. Khairy Zaimi et al. [3] inspected the Flow and Heat Transfer over a Shrinking Sheet in a Nano fluid with Suction at the Boundary. Prasad et al. [4] working a fourth order Runge-Kutta integration system to explore the consequence of variable fluid viscosity, magnetic parameter, Prandtl number, variable thermal conductivity, thermal radiation parameter and heat source/sink parameter, on MHD fluid flow over a stretching sheet. Three-dimensional flow in a channel with a stretching wall was investigated by Borkakoti and Bharali [5]. Domairry and Aziz [6] found an analytic solution for unsteady MHD squeezing flow with suction and injection properties by the use of homotopy perturbation technique. El-Mistikawy and Attia [7] was investigated the influence of an external uniform magnetic field on the flow due to a rotating disk. Syahira Mansur and AnuarIshak [8] studying the heat transfer characteristic of an unsteady boundary layer flow of a nanofluid over a stretching sheet. Mehmood and Ali [9] analyzed a three-dimensional flow in a channel bounded through the lower stretching plate and upper permeable plate and experimental that the viscous drag at lower wall rises due to the incidence of injection at the higher plate. To the best of authors' knowledge, Choi and Eastman [10] stood probably the first investigators who employed a mixture of nanoparticles and base fluid and called this mixture a "Nano fluid." A varied choice of evaluation documents have been issued on Nano fluids in recent years. NavidFreidoonimehr [11] derives a coupled system of nonlinear ordinary differential equations to model the three- dimensional flow rotating channel of a nanofluid on a lower permeable stretching wall. The three-dimensional problem of steady fluid deposition on an inclined rotating disk is studied by Sheikholeslami et al. [12] and M. Sheikholeslami [13] at al study is to apply HPM to find approximate solutions of nonlinear differential equations governing the problem of heat transfer in the unsteady squeezing Nano fluid flow between parallel plates.




Figure 1: Schematic diagram of the flow configuration and the coordinate system for the considered flow

## International Journal for Research in Applied Science & Engineering Technology (IJRASET)

### II. MATHEMATICAL FORMULATION OF THE PROBLEM

Consider unsteady 3D rotating Nano fluid flow of an incompressible electrically conducting viscous fluid between two infinite horizontal plane walls. The lower plane is placed at  $y=0$  and is stretched with a time-dependent velocity  $U_o(t) = ax/(1-\gamma t)$  in  $x$ -direction. The upper plane is also placed at a variable distance  $h(t) = \sqrt{v_f(1-\gamma t)/a}$  and the fluid is squeezed with a time-dependent velocity  $v_h = dh/dt$  in the negative  $y$ -direction. The fluid and the channel are rotating around  $y$ -axis with an angular velocity  $\Omega = \omega\hat{j}/(1-\gamma t)$  and also the lower plate intakes the flow with the velocity  $-V_0/(1-\gamma t)$ . A magnetic field with density  $B_0/\sqrt{(1-\gamma t)}$  is applied along the  $y$ -axis about the system which is rotating. These velocities and magnetic fields are introduced to obtain similarity solutions by reducing governing equations into ordinary differential equations (ODEs).

The physical model of the considered problem along with the coordinate system is illustrated in Figure 1. The governing equations of continuity and momentum of Nano fluid flow in a rotating frame.

$$\nabla \cdot \mathbf{V} = 0, \tag{1}$$

$$\rho_{nf} \left[ \frac{\partial \mathbf{V}}{\partial t} + (\mathbf{V} \cdot \nabla) \mathbf{V} + 2\Omega \times \mathbf{V} \right] = \nabla \cdot \mathbf{T} + \mathbf{J} \times \mathbf{B},$$

Where  $\mathbf{T}$  is the Cauchy stress tensor,  $\mathbf{J}$  the magnetic flux, and  $\mathbf{B}$  the current density. The above governing equations can be also described by the following set of Navier-Stokes equations [14, 15]:

$$\begin{aligned} \frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} &= 0 \\ \frac{\partial u}{\partial t} + u \frac{\partial u}{\partial x} + v \frac{\partial u}{\partial y} + 2 \frac{\omega}{1-\gamma t} \omega &= - \frac{1}{\rho_{nf}} \frac{\partial p}{\partial x} + v_{nf} \left[ \frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} \right] - \frac{\sigma B_0^2}{\rho_{nf} (1-\gamma t)} u + g\beta (T - T_\infty) + g\beta^* (C - C_\infty) \\ \frac{\partial v}{\partial t} + u \frac{\partial v}{\partial x} + v \frac{\partial v}{\partial y} &= - \frac{1}{\rho_{nf}} \frac{\partial p}{\partial y} + v_{nf} \left[ \frac{\partial^2 v}{\partial x^2} + \frac{\partial^2 v}{\partial y^2} \right] \\ \frac{\partial \omega}{\partial t} + u \frac{\partial \omega}{\partial x} + v \frac{\partial \omega}{\partial y} - 2 \frac{\omega}{1-\gamma t} \omega &= v_{nf} \left[ \frac{\partial^2 \omega}{\partial x^2} + \frac{\partial^2 \omega}{\partial y^2} \right] - \frac{\sigma B_0^2}{\rho_{nf} (1-\gamma t)} \omega, \end{aligned} \tag{2}$$

Where  $\rho_{nf}$  is the Nano fluid density,  $v_{nf} (= \mu_{nf} / \rho_{nf})$  is the Nano fluid kinematic viscosity, where  $\mu_{nf}$  has been proposed by Brinkman,  $\sigma$  is the electrical conductivity,  $B_0$  is the magnetic field, and  $\gamma$  is the characteristic parameter with dimension of  $(time)^{-1}$  and  $\gamma t < 1$ . The above Nano fluid constants are defined as follows:

$$\mu_{nf} = \frac{\mu_f}{(1-\phi)^{2.5}}, \rho_{nf} = (1-\phi)\rho_f + \phi\rho_s \tag{3}$$

Where  $\mu_f$  is the viscosity of the fluid fraction,  $\phi$  is the nanoparticle volume fraction, and  $\rho_f$  and  $\rho_s$  are the densities of the fluid and of the solid fractions, respectively. The thermo physical properties of the base fluid (water) and different nano particles. The appropriate boundary conditions are introduced as follows:

$$\left. \begin{aligned} u(x, y, t) &= U_0 = \frac{ax}{1-\gamma t} \\ v(x, y, t) &= - \frac{V_0}{1-\gamma t}, \\ w(x, y, t) &= 0 \end{aligned} \right\} \text{ at } y = 0$$

## International Journal for Research in Applied Science & Engineering Technology (IJRASET)

$$\left. \begin{aligned} u(x, y, t) &= 0 \\ v(x, y, t) &= V_h = \frac{dh}{dt} = \frac{-\gamma}{2} \sqrt{\frac{vf}{a(1-\gamma t)}} \\ w(x, y, t) &= 0 \end{aligned} \right\} \text{at} \quad (4)$$

Where  $a$  is the stretching rate of the lower plate. The following appropriate similarity transformations are employed to convert the above governing equations (2)–(4) into a system of ordinary differential equations in terms of a stream function  $\psi$ :

$$\psi = \sqrt{\frac{avf}{1-\gamma t}} x f(\eta), \quad \eta = \frac{y}{h(t)}, \quad (5)$$

$$u = \frac{\partial \psi}{\partial y} = U_0 f'(\eta), \quad v = -\frac{\partial \psi}{\partial x} = -\sqrt{\frac{avf}{1-\gamma t}} f(\eta) \quad (6)$$

$$w = U_0 g(\eta)$$

Substituting the similarity transformations (5) and (6) into (2)-(4), we obtain the following System of nonlinear ordinary differential equations:

$$f''' + \frac{vf}{v_{nf}} (ff'' - (f')^2 - \beta(f' + \frac{\eta}{2} f'')) + Gr\theta + Gm\phi - 2\Omega g - \frac{1}{\rho_{nf} / \rho_f} M^2 f' = \frac{(1-\gamma t)^2 v_f}{\rho_{nf} a^2 x v_{nf}} \frac{\partial p}{\partial x}$$

$$-f'' + \frac{vf}{v_{nf}} (-ff' - \frac{\beta}{2} (f + \eta f'')) = \frac{(1-\gamma t)}{\rho_{nf} a^2 x v_{nf}} \frac{\partial p}{\partial \eta} \quad (7)$$

$$g'' + \frac{vf}{v_{nf}} (fg' - f'g - \beta(g + \frac{\eta}{2} g') + 2\Omega f') - \frac{1}{\mu_{nf} / \mu_f} M^2 g = 0 \quad (8)$$

Where  $\beta = \gamma/a$  is the characteristic parameter of the flow,  $\Omega = \omega/a$  is the rotation parameter,  $M^2 = \sigma B_0^2 / \rho_f a$  is the magnetic parameter, and prime denotes differentiation with respect to  $\eta$ . In order to squeeze the flow, we take  $\beta > 0$ , for which the upper plate moves downward with velocity  $V_h < 0$ . For  $\beta < 0$  the upper plate moves apart with respect to the plane  $y = 0$  and  $\beta = 0$  corresponds to the steady state case of the considered problem or stationary upper plate. In order to reduce the number of independent variables and to retain the similarity solution, (7) are simplified by cross differentiation and thus we obtain the following system of differential equations:

$$f^{iv} - (1-\varphi + \varphi(\rho_s / \rho_f))(1-\varphi)^{2.5} \times (ff'' - ff''' + 2\Omega g' + \frac{\beta}{2} (3f'' + \eta f''')) - (1-\varphi)^{2.5} M^2 f'' = 0$$

$$g'' - (1-\varphi + \varphi(\rho_s / \rho_f))(1-\varphi)^{2.5} \times ((fg' - f'g + \beta(g + \frac{\eta}{2} g') + 2\Omega f')) - (1-\varphi)^{2.5} M^2 g = 0 \quad (9)$$

The transformed boundary conditions take the form

$$\begin{aligned} f(0) &= \omega_0, f'(0) = 1, g(0) = 0, \\ f(1) &= \frac{\beta}{2}, f'(1) = 0, g(1) = 0, \\ \omega_0 &= V_0 / ah \end{aligned} \quad (10)$$

Where  $\omega_0 = V_0 / ah$  is the suction parameter In this problem, the physical quantity of interest is the skin friction coefficients  $C_f$

## International Journal for Research in Applied Science & Engineering Technology (IJRASET)

along the stretching wall at the lower and upper walls which are defined as [13]

$$C_{f,lower} = \frac{\mu_{nf}(\partial u / \partial y)_{y=0}}{\rho_{nf}U_0^2}, \quad (11)$$

$$C_{f,upper} = \frac{\mu_{nf}(\partial u / \partial y)_{y=h(t)}}{\rho_{nf}U_0^2},$$

Substituting (6) into (11) we obtain

$$\bar{C}_{f,lower} =$$

$$C_{f,lower} Re_x = \frac{f''(0)}{(1-\phi + \phi(\rho_s / \rho_f))(1-\phi)^{2.5}},$$

$$\bar{C}_{f,upper} =$$

$$C_{f,upper} Re_x = \frac{f''(1)}{(1-\phi + \phi(\rho_s / \rho_f))(1-\phi)^{2.5}}, \quad (12)$$

Where  $Re_x = \rho_f U_0 h / \mu_f$  is the local Reynolds number. In this section we have derived the coupled system of nonlinear ordinary differential equations (9) to model the three-dimensional flow of a Nano fluid in a rotating channel on a lower permeable stretching wall. We next apply the DTM to solve the coupled system.

### III. NUMERICAL ANALYSIS

In this study is to analyzed Unsteady 3D rotating Nano fluid flow of an Incompressible electronically conducting viscous fluid between two infinite horizontal plane walls investigated Numerically, The governing Navier stokes equations are converted into ordinary differential equations by using similarity transformation. Runge kutta method sixth order by using mathematical software is used to solve the complete system of nonlinear ODE. The non dimensional parameters characteristic parameter of the flow, rotation parameter, the magnetic parameter, nano particle volume fraction, the suction parameter analyzed numerically and graphically with comparison of analytical result.

### IV. RESULTS AND DISCUSSION

In this section we analyzed the clear insight of the Problem. The non-dimensional parameters are Rotation parameter( $\Omega$ ), Characteristic parameter( $\beta$ ), Magnetic parameter( $M$ ), Nano particle volume friction( $\phi$ ) and Suction parameter ( $\omega_0$ ) The Normal velocity  $f(\eta)$  and the transverse velocity  $g(\eta)$  profiles are given graphically

Fig 1 exhibits the schematic diagram of the flow configuration in the physical problem. Fig 2 & Fig 3 shows that the effect of Rotation parameter ( $\Omega$ ) and the Magnetic parameter ( $M$ ) on the transverse velocity profiles ( $g(\eta)$ ).It is observed that, the velocity profiles increases with Increasing values of  $\Omega$  and  $M$

Fig4 & Fig5 shows that the Effect of suction parameter ( $\omega_0$ ) and the nano particle volume fraction ( $\phi$ ) on the transverse velocity profiles  $g(\eta)$ . It is observed that the velocity profile decreases with increasing values of  $\omega_0$  and  $\phi$

Fig6 & Fig7 shows that the effect of Rotation parameter ( $\Omega$ ) and the Magnetic parameter ( $M$ ) On the Normal velocity profiles  $f(\eta)$ .It is observed that the velocity profile decrease with an increasing values of  $\Omega$  and  $M$

Fig 8 & Fig 9 shows that the effect of characteristic parameter ( $\beta$ ) on the normal velocity ( $\eta$ ) and the transverse velocity  $g(\eta)$  profiles both are enhances with increasing values of  $\beta$  ,Fig 10 & Fig 11 shows that the effect of suction parameter ( $\omega_0$ ) and Nano particle volume fraction ( $\phi$ ) on the normal velocity ( $\eta$ ) profiles, It is observed that the velocity profiles increases that increasing values of  $\phi$  and  $\omega_0$

# International Journal for Research in Applied Science & Engineering Technology (IJRASET)




Figure 2: Effect of  $\Omega$  on the transverse velocity of  $g(\eta)$  when  $\beta=1$ ,  $\varphi=0.1$ , and  $M=\omega_0=0.5$ .




Figure 3: Effect of  $\Omega$  on the transverse velocity of  $g(\eta)$  when  $\beta=1$ ,  $\varphi=0.1$ , and  $M=\omega_0=0.5$ .




Figure 4: Effect of  $M$  on the velocity component of  $g(\eta)$  when  $\beta=\Omega=1$ ,  $\varphi=0.1$ , and  $\omega_0=0.5$ .

# International Journal for Research in Applied Science & Engineering Technology (IJRASET)




Figure 5: Effect of  $\omega_0$  on the velocity component of  $g(\eta)$   
when  $\beta = \Omega = 1$ ,  $M = 0.5$ , and  $\varphi = 0.1$ .




Figure 6: Effect of Nano particle types on the velocity component of  $g(\eta)$   
when  $\beta = \Omega = 1$ ,  $M = \omega_0 = 0.5$ , and  $\varphi = 0.1$ .




Figure 7: Effect of  $\beta$  on the velocity component of  $f(\eta)$   
when  $\Omega = 1$ ,  $\varphi = 0.1$ , and  $M = \omega_0 = 0.5$ .

# International Journal for Research in Applied Science & Engineering Technology (IJRASET)




Figure 8: Effect of  $\beta$  on the velocity component of  $g(\eta)$   
 when  $\Omega=1$ ,  $\varphi = 0.1$ , and  $M = \omega_0 = 0.5$ .




Figure 10: Effect of  $\omega_0$  on the velocity component of  $f(\eta)$   
 when  $\beta = \Omega = 1$ ,  $M = 0.5$ , and  $\varphi = 0.1$ .




Figure 11: Effect of Nano particle types on the velocity component of  $f(\eta)$   
 when  $\beta = \Omega = 1$ ,  $M = \omega_0 = 0.5$ , and  $\varphi = 0.1$ .

## V. CONCLUSION



## International Journal for Research in Applied Science & Engineering Technology (IJRASET)

In this paper, we studied the learning on Numerical Analysis of Three-Dimensional Squeezing Nanofluid Flow in a Rotating Channel on a Lower Stretching Porous Wall. The non dimensional parameters characteristic parameter of the flow, the magnetic parameter, nano particle volume fraction, rotation parameter, the suction parameter analyzed numerically and graphically with comparison of analytical result.

### REFERENCES

- [1] S. Munawar, A. Mehmood, and A. Ali, "Three-dimensional squeezing flow in a rotating channel of lower stretching porous wall," *Computers and Mathematics with Applications*, vol. 64, no. 6, pp. 1575–1586, 2012.
- [2] N. Bachok, A. Ishak, and I. Pop, "Flow and heat transfer over a rotating porous disk in a nanofluid," *Physica B: Condensed Matter*, vol. 406, no. 9, pp. 1767–1772, 2011.
- [3] Khairy Zaimia and Anuar Ishak, "Flow and Heat Transfer over a Shrinking Sheet in a Nanofluid with Suction at the Boundary" *AIP Conference Proceedings* 1571, 963 (2013); doi: 10.1063/1.4858778
- [4] K. V. Prasad, D. Pal, V. Umesh, and N. S. P. Rao, "The effect of variable viscosity on MHD viscoelastic fluid flow and heat transfer over a stretching sheet," *Communications in Nonlinear Science and Numerical Simulation*, vol. 15, no. 2, pp. 331–344, 2010.
- [5] A. K. Borkakoti and A. Bharali, "Hydromagnetic flow and heat transfer between two horizontal plates, the lower plate being a stretching sheet," *Quarterly of Applied Mathematics*, vol. 40, no. 4, pp. 461–467, 1983.
- [6] G. Domairry and A. Aziz, "Approximate analysis of MHD squeeze flow between two parallel disks with suction or injection by homotopy perturbation method," *Mathematical Problems in Engineering*, vol. 2009, Article ID 603916, 19 pages, 2009.
- [7] El-Mistikawy, T. M. A. and Attia, H. A. (1990). The rotating disk flow in the presence of strong magnetic field, in *Proceedings of the 3rd International Congress of Fluid Mechanics*, Cairo, Egypt, Jan. 2–4, vol. 3, 1211–1222.
- [8] Syahira Mansur and Anuar Ishak (2014). Unsteady Boundary Layer Flow and Heat Transfer over a Stretching Sheet with a Convective Boundary Condition in a Nanofluid, *AIP Conference Proceedings* 1602, 311 (2014); doi: 10.1063/1.4882504
- [9] A. Mehmood, A. Ali, Analytic homotopy solution of generalized three-dimensional channel flow due to uniform stretching plate, *Acta Mech. Sin.* 23 (2007) 503–510.
- [10] S.U.S.Choi and J.A.Eastman, "Enhancing thermal conductivity of fluids with nanoparticles," *Materials Science*, vol. 231, pp. 99–105, 1995.
- [11] Navid Freidoonimehr, Mohammad Mehdi Rashidi, Analytical Modelling of Three-Dimensional Squeezing Nanofluid Flow in a Rotating Channel on a Lower Stretching Porous Wall. Hindawi Publishing Corporation *Mathematical Problems in Engineering* Volume 2014, Article ID 692728, 14 pages: <http://dx.doi.org/10.1155/2014/692728>
- [12] M. Sheikholeslami, H.R. Ashorynejad, D.D. Ganji, A. Yıldırım, Homotopy perturbation method for three-dimensional problem of condensation film on inclined rotating disk, *Scientia Iranica B* 19 (3) (2012) 437–4
- [13] M. Sheikholeslami, D.D. Ganji, (2012) "Heat transfer of Cu-water nanofluid flow between parallel plates" *Department of Mechanical Engineering, Babol University of Technology, Babol, Iran.* 235 (2013) 873–879
- [14] M. Kurosaka, "The oscillatory boundary layer growth over the top and bottom plates of a rotating channel," *Journal of Fluids Engineering, Transactions of the ASME*, vol. 95, no. 1, pp. 68–74, 1973.
- [15] H. S. Takhar, A. J. Chamkha, and G. Nath, "MHD flow over a moving plate in a rotating fluid with magnetic field, hall currents and free stream velocity," *International Journal of Engineering Science*, vol. 40, no. 13, pp. 1511–1527, 2002.



10.22214/IJRASET



45.98



IMPACT FACTOR:  
7.129



IMPACT FACTOR:  
7.429



# INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24\*7 Support on Whatsapp)