



iJRASET

International Journal For Research in
Applied Science and Engineering Technology



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Volume: 5 Issue: VI Month of publication: June 2017

DOI:

www.ijraset.com

Call:  08813907089

E-mail ID: ijraset@gmail.com

An Approach to Design a Smart Grid Tied System with Increased Efficiency and Reduction of System Complexity for Solar Power

Vikas Kumar Chandra¹, Pranay Kumar Rahi²

¹Asst. Prof. of EEE Department, Chouksey Engineering College Bilaspur,(C.G.)

²Asst. Prof. of EEE Department, Institute of Technology Korba,(C.G.)

Abstract: Energy is vital for the progress of a nation and it has to be con-served in a more efficient manner and reduced system complexity. In this paper we proposed a design of a smart grid system without storage device. This system is capable to feed solar energy to power grid when grid power is available and backup the on-site load as well when the grid power is unavailable. The total system is controlled with the help of some the sensors , converter and a micro-controller. As a whole a significant reduction in the system costs and efficient system performance can be realized.

Keywords: Relay, PV System ,Net Metering, Off Grid System, Grid Tied System.

I. INTRODUCTION

Smart Grid technology is digital technology which have provide effective monitoring,control and distribution of electric power to the consumer via two way digital communication. Power systems are fundamentaly reliant on control, communications, and computation for ensuring stable, reliable, efficient operations

This system is capable to feed solar energy to the utili-ty power grid when grid power is available and backup the on-site load as well when the grid power is unavailable. The Smart Grid will be characterized by a two-way flow of electricity and information to create an automated, widely distributed energy delivery network. It incorporates into the grid the benefits of distributed computing and communications to deliver real-time information and enable the near instantaneous balance of supply and demand at the device level. Smart grid improvements will also integrate with intermittent energy sources that pose a challenge to the current system, like wind and solar power. New technologies will encourage consumers to invest in distributed generation, or locally-generated power sources, such as solar panels on a home, to supplement their power needs.

Making such investments worthwhile to consumers also requires regulatory change to allow different pricing contracts. For example, a home could be powered by its own solar energy during the day, and the consumer could sell any16extra energy produced by his or her panels back to the larger grid (this contract option is called—net metering).

Off Grid System-In this system PV system generats power this power is stored in battery via power conditionar then it can be used as a dc power directly or used as ac power via passing it through inverter but problem with the system is it require large battery and bulk inverter if it is used as dc or ac power and other disadvantage of the system is 30% power loss because it is stored in a battery and transmission losses.




Fig-1 Off Grid System

II. PROPOSED MATHEDODOGY

Grid Tied System-A newly designed grid-tied PV system is shown in Fig.2. Here the grid-tied PV system is consists of an internal processing junction box with its three end point. These are solar power, utility power grid and Residential load. Here this system always tries to feed the solar power to the utility power grid. At the same time the residential load will consume the power from the utility power grid. But if the grid power is unavaila-ble then the residential load demand will be supplied by the solar power.

International Journal for Research in Applied Science & Engineering Technology (IJRASET)




Fig -2 Grid Tied System

III. PRINCIPLE OF WORKING

If power is available in the grid The operation of the system is completely depends upon the two relay and their working method (normally Open and normally Closed). First solar panel is produces solar power then it is well conditioned by various power conditioners. The power produced by power conditioner is then supplied to utility grid this can be done when relay 1 is in normally opened mode and at the same time residential loads will be supplied by utility grid if relay 2 is normally closed mode and power is available in grid. If power is not available in grid residential loads will be supplied by directly from the solar panel by normally closed of relay 1 and normally opened by relay 2. Again if there is any overloading situation due to the residential load the relay 1 will be operate to normally closed the connection and ensure the safety of the system. At the same time it will generate a signal to the consumer for reducing the load. This is how the system will operate with a most efficient manner.





Fig-3 Principle of working by using two relay

IV. CONTROL SYSTEM OF METHEDODOGY

The system block diagram consists of solar PV array, MPPT charge controller, DC to DC converter, High efficient Grid Tie inverter, AC three phase synchronizer, Microcontroller, DC power measuring device, CT, PT, ADC (Analogue to Digital converter), Relays and Metering device. We can describe all those elements in three parts. The power output of a PV array depends on the voltage level where it operates under a given condition of irradiance and cell-surface temperature. For efficient operation, a PV array should operate near at the peak point of. Various Maximum Power Tracking (MPPT) techniques have been proposed. The MPPT device of the block diagram in always tries to stable the PV output voltage and also ensure the maximum power output of the PV system.



International Journal for Research in Applied Science & Engineering Technology (IJRASET)

The inverter is the heart of the PV system and is the focus of all utility-interconnection. An inverter is a device that converts direct current to alternating current. The PV inverters are classified into two categories, Stand Alone Type and Synchronous Grid Tie Type. Synchronous inverter is a special type of inverter which is specially designed for solar panel. This type of inverter always collect the data of voltage and frequency of utility power grid by a AC synchronizer and synchronize the inverter output with the utility power grid. So that, it is possible to install a medium to large-size PV array.

V. CONCLUSION

This paper is proposed a methodology which can identify the benefit of designing a user (utility and industry) friendly system that increases the efficiency and reliability by promoting two-way communication to optimally exchange the available electricity with the help of smart grid technologies. System lambda which is the minimum cost of producing the next megawatt hour by a typical utility is determined. Utility and Industry operations, and them earning of Integrated Industrial Electric System. Brief notes on Smart Grid, its Technologies and the anticipated saving with the use of these technologies is presented.

REFERENCES

- [1] M. Mehedi Farhad, M. Mohammad Ali, M. Asif Iqbal, N. Nahar Islam, N. Ashraf, International Journal of Advancements in Research & Technology, Volume 1, Issue6, November-2012 ISSN 2278-7763 A New Approach to Design of an optimized Grid Tied Smart Solar Photovoltaic (PV) System
- [2] Islam Sharif—Renewable energy development in Bangladesh, Ex-ecutive Exchange on the use and integration of Renewable Energy in the Power Sector, Madrid, Spain, October 19-23, 2003
- [3] P.Naglaxmi,M.Veda Chary,International Journal of Morden Research,Vol. 3 Issue.5 sep- oct 2013 pp2836-2839 ISSN:2249-6645 ,Efficient energy manegment system with solar energy
- [4] Blume, Steven W. Electric Power System Basics. s.l. : Wiley IEEE, 2007. Vol. 32. 0470129875,9780470129876
- [5] L. H. Tsoukalas and R. Gao, "From smart grids to an energy internet:Assumptions, architectures, and requirements," in Proc. of Third Int'l.Conf. on Electric Utility Deregulation and Restructuring and Power Technologies, Nanjing, China, Apr. 2008.
- [6] D. Kearney. "Solar Electric Generating Stations (SEGS)," IEEE Power Engineering Review, vol. 9, no. 8, pp. 4–8, 1989. doi:10.1109/MPER.1989.4310850.
- [7] K. H. Hussein, —Maximum photovoltaic power tracking: An algo-rithm for rapidly changing atmospheric conditions, Proc. Inst. Electr. Eng.—Generation, Transmission, Distribution, vol. 142, no. 1, pp. 59–64, Jan. 1995.K. Elissa,—An Overview of Decision Theory," unpublished. (Unpublished manuscript).
- [8] M. Gohul, T. Jayach, A. M. Ali, T. G. Raju, N.Santhosh Kumar, M.R. Saravanan, —A new design of grid tie inverter for a grid interactive so-lar photovoltaic power generation-An alternative option for energy conservation & security IJJECT Vol. .2, Issue 3, Sept.2011.
- [9] Richard E.Brown,fellow,Impact of smart grid on distribution system design.



10.22214/IJRASET



45.98



IMPACT FACTOR:
7.129



IMPACT FACTOR:
7.429



INTERNATIONAL JOURNAL FOR RESEARCH

IN APPLIED SCIENCE & ENGINEERING TECHNOLOGY

Call : 08813907089  (24*7 Support on Whatsapp)